


MARK	DATE	REMARKS
\triangle		
2		







P.C.B DIMENSION (TOP VIEW)

SPECIFICATION

1. Rating: 150mA, 42V DC (Switching)

200mA, 42V DC (None-Switching)

Contact Resistance: 80mΩ Max
Insulation Resistance: 100MΩ Min

4. Operating Force: 700gf Max

5. Life cycle: 10,000 steps

				Real	Code		
			С	1	2	4	8
	10 P o s i t i o n	0	•				
		1	•	•			
		2	•		•		
		3	•	•	•		
		4	•			•	
		5	•	•		•	
		6	•		•	•	
		7	•	•	•	•	
		8	•				•
10		9	•	•			•
16 P o s i		Α	•		•		•
0		В	•	•	•		•
i		С	•			•	•
t i o n		D	•	•		•	•
		Ε	•		•	•	•
		F	•	•	•	•	•

APPD	CHKD	D'SGD	TITLE. ROTARY DIP SWITCH				
K.L. LEE	J.P ROH	Y.N. JEON	MODEL NO.	FDR-10H	REV	02	
	0.1 11011	2018.07.04	SUNGMUN ELECTRONICS CO., LTD.				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Coded Rotary Switches category:

Click to view products by Sungmun manufacturer:

Other Similar products are found below:

PT65SG178 PT65SG23 DRS4010 CW1S-2E11 S-1031A SBS1004 P36S101TR P65THR101L254 RM3AF-10R-V-T/R RH3HAF-10R-V-B PT65501RT P25SMT101TR P65SMT101 P65THR101V MSDR-10H1 GSDR-10S 01-1433 07-3153 07-3154 CRD10CM0SBR DRS4116 94HCB16RAT 94HCB10T 94HBB16WT 94HBB16RAT 94HBB10WT 94HBB10WAT 94HBB10WAT 94HBB08RAT 94HAC10T 94HAB16WT 94HAB16WT 94HAB10WAT 94H