

# Multilayer Chip High Q Inductor – HQ1005C Series

Operating Temp. : -55°C~+125°C



## FEATURES

- Monolithic structure for high reliability
- High self-resonant frequency
- Excellent solderability and high heat resistance
- High Q value correspond to wire wound inductor

## APPLICATIONS

- RF circuit in telecommunication and other Equipments
- Mobile phones such as GSM, CDMA, TD-LTE, FDD-LTE, PDC, 5GNR, etc.
- Bluetooth, W-LAN

## PRODUCT IDENTIFICATION

**HQ**

①

①

| Type |                      |
|------|----------------------|
| HQ   | Chip High Q Inductor |

**1005**

②

**C**

③

②

| External Dimensions (L×W) (mm) |         |
|--------------------------------|---------|
| 1005 [0402]                    | 1.0×0.5 |

**3N9**

④

④

| Nominal Inductance |               |
|--------------------|---------------|
| Example            | Nominal Value |
| 3N9                | 3.9nH         |
| 10N                | 10nH          |
| ※N=nH              |               |

⑤

| Inductance Tolerance |        |
|----------------------|--------|
| B                    | ±0.1nH |
| C                    | ±0.2nH |
| S                    | ±0.3nH |
| G                    | ±2%    |
| H                    | ±3%    |
| J                    | ±5%    |

**S**

⑤

③

| Material Code |  |
|---------------|--|
| C             |  |


**T**

⑥

⑥

| Packing |             |
|---------|-------------|
| T       | Tape & Reel |

## SHAPE AND DIMENSIONS



Unit: mm [inch]

| Type             | L                         | W                         | T                         | a                         |
|------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| HQ1005<br>[0402] | 1.0±0.15<br>[0.039±0.006] | 0.6±0.15<br>[0.024±0.006] | 0.5±0.15<br>[0.020±0.006] | 0.25±0.1<br>[0.010±0.004] |

# SPECIFICATIONS

## HQ1005 TYPE

| Part Number  | Inductance | Min. Quality Factor | L, Q Test Freq. L/Q | Typical Q @ Freq. (MHz) |     |     |      | Min. Self-resonance Frequency | Max. DC Resistance | Max. Rated Current | Thickness               |
|--------------|------------|---------------------|---------------------|-------------------------|-----|-----|------|-------------------------------|--------------------|--------------------|-------------------------|
|              |            |                     |                     | 100                     | 250 | 900 | 1800 |                               |                    |                    |                         |
| Units        | nH         | -                   | MHz                 | -                       |     |     |      | MHz                           | $\Omega$           | mA                 | mm [inch]               |
| Symbol       | L          | Q                   | Freq                | Q                       |     |     |      | SRF                           | DCR                | Ir                 | T                       |
| HQ1005C1N0□T | 1.0        | 20                  | 250                 | 13                      | 22  | 48  | 75   | 6000                          | 0.05               | 1000               | 0.5±0.15<br>[.020±.006] |
| HQ1005C1N2□T | 1.2        | 20                  | 250                 | 13                      | 22  | 48  | 75   | 6000                          | 0.05               | 1000               |                         |
| HQ1005C1N5□T | 1.5        | 20                  | 250                 | 13                      | 22  | 58  | 76   | 6000                          | 0.05               | 1000               |                         |
| HQ1005C1N8□T | 1.8        | 20                  | 250                 | 13                      | 22  | 49  | 78   | 6000                          | 0.07               | 800                |                         |
| HQ1005C2N0□T | 2.0        | 20                  | 250                 | 14                      | 23  | 49  | 82   | 6000                          | 0.07               | 800                |                         |
| HQ1005C2N2□T | 2.2        | 20                  | 250                 | 14                      | 23  | 49  | 82   | 6000                          | 0.07               | 800                |                         |
| HQ1005C2N4□T | 2.4        | 20                  | 250                 | 14                      | 23  | 47  | 78   | 6000                          | 0.07               | 800                |                         |
| HQ1005C2N5□T | 2.5        | 20                  | 250                 | 14                      | 23  | 47  | 78   | 6000                          | 0.07               | 800                |                         |
| HQ1005C2N7□T | 2.7        | 20                  | 250                 | 14                      | 23  | 48  | 82   | 6000                          | 0.09               | 700                |                         |
| HQ1005C2N9□T | 2.9        | 20                  | 250                 | 14                      | 23  | 48  | 82   | 6000                          | 0.09               | 700                |                         |
| HQ1005C3N0□T | 3.0        | 20                  | 250                 | 14                      | 23  | 50  | 84   | 6000                          | 0.09               | 700                |                         |
| HQ1005C3N3□T | 3.3        | 20                  | 250                 | 14                      | 24  | 52  | 90   | 6000                          | 0.09               | 700                |                         |
| HQ1005C3N6□T | 3.6        | 20                  | 250                 | 15                      | 24  | 55  | 95   | 6000                          | 0.10               | 700                |                         |
| HQ1005C3N9□T | 3.9        | 20                  | 250                 | 15                      | 25  | 50  | 89   | 6000                          | 0.10               | 700                |                         |
| HQ1005C4N1□T | 4.1        | 20                  | 250                 | 15                      | 25  | 49  | 86   | 6000                          | 0.12               | 650                |                         |
| HQ1005C4N3□T | 4.3        | 20                  | 250                 | 15                      | 25  | 49  | 86   | 6000                          | 0.13               | 600                |                         |
| HQ1005C4N7□T | 4.7        | 20                  | 250                 | 15                      | 26  | 50  | 88   | 6000                          | 0.13               | 600                |                         |
| HQ1005C5N1□T | 5.1        | 20                  | 250                 | 15                      | 26  | 49  | 84   | 5500                          | 0.13               | 600                |                         |
| HQ1005C5N6□T | 5.6        | 20                  | 250                 | 15                      | 27  | 50  | 84   | 5500                          | 0.13               | 600                |                         |
| HQ1005C5N8□T | 5.8        | 20                  | 250                 | 15                      | 27  | 50  | 82   | 5500                          | 0.13               | 600                |                         |
| HQ1005C6N2□T | 6.2        | 20                  | 250                 | 15                      | 27  | 50  | 80   | 5500                          | 0.14               | 550                |                         |
| HQ1005C6N8□T | 6.8        | 22                  | 250                 | 15                      | 27  | 55  | 89   | 5000                          | 0.15               | 550                |                         |
| HQ1005C7N3□T | 7.3        | 22                  | 250                 | 15                      | 27  | 54  | 90   | 5000                          | 0.16               | 550                |                         |
| HQ1005C7N5□T | 7.5        | 22                  | 250                 | 15                      | 27  | 54  | 90   | 5000                          | 0.16               | 550                |                         |
| HQ1005C8N2□T | 8.2        | 22                  | 250                 | 15                      | 27  | 56  | 84   | 5000                          | 0.16               | 550                |                         |
| HQ1005C8N7□T | 8.7        | 22                  | 250                 | 15                      | 27  | 53  | 80   | 5000                          | 0.17               | 500                |                         |
| HQ1005C9N1□T | 9.1        | 22                  | 250                 | 15                      | 27  | 53  | 79   | 4500                          | 0.18               | 500                |                         |
| HQ1005C9N5□T | 9.5        | 22                  | 250                 | 15                      | 27  | 52  | 77   | 4500                          | 0.18               | 500                |                         |
| HQ1005C10N□T | 10         | 22                  | 250                 | 16                      | 29  | 52  | 75   | 4500                          | 0.18               | 500                |                         |
| HQ1005C11N□T | 11         | 22                  | 250                 | 16                      | 28  | 52  | 71   | 4000                          | 0.20               | 500                |                         |
| HQ1005C12N□T | 12         | 22                  | 250                 | 16                      | 29  | 51  | 68   | 4000                          | 0.20               | 500                |                         |
| HQ1005C15N□T | 15         | 22                  | 250                 | 16                      | 29  | 50  | 60   | 4000                          | 0.22               | 430                |                         |


※□: Please specify the inductance tolerance. For  $L \leq 6.2\text{nH}$ , choose  $B = \pm 0.1\text{nH}$  or  $C = \pm 0.2\text{nH}$  or  $S = \pm 0.3\text{nH}$ ; For  $L > 6.2\text{nH}$ , choose  $G = \pm 2\%$  or  $H = \pm 3\%$  or  $J = \pm 5\%$ .

※: Please refer to "Measurement Notice For RF Inductors".


## TYPICAL ELECTRICAL CHARACTERISTICS

### HQ1005 TYPE

Inductance vs. Frequency Characteristics



Q vs. Frequency Characteristics



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Fixed Inductors](#) category:*

*Click to view products by [Sunlord](#) manufacturer:*

Other Similar products are found below :

[CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#) [RCR1010NP-470M](#)