

Multilayer Chip Power Inductor – MCL-A Series

Operating Temp. : -40°C~+125°C



FEATURES

- Monolithic structure for high reliability
- Excellent solderability and high heat resistance
- No cross coupling due to magnetic shield
- High DC bias current due to developed material
- Low DC resistance

APPLICATIONS


- DC-DC converter circuits for mobile phones, wearable devices, DVCs, HDDs, etc

PRODUCT IDENTIFICATION

<u>MCL</u>	<u>2012</u>	<u>A</u>	<u>2R2</u>	<u>M</u>	<u>T</u>																
①	②	③	④	⑤	⑥																
①		②			③																
<table border="1"> <tr><th colspan="2">Type</th></tr> <tr><td>MCL</td><td>Chip Power Inductor</td></tr> </table>	Type		MCL	Chip Power Inductor		<table border="1"> <tr><th colspan="2">External Dimensions (LxW) (mm)</th></tr> <tr><td>2012 [0805]</td><td>2.0x1.25</td></tr> <tr><td>2016 [0806]</td><td>2.0x1.6</td></tr> <tr><td>2520 [1008]</td><td>2.5x2.0</td></tr> </table>	External Dimensions (LxW) (mm)		2012 [0805]	2.0x1.25	2016 [0806]	2.0x1.6	2520 [1008]	2.5x2.0			<table border="1"> <tr><th colspan="2">Feature Type</th></tr> <tr><td>A</td><td>Inner Code</td></tr> </table>	Feature Type		A	Inner Code
Type																					
MCL	Chip Power Inductor																				
External Dimensions (LxW) (mm)																					
2012 [0805]	2.0x1.25																				
2016 [0806]	2.0x1.6																				
2520 [1008]	2.5x2.0																				
Feature Type																					
A	Inner Code																				
④		⑤			⑥																
<table border="1"> <tr><th colspan="2">Nominal Inductance</th></tr> <tr><th>Example</th><th>Nominal Value</th></tr> <tr><td>2R2</td><td>2.2μH</td></tr> <tr><td colspan="2">※R= decimal point</td></tr> </table>	Nominal Inductance		Example	Nominal Value	2R2	2.2μH	※R= decimal point			<table border="1"> <tr><th colspan="2">Inductance Tolerance</th></tr> <tr><td>M</td><td>±20%</td></tr> </table>	Inductance Tolerance		M	±20%			<table border="1"> <tr><th colspan="2">包装 Packing</th></tr> <tr><td>T</td><td>编带 Tape & Reel</td></tr> </table>	包装 Packing		T	编带 Tape & Reel
Nominal Inductance																					
Example	Nominal Value																				
2R2	2.2μH																				
※R= decimal point																					
Inductance Tolerance																					
M	±20%																				
包装 Packing																					
T	编带 Tape & Reel																				

SHAPE AND DIMENSIONS

Unit: mm [inch]



Type	L	W	T	a
MCL2012-A [0805]	2.0 (+0.3, -0.1) [.079 (+.012, -.004)]	1.25±0.2 [.049±.008]	0.85±0.2 [.033±.008]	0.5±0.3 [.020±.012]
MCL2016-A [0806]	2.0 (+0.3, -0.1) [.079 (+.012, -.004)]	1.6±0.2 [.063±.008]	0.9±0.1 [.035±.004]	0.5±0.3 [.020±.012]
MCL2520-A [1008]	2.5±0.2 [.098±.008]	2.0(+0.3, -0.1) [.079(+.012, -.004)]	0.9±0.1 [.035±.004]	0.5±0.3 [.020±.012]

SPECIFICATIONS

MCL2012A TYPE

Part Number	Inductance	L Test Freq.	DC Resistance		Min. Self-resonant Frequency	Saturation Current Typ.	Heat Rating Current Max.
Units	μH	MHz	Ω		MHz	A	A
Symbol	L	Freq.	DCR		S.R.F	Isat	Irms
			Max.	Typ.			
MCL2012A1R0MT	1.0	1	0.150	0.120	120	0.45	1.45
MCL2012A1R5MT	1.5	1	0.187	0.150	90	0.35	1.35
MCL2012A2R2MT	2.2	1	0.225	0.180	70	0.30	1.30
MCL2012A3R3MT	3.3	1	0.312	0.250	55	0.21	0.90
MCL2012A4R7MT	4.7	1	0.375	0.300	50	0.18	0.85
MCL2012A100MT	10	1	0.500	0.400	35	0.15	0.40

MCL2016A TYPE

Part Number	Inductance	L Test Freq.	DC Resistance		Min. Self-resonant Frequency	Saturation Current Typ.	Heat Rating Current Max.
Units	μH	MHz	Ω		MHz	A	A
Symbol	L	Freq.	DCR		S.R.F	Isat	Irms
			Max.	Typ.			
MCL2016A1R0MT	1.0	1	0.175	0.140	120	0.90	1.10
MCL2016A1R5MT	1.5	1	0.200	0.160	100	0.55	1.00
MCL2016A2R2MT	2.2	1	0.275	0.220	70	0.60	0.85
MCL2016A4R7MT	4.7	1	0.200	0.160	50	0.10	1.20

MCL2520A TYPE

Part Number	Inductance	L Test Freq.	DC Resistance		Min. Self-resonant Frequency	Saturation Current Typ.	Heat Rating Current Max.
Units	μH	MHz	Ω		MHz	A	A
Symbol	L	Freq.	DCR		S.R.F	Isat	Irms
			Max.	Typ.			
MCL2520A1R0MT	1.0	1	0.100	0.080	100	0.75	1.15
MCL2520A1R5MT	1.5	1	0.137	0.110	85	0.60	1.00
MCL2520A2R2MT	2.2	1	0.162	0.130	70	0.50	1.40
MCL2520A4R7MT	4.7	1	0.350	0.280	45	0.25	0.95

※Rated current: Isat or Irms, whichever is smaller;

※Isat: DC current at which the inductance drops approximate 30% from its value without current;

※Irms : DC current that causes the temperature rise ($\Delta T = 40^{\circ}\text{C}$) from 20°C ambient.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [Sunlord](#) manufacturer:

Other Similar products are found below :

[CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#) [RCR1010NP-470M](#)