

Multilayer Chip Ceramic Inductor - SDCL0603Q-02 Series

Operating Temp. : SDCL0603Q-02 series: -55°C~+125°C



FEATURES

- Monolithic structure for high reliability
- High self-resonant frequency
- Excellent solderability and high heat resistance
- High Q factor

APPLICATIONS

- RF circuit in telecommunication and other equipments

PRODUCT IDENTIFICATION

SDCL

①

Type	
SDCL	Chip Ceramic Inductor

0603

②

Q

③

External Dimensions (L×W) (mm)	
0603 [0201]	0.6×0.3

10N

④

④

Nominal Inductance	
Example	Nominal Value
3N9	3.9nH
10N	10nH
※R=, N=nH	

⑤

Inductance Tolerance	
B	±0.1nH
C	±0.2nH
S	±0.3nH
G	±2%
H	±3%
J	±5%

J

⑤

T

⑥

③

Characteristics Code	
Q	

02

⑦


⑥

Packing	
T	Tape & Reel

⑦

Serial Code	
02	

SHAPE AND DIMENSIONS



Unit: mm [inch]				
Type	L	W	T	a
SDCL0603Q-02	0.6±0.05	0.3±0.05	0.3±0.05	0.12±0.05
[0201]	[.024±.002]	[.012±.002]	[.012±.002]	[.0048±.002]

SPECIFICATIONS

SDCL0603Q-02 Series

Part Number	Inductance	Min. Quality Factor	L, Q Test Freq. L/Q	Typical Q @ Freq. (GHz)					Min. Self-resonant Frequency	Max. DC Resistance	Max. Rated Current
				0.5	0.8	1.8	2.0	2.4			
Units	nH	-	MHz	-					MHz	Ω	mA
Symbol	L	Q	Freq	Q					S.R.F	DCR	Ir
SDCL0603Q0N6□T02	0.6	13	500	>24	>32	>54	>57	>65	10000	0.06	600
SDCL0603Q0N7□T02	0.7	13	500	>24	>32	>54	>57	>65	10000	0.06	550
SDCL0603Q0N8□T02	0.8	13	500	>24	>32	>54	>57	>65	10000	0.07	550
SDCL0603Q0N9□T02	0.9	13	500	>24	>32	>54	>57	>65	10000	0.07	550
SDCL0603Q1N0□T02	1.0	13	500	24	32	54	57	65	10000	0.08	520
SDCL0603Q1N1□T02	1.1	13	500	19	26	45	47	55	10000	0.11	440
SDCL0603Q1N2□T02	1.2	13	500	19	25	43	44	52	10000	0.12	420
SDCL0603Q1N3□T02	1.3	13	500	19	25	40	42	47	10000	0.12	420
SDCL0603Q1N4□T02	1.4	13	500	19	24	39	41	47	10000	0.11	440
SDCL0603Q1N5□T02	1.5	13	500	19	24	39	41	46	10000	0.12	420
SDCL0603Q1N6□T02	1.6	13	500	19	24	39	41	46	10000	0.13	410
SDCL0603Q1N7□T02	1.7	13	500	19	24	39	41	46	10000	0.15	380
SDCL0603Q1N8□T02	1.8	13	500	19	24	39	41	46	10000	0.15	380
SDCL0603Q1N9□T02	1.9	13	500	18	24	38	40	45	10000	0.18	350
SDCL0603Q2N0□T02	2.0	13	500	17	24	38	39	44	10000	0.23	300
SDCL0603Q2N1□T02	2.1	13	500	17	24	37	39	44	10000	0.24	300
SDCL0603Q2N2□T02	2.2	13	500	17	24	38	40	43	10000	0.25	290
SDCL0603Q2N3□T02	2.3	13	500	17	24	37	39	43	10000	0.20	330
SDCL0603Q2N4□T02	2.4	13	500	17	23	36	38	42	10000	0.22	310
SDCL0603Q2N5□T02	2.5	13	500	17	23	35	36	40	9600	0.20	330
SDCL0603Q2N6□T02	2.6	13	500	17	22	34	35	39	9400	0.20	330
SDCL0603Q2N7□T02	2.7	13	500	17	22	34	35	39	9200	0.22	310
SDCL0603Q2N8□T02	2.8	13	500	17	22	34	35	39	8900	0.24	300
SDCL0603Q2N9□T02	2.9	13	500	17	22	34	35	39	8800	0.26	280
SDCL0603Q3N0□T02	3.0	13	500	17	22	34	35	39	8600	0.26	280
SDCL0603Q3N1□T02	3.1	13	500	17	22	34	35	39	8500	0.28	270
SDCL0603Q3N2□T02	3.2	13	500	17	22	33	35	39	8200	0.28	270
SDCL0603Q3N3□T02	3.3	13	500	18	23	34	36	40	8100	0.30	270
SDCL0603Q3N4□T02	3.4	13	500	17	23	33	35	39	8000	0.30	270
SDCL0603Q3N5□T02	3.5	13	500	17	23	33	35	39	7900	0.34	250
SDCL0603Q3N6□T02	3.6	13	500	16	23	33	35	39	7700	0.38	240
SDCL0603Q3N7□T02	3.7	13	500	16	23	33	35	38	7600	0.40	230
SDCL0603Q3N8□T02	3.8	13	500	16	22	33	35	38	7500	0.42	230
SDCL0603Q3N9□T02	3.9	13	500	16	22	33	35	38	7400	0.42	230
SDCL0603Q4N3□T02	4.3	13	500	16	21	32	34	37	6800	0.44	220
SDCL0603Q4N7□T02	4.7	13	500	16	22	33	35	38	6200	0.45	220
SDCL0603Q5N1□T02	5.1	13	500	17	22	34	36	38	5900	0.46	210
SDCL0603Q5N6□T02	5.6	13	500	16	21	33	34	37	5500	0.46	210
SDCL0603Q6N2□T02	6.2	13	500	18	23	34	35	37	5100	0.48	210
SDCL0603Q6N8□T02	6.8	13	500	17	22	32	33	35	4900	0.50	200
SDCL0603Q7N5□T02	7.5	13	500	16	21	31	33	34	4700	0.50	200
SDCL0603Q8N2□T02	8.2	13	500	16	21	31	32	34	4300	0.56	190
SDCL0603Q9N1□T02	9.1	13	500	16	20	30	31	32	4100	0.72	170
SDCL0603Q10N□T02	10	13	500	16	20	28	29	31	3800	0.80	160
SDCL0603Q12N□T02	12	13	500	16	20	27	28	28	3400	0.80	160

SPECIFICATIONS

SDCL0603Q-02 Series

Part Number	Inductance	Min. Quality Factor	L, Q Test Freq. L/Q	Typical Q @ Freq. (GHz)					Min. Self-resonant Frequency	Max. DC Resistance	Max. Rated Current
				0.5	0.8	1.8	2.0	2.4			
Units	nH	-	MHz	-					MHz	Ω	mA
Symbol	L	Q	Freq.	Q					S.R.F	DCR	I _r
SDCL0603Q15N□T02	15	13	500	15	19	24	24	23	2600	0.85	160
SDCL0603Q18N□T02	18	13	500	15	19	23	24	22	2300	1.00	140
SDCL0603Q22N□T02	22	13	500	15	19	22	23	20	1900	1.20	130
SDCL0603Q27N□T02	27	13	500	15	19	15	13	8	1800	1.60	120
SDCL0603Q33N□T02	33	11	300	14	15	8	5	-	1800	2.20	110
SDCL0603Q39N□T02	39	11	300	14	15	6	-	-	1600	2.30	100
SDCL0603Q47N□T02	47	11	300	14	15	-	-	-	1500	2.60	100
SDCL0603Q56N□T02	56	11	300	13	13	-	-	-	1400	2.80	80
SDCL0603Q68N□T02	68	11	300	13	11	-	-	-	1200	3.20	80
SDCL0603Q82N□T02	82	10	300	12	10	-	-	-	1100	3.80	70
SDCL0603QR10□T02	100	10	300	12	10	-	-	-	1000	4.00	60
SDCL0603QR12□T02	120	9	300	12	8	-	-	-	1000	5.00	50

※□: Please specify the inductance tolerance. For L≤6.2nH, choose B=±0.1nH,C=±0.2nH or S=±0.3nH; For L>6.2nH, choose G=±2%, H=±3% or J=±5%.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [Sunlord](#) manufacturer:

Other Similar products are found below :

[CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#) [RCR1010NP-470M](#)