

Multilayer Chip Balanced Filter – SLFBF Series

Operating Temp. : -40°C~+85°C



FEATURES

- Small size, enable high density mounting
- Low insertion loss, high attenuation
- Surface mount type, high reliability

APPLICATIONS

- Mobile communication system, such as GSM, DCS, PCS, etc.
- Bluetooth, WLAN

PRODUCT IDENTIFICATION

SLFBF

①

21

②

-2R450G

③

-B01

④

T

⑤

①

Type	
SLFBF	Balanced Filter

②

External Dimensions (LxW) (mm)	
21 [0805]	2.0x1.2

③

Center Frequency	
Example	Nominal Value
2R450G	2450.0MHz

④

Series Code
A02, A11, A21, B01

⑤

Packing
T Tape Carrier Package

SHAPE AND DIMENSIONS

Type: SLFBF21 Series	Dimensions and Land Patterns
	<p>(1): Unbalance Port (2): NC(DC feed Port) (3): NC (4)(6)(8): GND (5)(7): Balance Port M: MARK Unit:mm</p>

SPECIFICATIONS

SLFBF21 TYPE

Part Number	Unbalance Port Impedance	Balance Port Impedance	Frequency Range	Insertion Loss	Attenuation	Unbalance Port VSWR in BW	Balance Port VSWR in BW	Power Capacity
Units	Ω	Ω	MHz	dB	dB	-	-	mW
SLFBF21-2R450G-A11T	50	Conjugate match to MTK5931	2450±50	2.5dB Max. at 25°C	35.0dB Min. at 880~960MHz	2.0 Max.	2.0 Max.	500.0 Max.
					30.0dB Min. at 1710~1880MHz			
				2.6dB Max. at -40 to +85°C	20.0dB Min. at 1880~1990MHz			
					20.0dB Min. at 4800~5000MHz			
				2.0dB Max. at -40 to +85°C	25.0dB Min. at 7200~7500MHz			
					20.0dB Min. at 7200~7500MHz			
2.0dB Max. at -40 to +85°C	15.0dB Min. at 7200~7500MHz							
	15.0dB Min. at 3450~3880MHz							
2.8dB Max. at -40 to +85 °C	15.0dB Min. at 10360~11650MHz							
SLFBF21-2R450G-B01T	50	Conjugate match to CSR BC04, BC05	2450±50	3.4dB Max. at 25°C	45.0dB Min. at 880~960MHz	2.0 Max	2.0 Max	500.0 Max.
					30.0dB Min. at 1710~1880MHz			
				3.7dB Max. at -40 to +85°C	20.0dB Min. at 1880~1990MHz			
					20.0dB Min. at 4800~5000MHz			
20.0dB Min. at 7200~7500MHz								

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Signal Conditioning](#) category:

Click to view products by [Sunlord](#) manufacturer:

Other Similar products are found below :

[MAPDCC0004](#) [PD0409J5050S2HF](#) [880157](#) [HHS-109-PIN](#) [DC1417J5005AHF](#) [DC4859J5005AHF](#) [AFS14A30-2185.00-T3](#) [AFS14A35-1591.50-T3](#) [DS-323-PIN](#) [DSS-313-PIN](#) [B39321R801H210](#) [B39321R821H210](#) [B39921B4317P810](#) [1A0220-3](#) [2089-6207-00](#) [JP510S](#) [LFB212G45SG8C341](#) [LFB322G45SN1A504](#) [LFL182G45TC3B746](#) [SF2159E](#) [30057](#) [1P510S](#) [CER0813B](#) [3A325](#) [40287](#) [41180](#) [ATB3225-75032NCT](#) [B69842N5807A150](#) [BD0810N50100AHF](#) [BD2326L50200AHF](#) [BD2425J50200AHF](#) [HMC189AMS8TR](#) [C5060J5003AHF](#) [JHS-114-PIN](#) [JP503AS](#) [DC0710J5005AHF](#) [DC2327J5005AHF](#) [DC3338J5005AHF](#) [43020](#) [LFB2H2G60BB1C106](#) [LFL15869MTC1B787](#) [X3C19F1-20S](#) [XC3500P-20S](#) [10013-20](#) [SF2081E](#) [SF2194E](#) [SF2238E](#) [CDBLB455KCAX39-B0](#) [RF1353C](#) [PD0922J5050D2HF](#)