

**IEC320-C7 (EU)**

|                   |                          |
|-------------------|--------------------------|
| Country of Origin | China                    |
| RoHS              | yes                      |
| Application       | For Class II. Appliances |
| Approvals         | ENEC                     |

|                  |                              |                     |
|------------------|------------------------------|---------------------|
| Length/cord      | 1.8m / 2x0.75mm <sup>2</sup> |                     |
| Plug             | SP-021A 2,5A/250V            |                     |
| Connector        | IS-033 2,5A/250V             |                     |
| Rating           | 300/300V 70°C                |                     |
| Flex cord        | H03VVH2-F                    |                     |
| WEIGHT / PACKING | 1pc                          | N.W.: 82 g / pc     |
|                  | BOX                          | 200 pcs / 1box      |
|                  |                              | G.W.: 17,3 kg / box |
|                  |                              | 0.55x0.36x0.20 [m]  |



Available also in white version

**IEC320-C7 (UK)**

|                   |                          |
|-------------------|--------------------------|
| Country of Origin | China                    |
| RoHS              | yes                      |
| Application       | For Class II. Appliances |
| Approvals         | ASTA, Singapore, ENEC    |

|                  |                              |                     |
|------------------|------------------------------|---------------------|
| Length/cord      | 1.8m / 2x0.75mm <sup>2</sup> |                     |
| Plug             | SP-62 5A/250V                |                     |
| Connector        | IS-033 2,5A/250V             |                     |
| Fuse             | 5A                           |                     |
| Rating           | 300/300V 70°C                |                     |
| Flex cord        | H03VVH2-F                    |                     |
| WEIGHT / PACKING | 1pc                          | N.W.: 146 g / pc    |
|                  | BOX                          | 100 pcs / 1box      |
|                  |                              | G.W.: 14,6 kg / box |
|                  |                              | 0.55x0.36x0.20 [m]  |


**IEC320-C7 (USA)**

|                   |                          |
|-------------------|--------------------------|
| Country of Origin | China                    |
| RoHS              | yes                      |
| Application       | For Class II. Appliances |
| Approvals         | UL, CSA                  |

|                  |                              |                     |
|------------------|------------------------------|---------------------|
| Length/cord      | 1.8m / 2x0.75mm <sup>2</sup> |                     |
| Plug             | SP-12N 7A/125V               |                     |
| Connector        | IS-033 7A/125V               |                     |
| Rating           | 300V 105°C                   |                     |
| Flex cord        | SPT-1                        |                     |
| WEIGHT / PACKING | 1pc                          | N.W.: 71 g / pc     |
|                  | BOX                          | 200 pcs / 1box      |
|                  |                              | G.W.: 14,7 kg / box |
|                  |                              | 0.55x0.36x0.20 [m]  |



**IEC320-C7 (Aus)**

Country of Origin      China  
 RoHS                      yes  
 Application              For Class II. Appliances  
 Approvals                SAA

|                  |     |                              |
|------------------|-----|------------------------------|
| Length/cord      |     | 1.8m / 2x0.75mm <sup>2</sup> |
| Plug             |     | SP-501A 7,5A/250V            |
| Connector        |     | IS-033 2,5A/250V             |
| Rating           |     | 300/300V 70°C                |
| Flex cord        |     | H03VVH2-F                    |
| WEIGHT / PACKING | 1pc | N.W.: 92 g / pc              |
|                  | BOX | 125 pcs / 1box               |
|                  |     | G.W.: 12,4 kg / box          |
|                  |     | 0.55x0.36x0.20 [m]           |


**IEC320-C7 (Japan)**

Country of Origin      China  
 RoHS                      yes  
 Application              For Class II. Appliances  
 Approvals                PSE

|                  |     |                              |
|------------------|-----|------------------------------|
| Length/cord      |     | 1.8m / 2x0.75mm <sup>2</sup> |
| Plug             |     | SP-18B 7A/125V               |
| Connector        |     | IS-033C 7A/125V              |
| Rating           |     | 300V 60°C                    |
| Flex cord        |     | VCTFK                        |
| WEIGHT / PACKING | 1pc | N.W.: 104 g / pc             |
|                  | BOX | 150 pcs / 1box               |
|                  |     | G.W.: 16,3 kg / box          |
|                  |     | 0.55x0.36x0.20 [m]           |



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [AC Power Leads](#) category:*

*Click to view products by [Sunny](#) manufacturer:*

Other Similar products are found below :

[YP-61+YC12](#) [YP21A+YC13](#) [6601](#) [FTP-629Y603](#) [1700001947](#) [IL13-EU1-H05-3100-300-S](#) [P28976-M45](#) [BB-3271V86](#) [P29844-M5](#)  
[P29844-M10](#) [P28818-M6](#) [387005324](#) [387005325](#) [59903000000](#) [387007040](#) [IL13P-EU1-H05-3100-300](#) [PCAK2](#) [PPA00002-25F](#) [EM9169](#)  
[32004](#) [32002](#) [W-98979](#) [W-98980](#) [W-98983](#) [W-98987](#) [W-99183](#) [AK-RD-07A](#) [LPS275](#) [18049236](#) [LA0055](#) [HC-3C1.5MM-W-P](#) [NUFPWC-](#)  
[03PMMS-LC500](#) [NUF-MSAP-08BMMM-RJ](#) [BEST 053](#) [W-99469](#) [W2243](#) [W-99945](#) [W-99764](#) [W-98642](#) [W-98643](#) [W-99440](#) [W-97783](#) [W-](#)  
[99175](#) [W-97760](#) [W-99243](#) [M02411](#) [W-98692](#) [50078](#) [M01895](#) [AK-RD-06A](#)