



SK3410T120

Band41, RF SAW Filter
Preliminary : January 2018

MSL 3 Device



- Electrical Characteristics
- Package Dimensions
- Testing Environment
- Frequency Characteristics

□ Electrical Characteristics

Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-30	-	+85
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	3
Maximum Input Power	dBm	-	-	29
Source Impedance (Unbalance) ⁽¹⁾	Ω	-	50	-
Load Impedance (Unbalance) ⁽¹⁾	Ω	-	50	-
Package type & size	C24			
Length x Width	mm ²	-	1.4 x 1.1	-
Height	mm	-	-	0.65

Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	2595.0	-
Insertion Loss within 2535.0 ~ 2655.0 MHz	dB	-	2.0	2.8
Amplitude Ripple within 2535.0 ~ 2655.0 MHz	dB _{p-p}	-	1.0	2.0
Attenuation:				
2110.0 ~ 2170.0 MHz	dB	17	20	-
2401.0 ~ 2468.0 MHz (WLAN Ch 1~10)	dB	18	21	-
2451.0 ~ 2473.0 MHz (WLAN Ch 11)	dB	25	33	-
2456.0 ~ 2478.0 MHz (WLAN Ch 12)	dB	25	33	-
2461.0 ~ 2483.0 MHz (WLAN Ch 13)	dB	25	30	-
2775.0 ~ 4992.0 MHz	dB	18	21	-
VSWR within 2535.0 ~ 2655.0 MHz	-	-	1.6	2.3

Notes : (1) With Matching Network (Ref. Testing Environment Circuit as shown below).


□ Package Dimensions



Marking Descriptions	
S	SUNTEK
h	Band Class
A	Series Number
△	Date Code(Year+Month)

Pin Description	
B, C, E	Ground
A	Input
D	Output


□ Testing Environment





Source & Load Impedance: 50 Ω

□ Frequency Characteristics



Frequency Response



VSWR



Smith Chart



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Signal Conditioning](#) category:

Click to view products by [Suntek](#) manufacturer:

Other Similar products are found below :

[MAPDCC0001](#) [MAPDCC0004](#) [PD0409J5050S2HF](#) [HHS-109-PIN](#) [AFS14A35-1591.50-T3](#) [DS-323-PIN](#) [DSS-313-PIN](#) [B39321R801H210](#)
[1A0220-3](#) [JP510S](#) [LFB212G45SG8C341](#) [LFB322G45SN1A504](#) [LFL182G45TC3B746](#) [SF2159E](#) [30057](#) [AFS1575.42S4-T](#) [FM-104-PIN](#)
[CER0813B](#) [MAPDCC0005](#) [3A325](#) [40287](#) [41180](#) [ATB3225-75032NCT](#) [BD0810N50100AHF](#) [JHS-115-PIN](#) [DC0710J5005AHF](#)
[DC2327J5005AHF](#) [43020](#) [LFB2H2G60BB1C106](#) [LFL15869MTC1B787](#) [X3C19F1-20S](#) [XC3500P-20S](#) [10013-20](#) [SF2194E](#)
[CDBLB455KCAX39-B0](#) [TGL2208-SM, EVAL](#) [RF1353C](#) [051157-0000](#) [PD0922J5050D2HF](#) [1E1305-3](#) [1F1304-3S](#) [1G1304-30](#)
[B0922J7575AHF](#) [10017-3](#) [TP-103-PIN](#) [BD1222J50200AHF](#) [BD1722J50100AHF](#) [2450DP39K5400E](#) [BD0810J50150AHF](#)
[BD1722J50200AHF](#)