

SUL6001 Low Noise High PSRR 1 Ch 500mA/1A Ultra Low Dropout LDO

FUNCTIONAL DESCRIPTION

The SUL6001 series is a CMOS-based positive low-dropout linear regulator (LDO) featuring 500 mA/ 1.0A that provides high PSRR, high output voltage accuracy, low-noise and low supply current

It consists of a voltage reference, an error amplifier, a resistor-ladder for output voltage setting. It also has under-voltage lockout (UVLO), over current/short circuit protection circuit and over temperature shutdown circuit.

The SUL6001 typically has 95mV dropout voltage (DFN1216-8, I_{out}=1A, V_{out}=3.3V) and 156mA dropout voltage (DFN1216-8, I_{out}=1A, V_{out}=1.8V) and chip enable function (EN) for long battery life.

Excellent ripple rejection, load transient and line transient response make it ideal for the power sources of mobile communication devices or camera modules in low light condition. It can also turn on under full load condition, making it suitable for harsh system environment.

The SUL6001 series LDOs have option for output current limit between 1.0A or 500mA by alternating the LCON pin between “H” or “L” for DFN1216-8 package version.

MAIN FEATURES


- Supply Current (no load): 85μA (typ.)
- Supply Current (Standby): 0.1μA (typ.)
- Dropout Voltage: 95mV (DFN1216-8, I_{out}=1A, V_{out}=3.3V, typ.)
- High-PSRR: 85dB @1kHz
- Output Noise: 10μV_{rms} (10-100KHz, 0.85V output voltage settings, typ.)
- Line Regulation: 0.01%/V
- Fixed Mode Voltage Range: 0.85V to 4.3V with 0.05V step.
- Adjustable Mode Voltage Range: 0.85V to 4.6V.
- Built-in Short Current Protection Limit: 120mA (LCON='H', 1.0A, typ.)
- Built-in Peak Current Protection Limit: 1.7A (LCON='H', 1.0A, typ.)
- Over Temperature Protection and Auto Recover
- Built-in Soft-Start and Inrush Current Limit
- Fast Auto Discharge Function for Power Down

APPLICATIONS


- Portable Device , Tablets and Smartphone
- Cameras, VCRs and Car Dash Cameras
- Low Light & Low Noise Cam Application
- Communications and Infrastructure
- AR or VR Application

BLOCK DIAGRAMS


DFN1216-8 (8 PIN)




SOT-89-3 (3 PIN)




SOT-89-5 (5 PIN)



SOT-23-5 Fixed Mode (5 PIN)



SOT-23-5 ADJ Mode (5 PIN)




It is not recommended to use the 1A version of the SOT-23-5 package.

Ordering Information


| Part Number | Package | Tape/Reel |
|--------------|-----------|-----------|
| SUL6001S5-XX | SOT23-5 | 3000 |
| SUL6001T5-XX | SOT89-5 | 1000 |
| SUL6001D6-XX | DFN2x2-6 | 4000 |
| SUL6001DRB | DFN3x3-8 | 5000 |
| SUL6001D8-XX | DFN1216-8 | 3000 |

For example, 28 means product outputs 2.8V, ADJ means adjustable.
SUL6001 devices are Pb-free and RoHS compliant.


PACKAGE INFORMATION & PIN DESCRIPTION




**SOT-89-3-AFT
Pin Configuration**




SOT-89-5 Pin Configuration




**SOT-89-3-BFT
Pin Configuration**



SOT-23-5 Pin Configuration (ADJ Mode)




**SOT-89-3-CFT
Pin Configuration**




SOT-23-5 Pin Configuration (Fixed Mode)

Top View




Bottom View




DFN1216-8 Pin Configuration


Top View




Top View



Top View



Top View




| Pin Name | Pin Function | PIN No | | | | |
|----------|-------------------------------------|-----------|-----------|------|-----------|-----|
| | | DFN1216-8 | DFN3030-8 | | DFN2020-6 | |
| | | | Fixed | ADJ | Fixed | ADJ |
| VIN | Input of Supply Voltage. | 7, 8 | 7, 8 | 7, 8 | 6 | 6 |
| VOUT | LDO Output Voltage pin. | 1, 2 | 1, 2 | 1, 2 | 1 | 1 |
| GND | Ground. | 5 | 4 | 4 | 3 | 3 |
| EN | Enable pin. | 6 | 5 | 5 | 4 | 4 |
| NC | No internal connection. | NA | 3, 6 | 6 | 2, 5 | 5 |
| ADJ | ADJ pin. | 4 | NA | 3 | NA | 2 |
| LCON | Output Current Limit Alternate Pin. | 3 | NA | NA | NA | NA |

| Pin Name | Pin Function | PIN No | | | | | |
|----------|--------------------------|----------|-----|----------|----|----|----------|
| | | SOT-23-5 | | SOT-89-3 | | | SOT-89-5 |
| | | Fixed | ADJ | A | B | C | ADJ |
| VIN | Input of Supply Voltage. | 1 | 1 | 1 | 2 | 3 | 4 |
| VOUT | LDO Output Voltage pin. | 5 | 5 | 3 | 3 | 1 | 5 |
| GND | Ground. | 2 | 2 | 2 | 1 | 2 | 2 |
| EN | Enable pin. | 3 | 3 | NA | NA | NA | 3 |
| NC | No internal connection. | 4 | NA | NA | NA | NA | NA |
| ADJ | ADJ pin. | NA | 4 | NA | NA | NA | 1 |

***Note: Connect exposed pad (heat sink on the back) to GND.**


TYPICAL APPLICATION CIRCUIT

A. Fixed mode example



* Recommended Ceramic Capacitors for Vin and Vout: 1µF

B. Adjustable (ADJ) mode example



The adjustable-version device requires external feedback divider resistors to set the output voltage.

V_{OUT} is set using the feedback divider resistors, R_1 and R_2 , according to the following equation:

$$V_{OUT} = V_{FB} \times (1 + R_1 / R_2)$$

For this device, $V_{FB} = 0.85$ V.

To ignore the FB pin current error term in the V_{OUT} equation, set the feedback divider current to 100x the FB pin current listed in the *Electrical Characteristics* table. This setting provides the maximum feedback divider series resistance, as shown in the following equation:

$$R_1 + R_2 \leq V_{OUT} / (I_{FB} \times 100)$$

For this device, $I_{FB} = 10$ nA.

ABSOLUTE MAXIMUM RATINGS

| Symbol | Item | Rating | | Unit |
|-------------------|--|-------------|------|------|
| V _{IN} | Input Voltage | 6.0 | | V |
| V _{CE} | Input Voltage (CE Pin) | -0.3 to 6.0 | | V |
| V _{LCON} | Input Voltage (LCON Pin) | -0.3 to 6.0 | | V |
| V _{OUT} | Output Voltage | -0.3 to 6.0 | | V |
| P _D | Power Dissipation (Standard Land Pattern) | DFN1216-8 | 1400 | mW |
| | | DFN3*3-8 | 1950 | mW |
| T _{OP} | Junction Temperature Range | -40 to 125 | | °C |
| T _{STG} | Storage Temperature Range | -55 to 125 | | °C |

RECOMMENDED OPERATING CONDITIONS

| Symbol | Item | Rating | Unit |
|-----------------------------------|-----------------------------|-------------|------|
| V _{IN} | Input Voltage | 1.32 to 5.5 | V |
| V _{OUT} | Output Voltage | 0.85 to 4.3 | V |
| T _a | Operating Temperature Range | -40 to 85 | °C |
| C _{IN} /C _{OUT} | Input/Output Capacitance | 1/1 | uF |

ELECTROSTATIC DISCHARGE

| Symbol | Parameter | Value | Unit |
|--------|--------------------|--------|------|
| ESD | Human Body Mode | ± 4 | kV |
| | Machine Mode | ± 250 | V |
| | Charge Device Mode | ± 1000 | V |

THERMAL DATA

| Symbol | Parameter | Value | | Unit |
|---------------|-------------------------------------|---------|-----|-----------------------------|
| θ_{JA} | Thermal resistance junction-ambient | DFN3*3 | 53 | $^{\circ}\text{C}/\text{W}$ |
| | | DFN1216 | 80 | |
| | | SOT23-5 | 260 | |


ELECTRICAL CHARACTERISTICS

$V_{IN} = V_{OUT} + 1.0\text{ V}$, $I_{OUT} = 1\text{ mA}$, $C_{IN} = C_{OUT} = 1.0\text{ }\mu\text{F}$, typical values are at $T_J = 25\text{ }^{\circ}\text{C}$; unless otherwise noted.

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Unit | |
|------------------|-------------------------|---|------------------------------|------|------|---------------|----|
| V_{IN} | Operating input voltage | | 1.32 | | 5.50 | V | |
| V_{OUT} | V_{OUT} accuracy | $V_{OUT} + 0.5\text{ V} \leq V_{IN} \leq 5.5\text{ V}$ | $V_{OUT} \geq 1.75\text{ V}$ | -1.0 | +1.0 | % | |
| | | | $V_{OUT} < 1.75\text{ V}$ | -20 | +20 | mV | |
| ΔV_{OUT} | Static line regulation | | | 0.01 | | %/V | |
| ΔV_{OUT} | Static load regulation | $I_{OUT} = 10\text{ mA to }500\text{ mA}$ | | 1 | 20 | mV | |
| | | $I_{OUT} = 10\text{ mA to }1000\text{ mA}$ | | | 40 | | |
| V_{DROP} | Dropout voltage | $I_{OUT} = 1\text{ A}$ | $V_{OUT}=1.2\text{ V}$ | | 245 | 340 | mV |
| | | | $V_{OUT}=1.8\text{ V}$ | | 140 | 235 | |
| | | | $V_{OUT}=2.5\text{ V}$ | | 105 | 175 | |
| | | | $V_{OUT}=3.3\text{ V}$ | | 85 | 150 | |
| | | | $V_{OUT}=4.3\text{ V}$ | | 60 | 130 | |
| | | $I_{OUT} = 500\text{ mA}$ For SOT-23-5 | $V_{OUT}=1.2\text{ V}$ | | 150 | 210 | |
| | | | $V_{OUT}=1.8\text{ V}$ | | 80 | 135 | |
| | | | $V_{OUT}=2.5\text{ V}$ | | 60 | 100 | |
| | | | $V_{OUT}=3.3\text{ V}$ | | 50 | 105 | |
| | | | $V_{OUT}=4.3\text{ V}$ | | 40 | 85 | |
| I_Q | Quiescent current | $I_{OUT} = 0\text{ mA}$ | | 85 | 140 | μA | |
| $I_{Standby}$ | Standby current | V_{IN} input current in OFF MODE: $V_{EN} = \text{GND}$ | | 0.1 | 3 | μA | |
| I_{LIM} | Output current limit | $I_{OUT} = 500\text{ mA}$ | 0.6 | 0.78 | | A | |
| | | $I_{OUT} = 1\text{ A}$ | | 1.7 | | | |
| I_{SC} | Short-circuit current | $V_{OUT} = 0\text{ V}$ | $I_{OUT} = 500\text{ mA}$ | | | 186 | mA |
| | | | $I_{OUT} = 1\text{ A}$ | | | | |
| I_{FB} | Feedback pin current | | | 0.01 | 0.1 | μA | |


ELECTRICAL CHARACTERISTICS (continued)

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Unit |
|------------------|------------------------------|-----------------------------------|------|------|------|-------|
| e _N | Output noise voltage | | | 10 | | μVrms |
| PSRR | Power Supply Rejection Ratio | | | 85 | | dB |
| T _{TSD} | Thermal shutdown | Shutdown, temperature increasing | | 165 | | °C |
| | | Reset, temperature decreasing | | 135 | | °C |
| CE | Enable input logic low | V _{IN} = 1.32 V to 5.5 V | | | 0.4 | V |
| | Enable input logic high | V _{IN} = 1.32 V to 5.5 V | 1 | | | |
| LCON | LCON input logic low | V _{IN} = 1.32 V to 5.5 V | | | 0.4 | V |
| | LCON input logic high | V _{IN} = 1.32 V to 5.5 V | 1 | | | |



*This is SUL6001D8-33 measurement data. Other PSRR information please contact SUNTEK.

Load Regulation (Dynamic)



| Symbol | Parameter | Condition | Min. | Typ. | Max. | Unit |
|--------------|--------------------|--------------------------|------|------|------|------|
| ΔV_1 | Undershoot Voltage | $I_{LOAD}=1mA\sim 250mA$ | | 30 | | mV |
| | | $I_{LOAD}=1mA\sim 500mA$ | | 40 | | |
| | | $I_{LOAD}=1mA\sim 1A$ | | 62 | | |
| | | $I_{LOAD}=0mA\sim 300mA$ | | 50 | | |
| | | $I_{LOAD}=0mA\sim 1A$ | | 90 | | |
| ΔV_2 | Overshoot Voltage | $I_{LOAD}=1mA\sim 250mA$ | | 28 | | mV |
| | | $I_{LOAD}=1mA\sim 500mA$ | | 40 | | |
| | | $I_{LOAD}=1mA\sim 1A$ | | 60 | | |
| | | $I_{LOAD}=0mA\sim 300mA$ | | 35 | | |
| | | $I_{LOAD}=0mA\sim 1A$ | | 65 | | |

| Symbol | Parameter | Condition | Min. | Typ. | Max. | Unit |
|--------------|-------------------------|--------------------------|------|------|------|---------|
| Δt_1 | Transient recovery time | $I_{LOAD}=1mA\sim 250mA$ | | 10 | | μS |
| | | $I_{LOAD}=1mA\sim 500mA$ | | 16 | | |
| | | $I_{LOAD}=1mA\sim 1A$ | | 18 | | |
| | | $I_{LOAD}=0mA\sim 300mA$ | | 60 | | |
| | | $I_{LOAD}=0mA\sim 1A$ | | 80 | | |
| Δt_2 | Transient recovery time | $I_{LOAD}=1mA\sim 250mA$ | | 12 | | μS |
| | | $I_{LOAD}=1mA\sim 500mA$ | | 12 | | |
| | | $I_{LOAD}=1mA\sim 1A$ | | 16 | | |
| | | $I_{LOAD}=0mA\sim 300mA$ | | 90 | | |
| | | $I_{LOAD}=0mA\sim 1A$ | | 300 | | |

*This table is SUL6001D8-33 measurement data. For detail load regulation information about other SUL6001 series LDOs, please contact SUNTEK.

FUNCTION DESCRIPTION

A. Short-Circuit Protect and Current Limitation

SUL6001 series LDOs can protect internal circuit under short-circuit condition on the output. When the load current increases above 1.55 A, the current limit and current foldback mechanism starts to restrict the I_{LIM} value. If the load resistance decreases even more then the foldback, circuit starts limiting the current to 0.2 A when $V_{OUT} = 0$.

B. Over Temperature Protection and Auto Recover

In order to prevent over thermal condition from damaging the device, SUL6001 series LDOs have internal thermal limiting functions designed to protect the device. It will rapidly shut off PMOS pass element during over temperature condition.

C. Current Foldback

The current limiting/ current foldback circuit plays an important role by controlling any excessive output current. Our SUL6001 series LDOs provide a current foldback circuit that can detect accurately when an over-current condition occurs.

D. Very Fast Transient Response

In addition to the main feedback loop, SUL6001 series LDOs contain a fast-transient loop that allows the LDO to respond faster to large-output transients. SUL6001 series LDOs that contain this loop are better able to minimize the effects of a load transient even the output capacitance is small. The recommended output capacitance value is 1 μ F. It's small size greatly reduce the cost and save PCB area.

E. Ultra High PSRR and Extreme Low Noise

SUNTEK's SUL6001 series high-performance LDO regulators feature remarkable power supply rejection ratio characteristics (up to 104 dB at 10 kHz) and extreme-low noise operation (as low as 6.3 μ VRMS with A-wt) resulting in cleaner and stable output voltages. Our LDO is very suitable for ultra-sensitive loads like camera module and security monitor, especially in low light condition.

F. Start-Up at Full Load

SUL6001 series LDOs can start-up at full load, make it very suitable for heavy load start up condition and severe system timing constraint.

G. Auto Discharge Function

SUL6001 series LDOs have an auto discharge function to quickly force the output voltage to zero. When the LDO is disabled, the auto discharge function quickly discharge the output capacitor, thereby reducing the output voltage to nearly zero. This function is very useful for quickly ON/OFF application.

H. Low Quiescent Current

SUL6001 series LDOs consume only 85 μ A (typical) while operating with no load condition. By reducing the quiescent current, your application can stay in standby/sleep mode much longer than leading low quiescent current LDOs in the market.



I. Under Voltage Lock OUT (UVLO)

SUL6001 has an undervoltage lockout (UVLO) function to make sure that whole circuit does nothing until the power supply voltage is high enough. When power supply voltage is high enough, reference circuit can generate right voltage ; logic function can generate correct control signals. This UVLO function can guarantee robust system performance.



TYPICAL CHARACTERISTICS



$V_{IN} = V_{SET}^{(1)} + 1.0 \text{ V}$, $I_{OUT} = 1 \text{ mA}$, $C_{IN} = C_{OUT} = 1.0 \mu\text{F}$, $L_{CON}='H'$, typical values are at $T_J = 25 \text{ }^\circ\text{C}$; unless otherwise noted.

Output Voltage vs. Input Voltage ($C_{IN} = C_{OUT} = 1.0 \mu\text{F}$, $T_a = 25 \text{ }^\circ\text{C}$)




Supply Current vs. Input Voltage ($C_{IN} = C_{OUT} = 1.0 \mu\text{F}$, $T_a = 25 \text{ }^\circ\text{C}$)






Supply Current vs. Temperature (CIN = COUT = 1.0 μ F, IOU= 0 mA)




Over Current Protect Foldback Characteristic (LCON = V_{IN}, C_{IN} = C_{OUT} = 1.0 μF, Ta = 25°C)


SUL6001D8-090




SUL6001D8-12




SUL6001D8-18




SUL6001D8-25



SUL6001D8-33




SUL6001D8-43




Output Noise Voltage (10 Hz to 100 kHz, $C_{IN} = C_{OUT} = 1.0 \mu F$, $T_a = 25^\circ C$)

SUL6001D8-090, $I_{OUT} = 100 \text{ mA}$

Amplitude Spectral Density




V_{RMS} from 10 Hz to 100 kHz




SUL6001D8-12, $I_{OUT} = 100 \text{ mA}$

Amplitude Spectral Density




V_{RMS} from 10 Hz to 100 kHz




SUL6001D8-33, I_{OUT} = 100 mA

Amplitude Spectral Density




V_{RMS} from 10 Hz to 100 kHz




Power Supply Ripple Rejection vs. Frequency ($V_{IN}=V_{OUT}+1V$, $C_{IN} = C_{OUT} = 1.0 \mu F$, Ripple = 0.2 Vp-p, $T_a = 25^\circ C$)

SUL6001D8-090


$I_{Load}=1mA$




$I_{Load}=10mA$



$I_{Load}=30mA$




$I_{Load}=150mA$




SUL6001D8-12


I_{Load}=1mA




I_{Load}=10mA



I_{Load}=30mA



I_{Load}=150mA




SUL6001D8-18


I_{Load}=1mA




I_{Load}=10mA



I_{Load}=30mA




I_{Load}=150mA




SUL6001D8-25


I_{Load}=1mA




I_{Load}=10mA



I_{Load}=30mA




I_{Load}=150mA




SUL6001D8-33


I_{Load}=1mA




I_{Load}=10mA



I_{Load}=30mA




I_{Load}=150mA




SUL6001D8-43

I_{Load}=1mA



I_{Load}=10mA



I_{Load}=30mA




I_{Load}=150mA




Load Transient Response ($V_{IN}=V_{OUT}+1V$, $C_{IN} = C_{OUT} = 1.0 \mu F$, $t_r = t_f = 1 \mu s$, $T_a = 25^\circ C$)

SUL6001D8-090


1mA -> 250mA




1mA -> 500mA




1mA -> 1000mA



0mA -> 300mA




0mA -> 1000mA




SUL6001D8-12


1mA -> 250mA




1mA -> 500mA




1mA -> 1000mA



0mA -> 300mA




0mA -> 1000mA




SUL6001D8-18


1mA -> 250mA




1mA -> 500mA




1mA -> 1000mA



0mA -> 300mA




0mA -> 1000mA




SUL6001D8-25


1mA -> 250mA




1mA -> 500mA




1mA -> 1000mA



0mA -> 300mA




0mA -> 1000mA




SUL6001D8-33


1mA -> 250mA




1mA -> 500mA




1mA -> 1000mA



0mA -> 300mA




0mA -> 1000mA




SUL6001D8-43


1mA -> 250mA




1mA -> 500mA




1mA -> 1000mA



0mA -> 300mA




0mA -> 1000mA




Turn-on waveform by V_{IN} & CE @ light load ($V_{IN} = CE = 0$ V to $V_{OUT}+1$ V, $C_{IN} = C_{OUT} = 1.0$ μ F, $T_a = 25^\circ$ C, $I_{OUT} = 1$ mA)


SUL6001D8-090




SUL6001D8-12




SUL6001D8-18




SUL6001D8-25



SUL6001D8-33




SUL6001D8-43




Turn-on waveform by V_{IN} & CE @ full load ($V_{IN} = CE = 0\text{ V}$ to $V_{OUT}+1\text{V}$, $C_{IN} = C_{OUT} = 1.0\ \mu\text{F}$, $T_a = 25^\circ\text{C}$, $I_{OUT}=1\text{A}$)


SUL6001D8-09Q




SUL6001D8-12




SUL6001D8-18




SUL6001D8-25



SUL6001D8-33




SUL6001D8-43




Turn-on by CE pin & Inrush current @ no load ($V_{IN} = V_{OUT} + 1V$, $CE = 0V$ to $1V$, $C_{IN} = C_{OUT} = 1.0 \mu F$, $T_a = 25^\circ C$, $I_{OUT} = 0 mA$)


SUL6001D8-09




SUL6001D8-12




SUL6001D8-18




SUL6001D8-25



SUL6001D8-33




SUL6001D8-43




Turn-on by CE pin @ full load ($V_{IN} = V_{OUT} + 1V$, $CE = 0V$ to $1V$, $C_{IN} = C_{OUT} = 1.0 \mu F$, $T_a = 25^\circ C$, $I_{OUT} = 1A$)


SUL6001D8-090




SUL6001D8-12




SUL6001D8-18




SUL6001D8-25




SUL6001D8-33



SUL6001D8-43





DFN1216-8 Package Information



| SYMBOL | MILLIMETER | | |
|--------|------------|------|------|
| | MIN | NOM | MAX |
| A | 0.35 | - | 0.40 |
| A1 | 0 | 0.02 | 0.05 |
| b | 0.13 | 0.18 | 0.23 |
| c | 0.127REF | | |
| D | 1.55 | 1.60 | 1.65 |
| D2 | 1.25 | 1.30 | 1.35 |
| e | 0.40BSC | | |
| Nd | 1.20BSC | | |
| E | 1.15 | 1.20 | 1.25 |
| E2 | 0.25 | 0.30 | 0.35 |
| L | 0.15 | 0.20 | 0.25 |
| L1 | 0.06 | 0.11 | 0.16 |
| L2 | 0.05REF | | |
| h | 0.10 | 0.15 | 0.20 |
| K | 0.15 | 0.20 | 0.25 |

SOT-23-5 Package Information





| Common Dimensions (Units of Measure=Millimeter) | | | |
|--|----------|---------|---------|
| SYMBOL | MINIMUM | NOMINAL | MAXIMUM |
| A | - | - | 1.35 |
| A1 | 0 | - | 0.15 |
| A2 | 1.00 | 1.10 | 1.20 |
| b | 0.35 | - | 0.45 |
| b1 | 0.32 | - | 0.38 |
| c | 0.14 | - | 0.20 |
| c1 | 0.14 | 0.15 | 0.16 |
| D | 2.82 | 2.92 | 3.02 |
| E | 2.60 | 2.80 | 3.00 |
| E1 | 1.526 | 1.626 | 1.726 |
| e | 0.90 | 0.95 | 1.00 |
| e1 | 1.80 | 1.90 | 2.00 |
| L | 0.35 | 0.45 | 0.60 |
| L1 | 0.6 REF | | |
| L2 | 0.25 REF | | |
| R | 0.10 | - | - |
| R1 | 0.10 | - | 0.25 |
| θ | 0° | 4° | 8° |
| θ 1 | 5° | 10° | 15° |


NOTES:

1. All dimensions refer to standard.
2. Dimensions D does not include mold FLASH.
3. Dimensions E1 does not include mold FLASH.
4. FLASH or protrusion shall not exceed 0.25mm per side.




SOT-89-5 Package Information



SECTION A-A





SECTION B-B



| SYMBOL | MILLIMETER | | |
|--------|------------|------|------|
| | MIN | NOM | MAX |
| A2 | 1.40 | 1.50 | 1.60 |
| b | 0.38 | — | 0.46 |
| b1 | 0.37 | 0.40 | 0.43 |
| c | 0.38 | — | 0.42 |
| c1 | 0.37 | 0.38 | 0.39 |
| a | 0.46 | — | 0.56 |
| a1 | 0.45 | 0.48 | 0.51 |
| D | 4.40 | 4.50 | 4.60 |
| D1 | 1.62 | — | 1.83 |
| E | 3.95 | — | 4.25 |
| E1 | 2.40 | 2.50 | 2.60 |
| e | 1.50BSC | | |
| L1 | 0.89 | — | 1.20 |

| L/F Size (mil) | Size (mm) | \triangle D2 | \triangle E2 |
|----------------|-----------|----------------|----------------|
| 85*70 | | 1.75REF | 2.84REF |

DFN2020-6 Package Information




COMMON DIMENSIONS
(UNITS OF MEASURE=mm)

| SYMBOL | MIN | NOM | MAX |
|--------|-----------|------|------|
| A | 0.70 | 0.75 | 0.80 |
| A1 | 0.00 | 0.02 | 0.05 |
| b | 0.20 | 0.25 | 0.30 |
| D | 1.95 | 2.00 | 2.07 |
| E | 1.95 | 2.00 | 2.07 |
| D1 | 0.80 | 0.90 | 1.00 |
| E1 | 0.90 | 1.00 | 1.10 |
| D2 | 0.20 | 0.30 | 0.40 |
| E2 | 0.65 | 0.75 | 0.85 |
| L | 0.20 | 0.25 | 0.35 |
| h | 0.20 | 0.25 | 0.30 |
| c | 0.203 REF | | |
| e | 0.65 BSC | | |

其它厚度尺寸如下

| | | | |
|---|------|------|------|
| A | 0.55 | 0.60 | 0.65 |
| A | 0.50 | 0.55 | 0.60 |

DFN3030-8 Package Information



| COMMON DIMENSIONS(MM) | | | |
|-----------------------|------------------|------|------|
| PKG. | W:VERY VERY THIN | | |
| REF. | MIN. | NOM. | MAX |
| A | 0.70 | 0.75 | 0.80 |
| A1 | 0.00 | — | 0.05 |
| A3 | 0.2 REF. | | |
| D | 2.95 | 3.00 | 3.05 |
| E | 2.95 | 3.00 | 3.05 |
| b | 0.25 | 0.30 | 0.35 |
| L | 0.30 | 0.40 | 0.50 |
| D2 | 2.40 | 2.45 | 2.50 |
| E2 | 1.60 | 1.65 | 1.70 |
| e | 0.65 BSC | | |
| b1 | 0.20 | | |

| | | |
|-------------------------------|----------------|------------------------------------|
| DESIGNED: | DATE: 28/03/09 | 8L DFN3x3 mm (PACKAGE ●OUTLINE) |
| APPD: | DATE: | |
| APPD: | DATE: | |
| APPD: | DATE: | |
| APPD: | DATE: | |
| DWG. NO: POD-DFN3030-08L-0.65 | REV.: B | SHEET NO : 1 OF 1 |

啟
2009

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Linear Voltage Regulators](#) category:

Click to view products by [Suntek](#) manufacturer:

Other Similar products are found below :

[LV5684PVD-XH](#) [MCDTSA6-2R](#) [L7815ACV-DG](#) [LV56801P-E](#) [UA7805CKC](#) [714954EB](#) [ZMR500QFTA](#) [BA033LBSG2-TR](#)
[NCV78M05ABDTRKG](#) [LV5680P-E](#) [L79M05T-E](#) [L78LR05D-MA-E](#) [NCV317MBTG](#) [NTE7227](#) [MP2018GZD-33-P](#) [MP2018GZD-5-P](#)
[LV5680NPVC-XH](#) [ZTS6538SE](#) [UA78L09CLP](#) [UA78L09CLPR](#) [CAT6221-PPTD-GT3](#) [MC78M09CDTRK](#) [NCV51190MNTAG](#)
[BL1118CS8TR1833](#) [BL8563CKETR18](#) [BL8077CKETR33](#) [BL9153-33CC3TR](#) [BL9161G-15BADRN](#) [BL9161G-28BADRN](#)
[BRCO7530MMC](#) [CJ7815B-TFN-ARG](#) [LM317C](#) [GM7333K](#) [GM7350K](#) [XC6206P332MR](#) [HT7533](#) [LM7912S/TR](#) [LT1764S/TR](#) [LM7805T](#)
[LM338T](#) [LM1117IMP-3.3/TR](#) [HT1117AM-3.3](#) [HT7550S](#) [AMS1117-3.3](#) [HT7150S](#) [78L12](#) [HT7550](#) [HT7533-1](#) [HXY6206I-2.5](#) [HT7133](#)