swissbit®

Product Fact Sheet

Industrial CFast™ Card

F-600 Series SATA Gen3 - 6.0 Gbit/s, SLC

Commercial and Industrial Temperature Grade

Date: April 08, 2020 Revision: 1.07



Product Fact Sheet F-600 Series



Product Summary

- Capacities: 4 GBytes, 8 GBytes, 16 GBytes, 32 GBytes, 64 GBytes
- Form Factor: CFast-Sized Solid State Drive (36.4 mm x 42.8 mm x 3.6 mm)
- Compliance: SATA Gen3 6 Gbit/s (Gen2 3 Gbit/s and Gen1 1.5 Gbit/s backward compatible)
- Command Sets: Supports ATA/ATAPI-8 and ACS-2
- Performance:
 - o Read Performance: Sequential Read up to 520 MBytes/s, Random Read 4K up to 76,000 IOPS
 - o Write Performance: Sequential Write up to 245 MBytes/s, Random Write 4K up to 54,000 IOPS
- Operating Temperature Range¹: Commercial: o °C to 70 °C; Industrial: -40 °C to 85 °C
- Storage Temperature Range: -40 °C to 85 °C
- Operating Voltage: 3.3 V ± 5%
- Power (Max Capacity): Read (Active): 1.6 W; Write (Active): 2.4 W; Idle: 347 mW; Slumber: 115 mW
- Data Retention: 10 Years @ Life Begin / 1 Year @ Life End
- Endurance in TeraBytes Written (TBW) Max Capacity²: Client ≥ 4,240; Embedded ≥ 1,370; Enterprise ≥ 615
- Shock/Vibration: 1,500 g / 50 g
- Hardware BCH Code ECC: up to 66 bit correction per 1 KByte page
- Mean Time Between Failure: > 2,000,000 hours
- Data Reliability: < 1 non-recoverable error per 10¹⁶ bits read

Product Features

- Dynamic and Static Wear Leveling
- Subpage Mode Flash Translation Layer (FTL)
- Active and Passive Data Care Management
- Lifetime Enhancements
 - Dynamic Bad Block Remapping
 - Write Amplification Reduction
- On-Board Power Fail Protection
- AHCI, TRIM, and NCQ Support
- ATA Security Feature Set Support
- DEVSLP Compatible
- In-Field Firmware Update
- Enterprise Grade Self-Monitoring, Analysis, and Reporting Technology (S.M.A.R.T.)
- AES256 Encryption (on request)
- 30 µinch Gold-Plated Connector (on request)
- Swissbit Life Time Monitoring (SBLTM) Tool and SDK for SBLTM (on request)

Why Swissbit?

Swissbit is focused on the design, development, manufacture, and support of leading edge memory and storage solutions for the worldwide OEM/ODM marketplace. As a global supplier, Swissbit recognizes and addressees the higher level of application requirements of today's industrial, Netcom, and automotive customers by providing best-in-class products and services, with uncompromised attention to driving overall value and quality.

Page 2 of 2

Adequate airflow is required to ensure the temperature, as reported in the S.M.A.R.T. data, does not exceed 115°C (industrial temperature drive) and 100°C (commercial temperature drive) respectively.

² According to JEDEC (JESD47I), the time to write the full TBW is a minimum of 18 months. Higher average daily data volume reduces the specified TBW. The values listed are estimates and are subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Memory Cards category:

Click to view products by Swissbit manufacturer:

Other Similar products are found below:

SQF-ISDS1-8G-21C USDCOEM-32GB LMEX1L128GG2 LMEX1L256GG2 LMEX1L016GG2 LMEX1L032GG2 LMEX1L064GG2
SDSDQAF4-032G-I SDSDQAF4-256G-I AP-CF016GKBNS-ETNRG CFLSH-016SDG MS-C6-8G WPCFC512M-HFITI-AA
WPMSD001G-PFITI WPMSD002G-PFITI WPMSD004G-PFISMAS WPMSD008G-PFISM WPMSD008G-PFISMAS WPMSD016GPFISM WPMSD016G-PFISMAS WPSDC001G-EAITI WPSDC002G-EAITI SPSDH008G-PFCSM SPSDH016G-PTCT5AS SPSDH032GPTCT5AS HMC-EF283 SDCFXPS-032G-X46 SDCFXSB-128G-G46 SDSDQB-032G-B35 SDSDQM-032G-B35A SDU4GDMGRB
SDU4GDPGRB 5788667-1-CUT-TAPE RP-SMLE32DA1 SDC4GDPGRB 2729389 VTDCFBPI004G SDSDAF3-016G-XI 2403484
VTDS41PI008G SDSDAF3-016G-I VSFCS2CC060G SDSDAF3-032G-XI SDSDAD-016G SDSDAF3-008G-XI SDSDAF3-008G-I
SDSDQAB-016G-J VTDCFBPI008G M1A0-0160R12 M1A0-0320R12