swissbit®

Product Fact Sheet

Industrial M.2 SATA SSD

X-600m2 2260 Series SATA Gen3 - 6.0 Gbit/s, SLC

Commercial and Industrial Temperature Grade

Date: August 30, 2019 Revision: 1.09





Product Fact Sheet X-600m2 2260 Series



Product Summary

- Capacities: 16 GBytes, 32 GBytes, 64 GBytes, 128 GBytes
- Form Factor: PCI Express™ M.2 (2260) (60 mm x 22 mm x 3.58 mm)
- Compliance: SATA Gen3 6 Gbit/s (Gen2 3 Gbit/s and Gen1 1.5 Gbit/s backward compatible)
- Command Sets: Supports ATA/ATAPI-8 and ACS-2
- Performance:
 - o Read Performance: Sequential Read up to 520 MBytes/s, Random Read 4K up to 76,000 IOPS
 - Write Performance: Sequential Write up to 405 MBytes/s, Random Write 4K up to 73,000 IOPS
- Operating Temperature Range*:
 - Commercial: o °C to 70 °C
 - o Industrial: -40 °C to 85 °C
- Storage Temperature Range: -40 °C to 85 °C
- Operating Voltage: 3.3 V ± 5%
- Power (Max Capacity): Read (Active): 1.7 W; Write (Active): 2.5 W; Idle: 380 mW; Slumber: 115 mW
- Data Retention: 10 Years @ Life Begin; 1 Year @ Life End
- Endurance in TeraBytes Written (TBW) Max Capacity†: Client \geq 7,715; Embedded \geq 2,500; Enterprise \geq 1,120
- Shock/Vibration: 1,500 g l 50 g
- Hardware BCH Code ECC: up to 66 bit correction per 1 KByte page
- Mean Time Between Failure: > 2,000,000 hours
- Data Reliability: < 1 non-recoverable error per 10¹⁶ bits read

Product Features

- Dynamic and Static Wear Leveling
- Data Care Management
 - o Active: Adaptive Read Refresh
 - o Passive: Background Media Scan
- Lifetime Enhancements
 - o Dynamic Bad Block Remapping
 - Write Amplification Reduction
- On-Board Power Fail Protection
- AHCI, TRIM, and NCQ Support
- ATA Security Feature Set Support
- DEVSLP Compatible
- In-Field Firmware Update
- Enterprise-Grade Self-Monitoring, Analysis, and Reporting Technology (S.M.A.R.T.)
- 30 µinch Gold-Plated Connector (IPC-6012B Class 2 Compliant)
- AES256 Encryption (on request)
- Swissbit Life Time Monitoring (SBLTM) Tool and SDK for SBLTM (on request)

Why Swissbit?

Swissbit is focused on the design, development, manufacture, and support of leading edge memory and storage solutions for the worldwide OEM/ODM marketplace. As a global supplier, Swissbit recognizes and addressees the higher level of application requirements of today's industrial, Netcom, and automotive customers by providing best-in-class products and services, with uncompromised attention to driving overall value and quality.

^{*} Adequate airflow is required to ensure the temperature, as reported in the S.M.A.R.T. data, does not exceed 115°C (industrial temperature drive) and 100°C (commercial temperature drive) respectively.

[†] According to JEDEC (JESD47I), the time to write the full TBW is a minimum of 18 months. Higher average daily data volume reduces the specified TBW. The values listed are estimates and are subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Solid State Drives - SSD category:

Click to view products by Swissbit manufacturer:

Other Similar products are found below:

ATCA7360-MMOD-SATA2 ASD25-MLC064G-CT-160-1 SQF-SM4V2-256G-SBC SD7SN6S-128G-1122 MTFDDAA120MBB2AE1ZABYY SDSDQAD-128G SM668GXB-ACS O1118 SDINADF4-64G-H SQF-S25V4-240G-SCC SQF-SDMM2-256G-S9E
SFSA016GQ1BJ8TO-I-DT-226-STD MTFDDAK060MBD-1AH12ITYY VSF202PC016G-100 AF512GSMEL-VABIP SSDPEKKA020T801
MTFDDAK064MBD-1AH12ITYY EP-SSMSF128AACS APS297F064G-4BTM1GWF HBRPEKNX0202A01 SSDPE21D015TAX1
SSDPED1D015TAX1 SSDPEKKF020T8X1 SSDPEKKR256G7XN SSDPEKKW020T8X1 SSDPEKKW512G801 SSDPEKNW020T801
SSDPEKNW020T9X1 SSDPEL1D380GAX1 SM2280S3G2/120G MTFDDAK1T9QDE-2AV1ZABYY MTFDDAK3T8QDE-2AV1ZABYY
MTFDDAT128MBD-1AK12ITYY MTFDDAV256TDL-1AW12ABYY MTFDDAK2T0TDL-1AW1ZABYY MTFDDAK1T0TDL1AW12ABYY MTFDDAV512TDL-1AW1ZABYY MTFDDAV256TDL-1AW1ZABYY MTFDHAL11TATCW-1AR1ZABYY
MTFDHAL12T8TDR-1AT1ZABYY MTFDHAL1T6TCU-1AR1ZABYY MTFDHAL1T9TCT-1AR1ZABYY MTFDHAL3T8TCT1AR1ZABYY MTFDHAL3T8TDP-1AT1ZABYY MTFDHAL6T4TCU-1AR1ZABYY MTFDHAL6T4TDR-1AT1ZABYY
MTFDHAL7T6TCT-1AR1ZABYY MTFDHAL7T6TDP-1AT1ZABYY MTFDHAL8TATCW-1AR1ZABYY MTFDHBA2T0QFD1AX1AABYY MTFDHBA512TCK-1AS15ABYY