swissbit®

Product Fact Sheet

Industrial mSATA SSD (M0-300 Full Size)

X-75m Series SATA Gen3 - 6.0 Gbit/s, 3D TLC

Commercial and Industrial Temperature Grade

Date: April 14, 2020 Revision: 1.02



Product Fact Sheet X-75m Series



Product Summary

- Capacities: 30 GBytes, 60 GBytes, 120 GBytes, 240 GBytes, 480 GBytes, 960 GBytes
- Form Factor: JEDEC MO-300 Full Size mSATA SSD (50.8 mm x 29.85 mm x 3.8 mm)
- Compliance: SATA Gen3 6 Gbit/s (Gen2 3 Gbit/s and Gen1 1.5 Gbit/s backward compatible)
- Command Sets: Supports ATA/ATAPI-8 and ACS-2
- Performance:
 - o Read Performance: Sequential Read up to 565 MBytes/s, Random Read 4K up to 73,600 IOPS
 - Write Performance: Sequential Write up to 495 MBytes/s, Random Write 4K up to 79,400 IOPS
- Operating Temperature Range1:
 - Commercial: o °C to 70 °C
 - o Industrial: -40 °C to 85 °C
- Storage Temperature Range: -40 °C to 85 °C
- Operating Voltage: 3.3 V ± 5%
- Power (Max): Read (Active): 2.4 W; Write (Active): 3.0 W; Idle: 395 mW; Partial: 100 mW
- Data Retention: 10 Years @ Life Begin; 1 Year @ Life End
- Endurance in TeraBytes Written (TBW) @ Max Capacity²: Sequential WL ≥ 3,240; Client WL ≥ 310; Enterprise WL ≥ 770
- Shock/Vibration: 1,500 g | 50 g
- LDPC ECC with up to 165 bit correction per 1 KByte page
- NAND Flash Technology: Triple-Level Cell (TLC) 3D NAND Flash
- Mean Time Between Failure: > 2,000,000 hours
- Data Reliability: < 1 non-recoverable error per 10¹⁶ bits read

Product Features

- Dynamic and Static Wear Leveling
- Active and Passive Data Care Management
- Lifetime Enhancements
 - Dynamic Bad Block Remapping
 - Write Amplification Reduction
- On-Board Power Fail Protection
- TRIM and NCO Support
- ATA Security Feature Set Support
- DEVSLP Compatible
- In-Field Firmware Update
- Enterprise-Grade Self-Monitoring, Analysis, and Reporting Technology (S.M.A.R.T.)
- 30 µinch Gold-Plated Connector (IPC-6012B Class 2 Compliant)
- End-to-End (E2E) Data Protection
- AES256 Encryption (on request)
- TCG OPAL 2.0 Compliant (on request)
- Swissbit Life Time Monitoring (SBLTM) Tool and SDK for SBLTM (on request)

Why Swissbit?

Swissbit is focused on the design, development, manufacture, and support of leading edge memory and storage solutions for the worldwide OEM/ODM marketplace. As a global supplier, Swissbit recognizes and addressees the higher level of application requirements of today's industrial, Netcom, and automotive customers by providing best-in-class products and services, with uncompromised attention to driving overall value and quality.

Swissbit AG Industriestrasse 4 CH-9552 Bronschhofen Switzerland Revision: 1.02
Template: Doc-3581
File: X-75m_fact_sheet_Rev102
Page 2 0f 2

¹ Adequate airflow is required to ensure the temperature, as reported in the S.M.A.R.T. data, does not exceed 110°C (industrial temperature drive) and 95°C (commercial temperature drive) respectively.

² According to JEDEC (JESD47I), the time to write the full TBW is a minimum of 18 months. Higher average daily data volume reduces the specified TBW. The values listed are estimates and are subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Solid State Drives - SSD category:

Click to view products by Swissbit manufacturer:

Other Similar products are found below:

ATCA7360-MMOD-SATA2 ASD25-MLC064G-CT-160-1 SQF-SM4V2-256G-SBC SD7SN6S-128G-1122 MTFDDAA120MBB2AE1ZABYY SDSDQAD-128G SM668GXB-ACS O1118 SDINADF4-64G-H SQF-S25V4-240G-SCC SQF-SDMM2-256G-S9E
SFSA016GQ1BJ8TO-I-DT-226-STD MTFDDAK060MBD-1AH12ITYY VSF202PC016G-100 AF512GSMEL-VABIP SSDPEKKA020T801
MTFDDAK064MBD-1AH12ITYY EP-SSMSF128AACS APS297F064G-4BTM1GWF HBRPEKNX0202A01 SSDPE21D015TAX1
SSDPED1D015TAX1 SSDPEKKF020T8X1 SSDPEKKR256G7XN SSDPEKKW020T8X1 SSDPEKKW512G801 SSDPEKNW020T801
SSDPEKNW020T9X1 SSDPEL1D380GAX1 SM2280S3G2/120G MTFDDAK1T9QDE-2AV1ZABYY MTFDDAK3T8QDE-2AV1ZABYY
MTFDDAT128MBD-1AK12ITYY MTFDDAV256TDL-1AW12ABYY MTFDDAK2T0TDL-1AW1ZABYY MTFDDAK1T0TDL1AW12ABYY MTFDDAV512TDL-1AW1ZABYY MTFDDAV256TDL-1AW1ZABYY MTFDHAL11TATCW-1AR1ZABYY
MTFDHAL12T8TDR-1AT1ZABYY MTFDHAL1T6TCU-1AR1ZABYY MTFDHAL1T9TCT-1AR1ZABYY MTFDHAL3T8TCT1AR1ZABYY MTFDHAL3T8TDP-1AT1ZABYY MTFDHAL6T4TCU-1AR1ZABYY MTFDHAL6T4TDR-1AT1ZABYY
MTFDHAL7T6TCT-1AR1ZABYY MTFDHAL7T6TDP-1AT1ZABYY MTFDHAL8TATCW-1AR1ZABYY MTFDHBA2T0QFD1AX1AABYY MTFDHBA512TCK-1AS15ABYY