durabit[™] "the better MLC"

swissbit®


Product Fact Sheet

Industrial M.2 SATA SSD

X-60m2 2260 Series SATA Gen3 - 6.0 Gbit/s, MLC

Commercial and Industrial Temperature Grade

Date: August 02, 2019 Revision: 1.09





Product Fact Sheet X-60m2 2260 Series



Product Summary

- Capacities: 30 GBytes, 60 GBytes, 120 GBytes, 240 GBytes, 480 GBytes
- Form Factor: PCI Express™ M.2 (2260) (60 mm x 22 mm x 3.58 mm)
- Compliance: SATA Gen3 6 Gbit/s (Gen2 3 Gbit/s and Gen1 1.5 Gbit/s backward compatible)
- Command Sets: Supports ATA/ATAPI-8 and ACS-2
- Performance:
 - o Read Performance: Sequential Read up to 520 MBytes/s, Random Read 4K up to 75,000 IOPS
 - Write Performance: Sequential Write up to 450 MBytes/s, Random Write 4K up to 75,000 IOPS
- Operating Temperature Range*:
 - o Commercial: o °C to 70 °C
 - o Industrial: -40 °C to 85 °C
- Storage Temperature Range: -40 °C to 85 °C
- Operating Voltage: 3.3 V ± 5%
- Power (Max): Read (Active): 1.5 W; Write (Active): 3.2 W; Idle: 380 mW; Slumber: 115 mW
- Data Retention: 10 Years @ Life Begin; 1 Year @ Life End
- Endurance in TeraBytes Written (TBW) Max Capacity†: Client > 975; Embedded > 280; Enterprise > 235
- Shock/Vibration: 1,500 g / 50 g
- Hardware BCH Code ECC: up to 66 bit correction per 1 KByte page
- NAND Flash Technology: Multi-Level Cell (MLC)
- Mean Time Between Failure: > 2,000,000 hours
- Data Reliability: < 1 non-recoverable error per 10¹⁶ bits read

Product Features

- Best-in-Class Performance and Endurance with durabit™ Technology
- Dynamic and Static Wear Leveling
- Subpage Mode Flash Translation Layer (FTL)
- Active and Passive Data Care Management
- Lifetime Enhancements
 - Dynamic Bad Block Remapping
 - Write Amplification Reduction
- On-Board Power Fail Protection
- AHCI, TRIM, and NCQ Support
- ATA Security Feature Set Support
- DEVSLP Compatible
- In-Field Firmware Update
- Enterprise-Grade Self-Monitoring, Analysis, and Reporting Technology (S.M.A.R.T.)
- 30 µinch Gold-Plated Connector (IPC-6012B Class 2 Compliant)
- AES256 Encryption (on request)
- Swissbit Life Time Monitoring (SBLTM) Tool and SDK for SBLTM (on request)

Why Swissbit?

Swissbit is focused on the design, development, manufacture, and support of leading edge memory and storage solutions for the worldwide OEM/ODM marketplace. As a global supplier, Swissbit recognizes and addressees the higher level of application requirements of today's industrial, Netcom, and automotive customers by providing best-in-class products and services, with uncompromised attention to driving overall value and quality.

^{*} Adequate airflow is required to ensure the temperature, as reported in the S.M.A.R.T. data, does not exceed 115°C (industrial temperature drive) and 100°C (commercial temperature drive) respectively.

[†] According to JEDEC (JESD47I), the time to write the full TBW is a minimum of 18 months. Higher average daily data volume reduces the specified TBW. The values listed are estimates and are subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Solid State Drives - SSD category:

Click to view products by Swissbit manufacturer:

Other Similar products are found below:

ATCA7360-MMOD-SATA2 ASD25-MLC064G-CT-160-1 SQF-SM4V2-256G-SBC SD7SN6S-128G-1122 MTFDDAA120MBB-2AE1ZABYY SDSDQAD-128G SM668GXB-ACS O1118 SDINADF4-64G-H SQF-S25V4-240G-SCC SQF-SDMM2-256G-S9E SFSA016GQ1BJ8TO-I-DT-226-STD MTFDDAK060MBD-1AH12ITYY VSF202PC016G-100 AF512GSMEL-VABIP SSDPEKKA020T801 MTFDDAK064MBD-1AH12ITYY EP-SSMSF128AACS APS297F064G-4BTM1GWF HBRPEKNX0202A01 SSDPE21D015TAX1 SSDPED1D015TAX1 SSDPEKKF020T8X1 SSDPEKKR256G7XN SSDPEKKW020T8X1 SSDPEKKW512G801 SSDPEKNW020T801 SSDPEKNW020T9X1 SSDPELID380GAX1 SM2280S3G2/120G MTFDDAK1T9QDE-2AV1ZABYY MTFDDAK3T8QDE-2AV1ZABYY MTFDDAT128MBD-1AK12ITYY MTFDDAV256TDL-1AW12ABYY MTFDDAK1T0TDL-1AW12ABYY MTFDDAV512TDL-1AW1ZABYY MTFDDAV256TDL-1AW1ZABYY MTFDHAL1TATCW-1AR1ZABYY MTFDHAL12T8TDR-1AT1ZABYY MTFDHAL1T6TCU-1AR1ZABYY MTFDHAL1T6TCU-1AR1ZABYY MTFDHAL3T8TDP-1AT1ZABYY MTFDHAL6T4TCU-1AR1ZABYY MTFDHAL5T8TDR-1AT1ZABYY MTFDHAL5TATCU-1AR1ZABYY MTFDHBA512TCK-1AS15ABYY MTFDHBA512TCK-1AS15ABYY MTFDHBA512TCK-1AS15ABYY SDAPMUW-128G-1022