everbit™

swissbit®

Product Fact Sheet

Industrial microSD / SDHC / SDXC Memory Card

S-46u Series UHS-I Interface, pSLC

Extended and Industrial Temperature Grade

Date: Revision: March 29, 2019 1.01





Product Fact Sheet S-46u Series



Product Summary

- Capacities: 2 GBytes, 4 GBytes, 8 GBytes, 16 GBytes, 32 GBytes, 64 GBytes
- Form Factor: Standard microSD memory Card form factor: 15.0mm x 11.0mm x 0.7mm (1.0mm)
- Compliance: Fully compliant with SD Memory Card specification 2.0 and
 - 3.0 and MICRO SD Memory Card Addendum 4.00
 - \circ $\:$ SD/SDHC/SDXC default/high speed mode and UHS supported
 - Up to speed class 10 and U3 according SD3.0 specification
 - FAT16, FAT32 or exFAT preformatted
- **Performance:** High performance 3.0 specification
 - SD Default speed, SD High speed, SD UHS-I
 - Read Performance: Sequential Read up to 46 MBytes/s, Random Read IOPS up to 1,433
 - Write Performance: Sequential Write up to 41 MBytes/s, Random Write IOPS up to 1,249
- Operating Temperature Range*:
 - Extended: -25 to 85 °C
 - Industrial: -40 to 85 °C
- Storage Temperature Range:
 - Extended: -25 to 100 °C
 - Industrial: -40 to 100 °C
- **Operating Voltage:** 2.7 ... 3.6V normal operating voltage (Low-power CMOS technology)
- Data Retention: 10 years @ Life Begin / 1 Year @ Life End
- Humidity: 85% RH @85°C 1000h
- Electromagnetic Compatibility Test: Radiated Emission; Radiated Immunity; Electrostatic Discharge

Product Features

- Optimized FW algorithms especially for high read access and long data retention applications
 - Patented power-off reliability technology, Wear Leveling technology
 - o Write Endurance technology, Read Disturb Management
 - Data Care Management, Near miss ECC technology
 - \circ $\;$ Diagnostic features with Life Time Monitoring tool support
- High reliability
 - S-46u cards with pseudo SLC (pSLC) feature higher write performance and endurance than MLC based cards (S-45u)
 - The product is optimized for long life cycle and provides excellent data retention in high temperature mission profiles.
 - \circ Number of card insertions/removals up to 20,000
 - SIP (System In Package) process for extreme dust, water and ESD proof
 - Selected AEC-Q100 qualification
- Manufactured in a TS 16949 certified factory
- Controlled BOM & PCN process
- Customized options like CID registers, CPRM keys, firmware incl. settings and marking by projects
- In-Field Firmware Update
- Swissbit Life Time Monitoring (SBLTM) Tool and SDK for SBLTM (on request)

Why Swissbit?

Swissbit is focused on the design, development, manufacture, and support of leading edge memory and storage solutions for the worldwide OEM/ODM marketplace. As a global supplier, Swissbit recognizes and addressees the higher level of application requirements of today's industrial, Netcom, and automotive customers by providing best-in-class products and services, with uncompromised attention to driving overall value and quality.

^{*} High Temperature storage without operation reduces the data retention, in operation the data will be refreshed, if data error issues were detected

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Memory Cards category:

Click to view products by Swissbit manufacturer:

Other Similar products are found below :

SQF-ISDS1-8G-21C USDCOEM-32GB LMEX1L128GG2 LMEX1L256GG2 LMEX1L016GG2 LMEX1L032GG2 LMEX1L064GG2 SDSDQAF4-032G-I SDSDQAF4-256G-I AP-CF016GKBNS-ETNRG CFLSH-016SDG MS-C6-8G HMC-EF283 SDCFXPS-032G-X46 SDCFXSB-128G-G46 SDSDQB-032G-B35 SDSDQM-032G-B35A SDU4GDMGRB SDU4GDPGRB 5788667-1-CUT-TAPE RP-SMLE32DA1 SDC4GDPGRB 2729389 VTDCFBPI004G SDSDAF3-016G-XI 2403484 VTDS41PI008G SDSDAF3-016G-I VSFCS2CC060G SDSDAF3-032G-XI SDSDAD-016G SDSDAF3-008G-XI SDSDAF3-008G-I SDSDQAB-016G-J VTDCFBPI008G M1A0-0160R12 M1A0-0320R12 M1A4-0320R12 M1AA-0160R12 M1AA-0320R12 M1AA-0640R12 M1AA-1280R12 SDCFXPS-256G-X46 SDSDXPK-128G-GN4IN SDSDXXG-032G-GN4IN SDSDXXY-064G-GN4IN SDSDXXY-128G-GN4IN SDSDXXY-512G-GN4IN SDSQXA1-128G-GN6MA SDSQXA1-256G-GN6MA