durabit™ "the better MLC"

swissbit®

Product Fact Sheet

Industrial microSDHC / SDXC Memory Card

S-45u Series
UHS-I Interface, MLC

Extended and Industrial Temperature Grade

Date: April 08, 2019

Revision: 1.24







Product Summary

- Capacities: 4 GBytes, 8 GBytes, 16 GBytes, 32 GBytes, 64 GBytes, 128 GBytes
- Form Factor: Standard microSD Memory card form factor 15.0mm x 11.0mm x 0.7mm (1.0mm)
- Compliance: Fully compliant with SD Memory Card specification 2.0 and
 - 3.0 and MICRO SD Memory Card Addendum 4.00
 - SDHC/SDXC default/high speed mode and UHS supported
 - Up to speed class 10 and U1 and according SD3.0 specification
 - FAT32 / exFAT preformatted
- Performance:
 - SD Default speed, SD High speed, SD UHS-I
 - o Read Performance: Sequential Read up to 44 MBytes/s, Random Read IOPS up to 1,349
 - Write Performance: Sequential Write up to 22 MBytes/s, Random Write IOPS up to 966
- Operating Temperature Range¹:
 - o Extended: -25 °C to 85 °C
 - o Industrial: -40 °C to 85 °C
- Storage Temperature Range:
 - o Extended: -25 °C to 100 °C
 - o Industrial: -40 °C to 100 °C
- Operating Voltage: 2.7...3.6V normal operating voltage (Low-power CMOS technology)
- Data Retention: 10 Years @ Life Begin / 1 Year @ Life End
- Humidity: 85% RH @85°C 1000h
- Electromagnetic Compatibility Test: Radiated Emission; Radiated Immunity; Electrostatic Discharge

Product Features

- Optimized FW algorithms especially for high read access and long data retention applications
 - Patented power-off reliability technology, Wear Leveling technology
 - o Write Endurance technology, Read Disturb Management
 - Data Care Management, Near miss ECC technology
 - o Diagnostic features with Life Time Monitoring tool support
- High reliability
 - Designed for industrial market especially read intensive application like navigation, infotainment, POS/POI, medical and general boot medium use case
 - The product is optimized for long life cycle and provides excellent data retention in high temperature mission profiles.
 - Number of card insertions/removals 20,000
 - SIP (System In Package) process for extreme dust, water and ESD proof
 - Selected AEC-Q100 qualification
- Manufactured in a TS 16949 certified factory
- Controlled BOM & PCN process
- Customized options like CID registers, CPRM keys, firmware incl. settings and marking by projects
- In-Field Firmware Update
- Swissbit Life Time Monitoring (SBLTM) Tool and SDK for SBLTM (on request)

Why Swissbit?

Swissbit strives to create innovative technologies for future market opportunities utilizing a highly skilled inhouse product research and development team. Swissbit maintains a marketing edge by continuing to manufacture world-class high quality memory products and providing customers with both high value and low cost of ownership achieved through efficient processes and procedures.

¹ High Temperature storage without operation reduces the data retention, in operation the data will be refreshed, if data error issues were detected

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Memory Cards category:

Click to view products by Swissbit manufacturer:

Other Similar products are found below:

SQF-ISDS1-8G-21C USDCOEM-32GB LMEX1L128GG2 LMEX1L256GG2 LMEX1L016GG2 LMEX1L032GG2 LMEX1L064GG2
SDSDQAF4-032G-I SDSDQAF4-256G-I AP-CF016GKBNS-ETNRG CFLSH-016SDG MS-C6-8G WPCFC512M-HFITI-AA
WPMSD001G-PFITI WPMSD002G-PFITI WPMSD004G-PFISMAS WPMSD008G-PFISM WPMSD008G-PFISMAS WPMSD016GPFISM WPMSD016G-PFISMAS WPSDC001G-EAITI WPSDC002G-EAITI SPSDH008G-PFCSM SPSDH016G-PTCT5AS SPSDH032GPTCT5AS HMC-EF283 SDCFXPS-032G-X46 SDCFXSB-128G-G46 SDSDQB-032G-B35 SDSDQM-032G-B35A SDU4GDMGRB
SDU4GDPGRB 5788667-1-CUT-TAPE RP-SMLE32DA1 SDC4GDPGRB 2729389 VTDCFBPI004G SDSDAF3-016G-XI 2403484
VTDS41PI008G SDSDAF3-016G-I VSFCS2CC060G SDSDAF3-032G-XI SDSDAD-016G SDSDAF3-008G-XI SDSDAF3-008G-I
SDSDQAB-016G-J VTDCFBPI008G M1A0-0160R12 M1A0-0320R12