

# swissbit®

## Product Fact Sheet

### Industrial USB Flash Drive Module

#### U-450 Series USB 2.0 High-Speed, SLC

Commercial and Industrial  
Temperature Grade

Date: January 26, 2023  
Revision: 1.02



## Product Summary

- **Capacities:** 1 GByte, 2 GBytes, 4 Gbytes, 8 GBytes, 16 GBytes
- **Form Factor:**
  - USB 2.0 solid state flash drive for internal 10-pin USB connector terminal (26.65mm x 36.8mm)
  - 2.54mm or 2.00mm connector with keyed pin
- **Compliance:** USB 2.0 High-Speed specification compatible (backward compliance with USB 1.1)
- **Performance:**
  - Read Performance: Sequential Read up to 36 MBytes/s, Random Read IOPS up to 1,900
  - Write Performance: Sequential Write up to 26 MBytes/s, Random Write IOPS up to 1,400
- **Operating Temperature Range:**
  - Commercial: 0 °C to 70 °C
  - Industrial: -40 °C to 85 °C
- **Storage Temperature Range:** -40 °C to 85 °C
- **Operating Voltage:** 3.3V ±5% or 5V ± 10%
- **Data Retention:** 10 Years @ Life Begin; 1 Year @ Life End
- **Endurance in TeraBytes Written (TBW):**
  - Enterprise Workload: up to 101
- **Shock/Vibration:** 1,500 *g* / 50 *g*
- **High-Performance 32-Bit Processor with Integrated, Parallel Flash Interface Engine:**
  - Single-Level Cell (SLC) NAND Flash
  - Hardware BCH Code ECC (up to 60bit correction per 1024 Bytes)
- **High Reliability:**
  - Mean Time Between Failure (MTBF): > 3,000,000 hours @ 25°C
  - Data Reliability: < 1 non-recoverable error per 10<sup>17</sup> bits read

## Product Features

- Subpage based Flash management for increased endurance & random performance
- Optimized FW algorithms especially for high read access and long data retention applications
  - Proven power fail management for highest reliability
  - Near Miss ECC technology
  - Read Disturb Management
  - Wear Leveling technology
  - Data Care Management
- Detailed S.M.A.R.T. support and extended vendor information
- LED for operation indication
- In-field firmware update
- Swissbit Life Time Monitoring (SBLTM) tool and SDK for SBLTM (on request)
- Controlled BOM & PCN process
- Customized options like registers, removable device, connector options, write protect switch, grounded mounting hole, densities, uploads, label, etc.

### Why Swissbit?

Swissbit is focused on the design, development, manufacture, and support of leading edge memory and storage solutions for the worldwide OEM/ODM marketplace. As a global supplier, Swissbit recognizes and addresses the higher level of application requirements of today's industrial, Netcom, and automotive customers by providing best-in-class products and services, with uncompromised attention to driving overall value and quality.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Flash Drives](#) category:*

*Click to view products by [Swissbit](#) manufacturer:*

Other Similar products are found below :

[100014877](#) [6921734937223](#) [6921734937209](#) [USB-FLASH-8GB \(THN-U202W0080E4\)](#) [UPI2-0160K0R11](#) [UTS2-0160K0R11](#) [UTS3-0160K0R11](#) [UTS3-0320K0R11](#) [UTS3-0640K0R11](#) [SDDD3-064G-G46](#) [UUN2-0320S0R11](#) [UUN2-0160S0R11](#) [UTS3-1280K0R11](#) [UTS2-1280K0R11](#) [UTS2-0640K0R11](#) [UTS2-0080K0R11](#) [UCU2-0160K0R11](#) [SDUFD51-032G](#) [2402809](#) [SDUFD33-032G](#) [APHA016GAG0CG-3TM](#) [APHA001GR13CG-6T](#) [SDUFDEC-016G](#) [SDUFD33-016G](#) [SDCZ430-032G-G46](#) [SDCZ430-064G-G46](#) [SDCZ430-128G-G46](#) [SDCZ430-256G-G46](#) [SDCZ48-256G-U46](#) [SDCZ73-032G-G46](#) [SDCZ73-064G-G46](#) [SDCZ73-128G-G46](#) [SDDD3-256G-G46](#) [SDDDC2-032G-G46](#) [SDDDC2-064G-G46](#) [SDDDC2-128G-G46](#) [SDDDC2-256G-G46](#) [SDDD3-032G-G46](#) [SDDD3-128G-G46](#) [SDCZ48-032G-U46](#) [SDCZ48-064G-U46](#) [SDCZ48-128G-U46](#) [AP64GAH355B](#) [USB3FKEY16B](#) [USB3FKEY256B](#) [USB3FKEY64B](#) [USB3FTVKEY6A128ZNCAPAPAUV](#) [USB3FTVKEY6A32ZNCAPAPAUV](#) [USB3FTVKEY6A256ZNCAPAPAUV](#) [USB3FTVKEY6A128GCAPAPAUV](#)