

### **Harsh Environment Connectivity Solutions**



**DIN Cable Mount** 

Male and female cord plug with shielded barrel or insulated snaplock plastic body. Two piece metal barrel surrounds pin insert to form an electrical shield. The entire insert assembly is held together by snapping the insulated plastic shell over the assembly. The barrel's special metal tab locks the shell in place. Standard color of plastic shell is gray. All-purpose cable clamp.

**Type 15GM7M - typical:** Male cord plug with shielded barrel and insulated snaplock plastic body. Two piece metal barrel surrounds pin insert to form an electrical shield. The entire insert assembly is held together by snapping the insulated plastic shell over the assembly. The barrel's special metal tab locks the shell in place. Standard color of plastic shell is gray. All-purpose cable clamp.

#### ORDERING INFORMATION

Part Number	Description	Pin
	Description	Arrangement
05GM3M	3 pins at 180°, Gray body and strain relief.	2
05GM5M	5 pins at 180°, Gray body and strain relief	5
09GM4M	4 pins at 210°, Gray body and strain relief	3
12GM5M	5 pins at 240°, Gray body and strain relief	4
12GM6M	6 pins at 240°, Gray body and strain relief	6
15GM7M	7 pins at 270°, Gray body and strain relief	7
15GM8M	8 pins at 270°, Gray body and strain relief	8
20GM8M	8 pins at 262°, Gray body and strain relief	10

#### **ELECTRICAL**

• Contact Resistance: Cord Plugs and Receptacles; .010 ohms, contact spring/pin .030 ohms,

4/11/2016 Switchcraft: Specification

ground clip/shell. Control and Switching Receptacles; .015 ohms, contact spring/pin; .020 ohms, switch contacts.

• Dielectric Withstanding Voltage: 500 V (rms)

Contact Rating: 5-pin; 3A, 34 V DC
 Leakage Resistance: 10<sup>5</sup>M (ohm)

• Recommended Wire Size: 22 wire gauge maximum

## **MECHANICAL**

## **Insertion/Withdrawal Forces:**

Number of Contacts	Insertion Force pound/N	Withdrawal Force pound/N
2	3.6/(16)	.45- 2.7/(2-12)
3	5.4/(24)	.67- 4.1/(3-18)
4	7.2/(32)	.90- 5.4/(4-24)
5	9.0/(40)	1.24- 6.8/(5.5-30)
6	10.8/(48)	1.46- 8.1/(6.5-36)
7	12.6/(56)	1.68- 9.5/(7.5-42)
8	14.4/(6	

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN Connectors category:

Click to view products by Switchcraft manufacturer:

Other Similar products are found below:

60KD4M 12DL6MX 12JL6M 164-183 17DN100-EX 17DN101-EX SMD7FRA011 16PJ224-E 171-0278 17PP048-EX M55116/1-2

KQLAX-8P M55116/10-0 SMD5FRA021 15AN84X 13AL6FX 61GA5F 152-002-2-4 0134 05 MDC-004 MDC-104 MDC-204 MDC-208

12BPKG DC-001 DC-007 591-0400 591-0500 DS1093-01-BN40 593-0700 MJ-372-4 MJ-372-6 MJ-372-8 57PC5M 592-0301 592-0511

164-377 610-0520 0105 05 0105 08 0107 08-1 690-0300 0132 05 930009200 MAB 4 930071200 MAB 5 S 930303517 MAB 3100 S

GRAU 930345200 MAB 8 S 930356517 MAS 70 S GRAU 930952517 MAB 5100 930954517 MAB 6100 GRAU