

## **Harsh Environment Connectivity Solutions**



Locking DIN Cable Mount

Male plug with ground key-rib. Unique 30° turn lockring securely fastens two halves of connector. Mates with lock flange female connectors and receptacles. Insert screw holds insert assembly in shell and also retains lockring on shell. Flexible black strain relief with 7/32" diameter cable entry. Heavy duty clamp.

#### **ELECTRICAL**

#### • Contact Resistance:

- Cord Plugs and Receptacles; .010 ohms, contact spring/pin .030 ohms, ground clip/shell.
- Control and Switching Receptacles; .015 ohms, contact spring/pin; .020 ohms, switch contacts.
- Dielectric Withstanding Voltage: 500 V (rms)
- Contact Rating: 5-pin; 3A, 34 V DC
- Leakage Resistance: 10<sup>5</sup>M (ohm)
- Recommended Wire Size: 22 wire gauge maximum

#### **MECHANICAL**

#### **Insertion/Withdrawal Forces:**

Number of Contacts	Insertion Force pound/N	Withdrawal Force pound/N
2	3.6/(16)	.45- 2.7/(2-12)
3	5.4/(24)	.67- 4.1/(3-18)
4	7.2/(32)	.90- 5.4/(4-24)
5	9.0/(40)	1.24- 6.8/(5.5-30)
6	10.8/(48)	1.46- 8.1/(6.5-36)
7	12.6/(56)	1.68- 9.5/(7.5-42)
8	14.4/(64)	1.90-10.8/(8.5-48)

NOTE: All connectors meet DIN specifications #41524. Din spec. numbers (except for 4-pin, 5-pin @ 240°, and 8-pin @ 262°)

### **MATERIAL**

Shell: Die-cast zinc alloy, nickel-plated
Receptacle Mounting Flange: Steel

Receptacle Body: PlasticInsert Material: Plastic

Socket Contacts: Tin-platedPin Contacts: Tin-plated

Switching Contacts: Silver-platedCable Relief Bushing: Soft plastic

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN Connectors category:

Click to view products by Switchcraft manufacturer:

Other Similar products are found below:

60KD4M 12DL6MX 12JL6M 17DN100-EX 17DN101-EX SMD7FRA011 16PJ224-E M55116/1-2 KQLAX-8P 164-229-6-5 M55116/10-0 SMD5FRA021 15AN84X 13AL6FX 61GA5F 152-002-2-4 0134 05 MDC-004 MDC-104 MDC-204 MDC-208 12BPKG DC-001 591-0400 591-0500 DS1093-01-BN40 593-0700 MJ-372-4 MJ-372-6 MJ-372-8 57PC5M 591-0800 592-0301 592-0511 164-377 610-0520 0105 05 0105 08 0107 08-1 690-0300 0132 05 930009200 MAB 4 930071200 MAB 5 S 930303517 MAB 3100 S GRAU 930345200 MAB 8 S 930356517 MAS 70 S GRAU 930778500 MAB 6 H 930959517 MAK 4100 930961517 MAK 5100 S 930964517 MAS 5100