

Switchcraft®

3.5 mm Inline Jacks



35LJN Series

3.5 mm Inline Jacks

Features & Benefits

- Solid metal housing.
- Available with gold or silver contacts.
- Two piece design simplifies termination
- Rated to 5000 insertion/withdrawal cycles
- Mates with 35HD series locking or non-locking plugs

Material Specifications

Housing: Copper alloy, nickel plated

Handle: Copper alloy, nickel plated

Cable Clamp: Steel, tin-plated

Tip & Ring: Copper alloy, silver or gold plated

Insulator: Thermoplastic

Specifications

Electrical Specifications

Contact Resistance: 0.020 ohms

Insulation Resistance : 2000 megohms

Dielectric Withstand Voltage: 250VAC

Mechanical Specifications

Insertion Force: 8 lbs MAX

Withdrawal Force: 1lbs MIN

Life Cycles: 5K

Max Soldering Temp/Time: 800°F/10s
or 700°F/20s

**Vibration per MIL-STD-202F
Method 201**

**Thermal Shock per MIL-STD-202F
Method 107G**

3.5mm Inline Jacks				
P/N	Contact Plating		Cable Opening	
	Silver	Gold	0.175"	0.290"
35LJN	X			X
35LJNAU		X		X
35LJBNS	X		X	
35LJNAUS		X	X	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Phone Connectors](#) category:

Click to view products by [Switchcraft](#) manufacturer:

Other Similar products are found below :

[M444B](#) [6J1041A](#) [R4F](#) [E12BPKG](#) [ECP4PKG](#) [161-3502L-E](#) [MT333X](#) [171-0350-EX](#) [171-101A-EX](#) [171-3325-EX](#) [176S](#) [NC3MG-V](#)
[NS112BX](#) [NYS228G](#) [P10834](#) [P2380](#) [P2381X](#) [P2411X](#) [P2412](#) [P2724](#) [JM2PB-AU BULK](#) [9144](#) [S2674](#) [280L](#) [163-158N-2-E](#) [171-3308-EX](#)
[171-3500-E](#) [2501FT](#) [CMT335](#) [M10662](#) [330Q](#) [RJ5VI-S](#) [40116](#) [TM1R-AU](#) [TM2PBMJ-AU](#) [TM2PJ-AU](#) [TM2PJ-AU BULK](#) [4803.1351](#)
[49201](#) [49205](#) [TS3PBJ-AU](#) [TS3PBMJ-AU](#) [TT32BX](#) [54B](#) [40112](#) [40205](#) [415](#) [XMT332B](#) [52170017-331](#) [570](#)