

NOTES:

- 1. RATED 15 AMP, 24 VOLT DC AT 105° C (CURRENT CARRY ONLY) WHEN USING 14 AWG STRANDED CONDUCTOR CABLE.
- 2. USE CABLE LUBE WHEN ASSEMBLING CABLE.
- 3. IP68 RATED WHEN MATED TO ST15S JACK.
- 4. HANDLE SHIPPED UNASSEMBLED.
- 5. THIS PRODUCT IS ROHS COMPLIANT.

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY. SIZE MULT **TEMPER UNLESS OTHERWISE SPECIFIED** 1. ALL DIMENSIONS IN INCHES [mm] **FINISH** MATERIAL - TWO PLACE DECIMALS ±0.02 [0.5] FIRST USED ON SCALE - THREE PLACE DECIMALS ±0.005 [0.13] 2:1 DATE DRAWN CHKD APVD TJK SRC SRC 5-13-19 28515 7/18/22 TJK TJK 6-29-22 7/26/22 SHEET 1 of 1 PART No. REV ECO NUMBER DATE BY APVD S15KS SERIES 15 AMP SEALED PLUG, RoHS Α DO NOT SCALE DRAWING **REVISIONS**

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Connectors category:

Click to view products by Switchcraft manufacturer:

Other Similar products are found below:

KLDX-SMT-0202-BPTR 171-0722-E K596 KLD-0201-BC 4C6831AX 10073976-112LF LCB60PW-M LCB30PW-M LCB60PB-M LCC30PB-M LCB50PW-M LCB50-F LCC30-M LCB40PW-M LCC30PW-M LCB50-F LCB40-F LCB30-F LCC40-M LCC40PB-M LCB40PB-M LCB40PB-M LCC40-F LCB60-M LCC40PW-M LCB50PB-M DC-002-100 DC-031A-130 DC-031A-100 DC-003A-130 DC-045-130 DC-192-130 DC-033-130 DC-011-100 DC-002F-130 DC-002-130 DB-14-2F DC-183B DC-060-04A DC-099-200 DC-015-250-A DC-016-200-A DC-005A-200 DC-044A-200 DC-088-200 DC-022A-200 DC-038-150 DC-012A-250 DC-005C-130 DC-012A-200