

SC800 Instrument Direct Box Audio Specifications

Switchcraft®

Parameter	Performance	Conditions	
Frequency Response	10Hz - 40kHz	+/-0.3dB, ref 1kHz	
Total Harmonic Distortion + Noise	< 0.006% <0.05%	at 1kHz, +4dBu Input, 22kHz Bandwidth at 20Hz, +4dBu Input, 22kHz Bandwidth	
Maximum Input Level	+21dBu	at 20Hz with 1% THD+Noise	
Input Impedance	> 150kΩ	at 1kHz	
Output Impedance	< 170Ω	at 1kHz	
Common Mode Rejection Ratio (CMRR)	>100dB	at 60Hz	
Deviation from Linear Phase	< 3° < 1° < 16°	at 20Hz at 1kHz at 20kHz	
Voltage Gain	-23dB -43dB	+/-1dB +/-1dB with 20dB pad engaged	
Pad Attenuation	20dB	+/-1dB	

Notes: All measurements were taken with a 25Ω unbalanced source and measured from the XLR with a $1k\Omega$ balanced load. Specifications subject to change without notice.

CUSTOMER DRAWING


SCALE 1:1		(GL®
DATE DRAWN		
3/2/10	SHEET 2 OF 3	
DRAWN BY	PART No.	REV
ВНМ	SC800	Α

6

5

SolidW

SolidWorks CAD File C



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Patch Panels category:

Click to view products by Switchcraft manufacturer:

Other Similar products are found below:

MMVP96K2N75T MMVP96K2NNT MMVP96K2NT MMVP96K3NNT QGPK1LCM QGPK3CAT5E QGPK3CAT5ES QGPK3LC

QGPK3LCM QGPK3ST QGPK3STM DS303 DS311 DS317 JS-16 JSH-24 QGPK1CAT5ES QGPK1CAT6S QGPK1LC QGPK1SC

QGPK1SCM QGPK1ST QGPK1STM QGPK3CAT6 QGPK3CAT6S QGPK3SC TT91202 TT91402 MMVP48K275T MMVP48K2NNT

MMVP48K2NT MMVP96K275T MMVP96K375T MMVP96K3N75T JSIS-72 K576 DS385 Switchcraft TT518 TT95DC TT91002

DS368 JS-36A JSI-8D2SF24 JSIX-64S JS-52W JSI-40S K6004B 314DI K6002D MMVPTL