

CUSTOMER DRAWING

1. PARTS ARE SHIPPED UNASSEMBLED
2. THESE ASSEMBLIES ARE ROHS COMPLIANT
3. SEE SHEET 2 FOR SPECIFICATIONS

REV	ECO NUMBER	DATE	BY	APVD
A	ECO 27926	8-17-17	SRC	TJK
REVISIONS				

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES [mm]
- TWO PLACE DECIMALS ±0.02 [0.5]
- THREE PLACE DECIMALS ±0.005 [0.13]

DO NOT SCALE DRAWING

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
SIZE *	WIDTH *	MULT *	LBS/M *	TEMPER *					
FINISH *					MATERIAL *				
SPEC No. *					SPEC No. *				
FIRST USED ON *			SCALE 1:1						
DATE DRAWN	BY	CHKD	APVD						
12-21+16	SRC	SRC	TJK						
			12-21-16	8-17-17	SHEET 1 OF 2				
NAME					PART No.		REV		
CABLE POWER JACK					ST10UC SERIES		A		

SolidWorks CAD File

Mechanical Specifications

Life: Mechanical only
 Vibration: 5000 cycles minimum using S10 style plugs
 Operating Forces: Mil-Std 202G Method 201A (jack or when mated with locking plug)
 3 lb maximum insertion. 0.2 lb minimum withdrawal when using S10 type plug

Electrical Specifications

Voltage Rating: 24 V AC/DC
 Current Rating: Refer to current rating table below
 Insulation Resistance: 1000M Ω min. initial
 Contact Resistance (initial): 10 m Ω max

Environmental Specifications

Operating Temperature Rating: -40 °C to +105 °C (-40°F to +221°F)
 Insulation Resistance: MIL-STD 202G Method 302 Condition B Only
 Thermal Shock: MIL-STD 202G Method 107G (jack or when mated with sealed locking plug)


Material Specifications

Handle, Housing, Flex relief: Copper alloy, nickel plated
 Insulator: Thermoplastic elastomer
 Center Pin: Thermoplastic, black
 Center & Shunt Terminals: Copper Alloy, Gold over Silver Plated
 Sleeve Spring Contact: Copper Alloy, Matte Tin Plated
 Copper Alloy, Gold over Silver Plated

CURRENT CARRY WHEN MATED TO A S10 STYLE PLUG

Wire (awg)	Current Rating (Amps) at Operating Temperature (° C)			
	90° C max	95° C max	100° C max	105° C max
16	13	12	11	10
18	12	11	10	9
20	11	10	9	8

Note: AC/DC Power Plugs & Jacks are for current carry only. Do not connect or disconnect under load. The circuitry on-off switch should be off before connecting or disconnecting the Power Plug to Jack.

SCALE 1:1		
DATE DRAWN 12-21-16		
DRAWN BY SRC	PART No. ST10UC SERIES_CD	REV A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Connectors](#) category:

Click to view products by [Switchcraft](#) manufacturer:

Other Similar products are found below :

[RAPC3FG](#) [B04P-VL-VN-1.8](#) [1600206-1](#) [163-0302](#) [163-0310-EX](#) [163-4024](#) [163-4117-EX](#) [163-5005-E](#) [163-7421](#) [171-0721-EX](#) [171-3118-EX](#) [173-23507-ST-EX](#) [KLDVX-SMT-02-ATR](#) [KLDX-SMT-0202-BP](#) [KLDX-SMT-0202-BPTR](#) [163-0179-EX](#) [163-0307-E](#) [163-4119-E](#) [171-0722-E](#) [171-3218-EX](#) [171-7391](#) [173-3413-ST-EX](#) [RAPCBRK](#) [K596](#) [KLD-0201-BC](#) [KLDVX-SMT-02-BTR](#) [KPPX-D](#) [TPCF-140-01-L-Q-4-RA](#) [RAPC3MHG](#) [RASM752TRX](#) [163-4800-E](#) [4C6831AX](#) [TS3PNJ](#) [DC-025LM-5A-2.5](#) [CL14218R](#) [AS250F RED](#) [DC-105-4A-1.6](#) [09441 AS120-F](#) [09442 AS120-M](#) [CP30240](#) [TAMIYA-M](#) [TAMIYA-MT1](#) [TAMIYA-MT2](#) [4840.1200](#) [4840.2202](#) [C5080HI-04P-18 + C5080HI-C](#) [JC-138](#) [JPO-25 \(FC6814\)](#) [JYO-26 \(FC6811\)](#) [JYO-29 \(FC68102\)](#)