



DIMENSIONS SHOWN ARE REFERENCE ONLY

NOTES:

1. MEETS SMPTE 2082-1
CHARACTERISTIC IMPEDANCE :75 OHMS
CONTACT RESISTANCE: 50 MILLIOHMS MAX.
2. WIRING: CENTER CONTACT TO CENTER CONTACTS
GROUND SLEEVE TO GROUND SLEEVE
3. MATERIAL:
PLUG: COPPER ALLOY, NICKEL PLATED.
CONTACT: COPPER ALLOY, GOLD PLATED.
INSULATOR: TEFLON
CABLE: SILVER PLATED CONDUCTOR, COPPER/TIN SHIELD.
OVERMOLD: THERMOPLASTIC ELASTOMER
4. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					FINISH			MATERIAL	
					SPEC No.			SPEC No.	
					FIRST USED ON		SCALE		
							3:2		
DATE DRAWN		BY	CHKD	APVD					
5/01/17		PNK	PNK	SRC					
			5/01/17	5/01/17					
REV					NAME			PART No.	
ECO NUMBER					LOOPING PLUG			VMMLPUHD	
DATE					UHD MICRO, OVERMOLDED, RoHS			REV	
BY									
APVD									
REVISIONS					DO NOT SCALE DRAWING				
0A	PDR 16006	5/01/17	PNK	SRC					

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Patch Panels](#) category:

Click to view products by [SWITCHCRAFT](#) manufacturer:

Other Similar products are found below :

[MMVP96K2N75T](#) [MMVP96K2NNT](#) [MMVP96K2NT](#) [MMVP96K3NNT](#) [QGPK1LCM](#) [QGPK3CAT5E](#) [QGPK3CAT5ES](#) [QGPK3LC](#)
[QGPK3LCM](#) [QGPK3ST](#) [QGPK3STM](#) [DS303](#) [DS311](#) [DS317](#) [JS-16](#) [JSH-24](#) [QGPK1CAT5ES](#) [QGPK1CAT6S](#) [QGPK1LC](#) [QGPK1SC](#)
[QGPK1SCM](#) [QGPK1ST](#) [QGPK1STM](#) [QGPK3CAT6](#) [QGPK3CAT6S](#) [QGPK3SC](#) [TT91202](#) [TT91402](#) [MMVP48K275T](#) [MMVP48K2NNT](#)
[MMVP48K2NT](#) [MMVP96K275T](#) [MMVP96K375T](#) [MMVP96K3N75T](#) [JSIS-72](#) [K576](#) [DS385](#) [Switchcraft TT518](#) [TT95DC](#) [TT91002](#)
[DS368](#) [JS-36A](#) [JSI-8D2SF24](#) [JSIX-64S](#) [JS-52W](#) [JSI-40S](#) [K6004B](#) [314DI](#) [K6002D](#) [MMVPTL](#)