
Extruded Sleeving H

Sleeving H is an extruded silicone sleeving.

Attributes

Sleeving H is flexible, non-transparent and available in various colours. Due to the silicone rubber coating, this sleeving provides high permanent temperature resistance of class H (180 °C) and thermal resistance up to 200 °C; the special quality version guarantees thermal resistance up to 250 °C.

Application

Sleeving H is used as lightweight, additional mechanical protection for applications with very high thermal stress. Furthermore, it offers additional electrical insulation for cables and enamelled copper wires in electric machines and transformers as well as in certain electronic applications.

Standards

Acc. IEC 60684-123/124

UL 94HB compliant

RoHS compliant according to 2011/65/EU

Delivery forms

Standard: transparent (inner diameter / ID 5)

Special colours on request:

Red, blue, white, black (ID5) and green (ID2)

Length in m on a cardboard ring:

0.3 - 2.0 mm 200 m rings/ cardboard spools

2.5 - 3.5 mm 100 m rings/ cardboard spools

4.0 - 9.0 mm 100 m rings

10.0 mm 50 m rings

14.0 - 30.0 mm on request

All dimensions can be delivered in adapted lengths.

	Unit of measure						
Inner diameter (ID)	mm	0.3	0.5	0.8+	1.0	1.5	2.0
Tolerance (ID)	mm	+0.10/-0.05	+0.15/-0.10	+0.15/-0.10	+0.20/-0.15	+0.20/-0.15	+0.20/-0.15

	Unit of measure						
Inner diameter (ID)	mm	2.5	3.0	4.0	5.0	6.0	8.0
Tolerance (ID)	mm	+0.20/-0.20	+0.20/-0.20	+0.20/-0.20	+0.20/-0.20	+0.25/-0.25	+0.25/-0.25

	Unit of measure						
Inner diameter (ID)	mm	10.0	12.0	16.0	20.0	25.0	30.0
Tolerance (ID)	mm	+0.25/-0.25	+0.25/-0.25	+0.50/-0.50	+0.50/-0.50	+0.50/-0.50	+0.50/-0.50

	Unit of measure						
Wall thickness (wt) nominal	mm	0.20	0.40	0.50	0.70	1.0	1.5
Tolerance (wt)	mm	-0.05/+0.15	-0.05/+0.15	0.05/0.15	-0.05/+0.15	-0.05/+0.15	-0.20/+0.20

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 04/19



		Conditions	Values	Test method	Values
Wall thickness (wt) nominal	2.0				
Tolerance (wt)	-0.20/+0.20				
Dielectric strength		appr. 1 / 0.1 mm wall thickness	DIN EN 60684		
Specific volume resistance	room temperature	min. 10 ¹¹	DIN EN 60684		
Resistance	weather, ozone, UV				

Products	Unit of measure	Values	Test method
Elongation at break	%	500 (min. 200)	DIN EN 60684
Tear force	MPa	11 (min. 5.5)	DIN EN 60684

Category	Unit of measure	Values
Thermal class	°C	180
Application range	°C	-60 up to 200 (special version up to 250)

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 04/19



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Synflex manufacturer](#):

Other Similar products are found below :

[1030 1320 47](#) [1032 0150 47](#) [1030 1400 47](#) [1030 0800 47](#) [1030 1800 45](#) [1030 1120 47](#) [1032 0710 47](#) [1030 1320 45](#) [1032 1600 47](#) [1030 1060 47](#) [1032 1320 44](#) [1030 1500 47](#) [1030 1500 44](#) [1030 1700 45](#) [1070 0118 47](#) [1032 0400 47](#) [1030 0650 47](#) [1030 0750 47](#) [1030 1180 45](#) [1030 0600 47](#) [1030 1800 47](#) [1032 0500 47](#) [1032 1120 47](#) [1030 1700 47](#) [1030 0750 45](#) [1032 1120 45](#) [1030 1120 44](#) [1040 0500 47](#) [1030 1120 45](#) [1032 0150 44](#) [1040 0500 45](#) [1032 0400 45](#) [1032 1060 47](#) [1030 0900 47](#) [1040 0400 47](#) [1032 0900 47](#) [1032 1000 45](#) [1030 0710 47](#) [1032 0200 44](#) [1032 0600 44](#) [1070 0118 44](#) [1032 0300 45](#) [1032 0600 45](#) [1032 0600 47](#) [1032 1180 47](#) [1030 0800 45](#) [1040 0300 47](#) [1032 0200 45](#) [1030 1500 45](#) [1030 1600 45](#)