



T1M-07-F-SV-L

T1M-05-F-SH-L



ISS1-10-L



CC09R-01-GF

(1.00 mm) .0394"

ISS1, CC09R, CC09M, T1M SERIES

# DISCRETE WIRE COMPONENTS & TOOLING

## SPECIFICATIONS

For complete specifications see [www.samtec.com?ISS1](http://www.samtec.com?ISS1), [www.samtec.com?CC09R](http://www.samtec.com?CC09R) or [www.samtec.com?CC09M](http://www.samtec.com?CC09M)

## TOOLING

- Hand tool: CAT-HT-309-2830-12
- Clamp for mounting hand tool to work table: CAT-HT-MNT-01
- Mini Applicator: CAT-MA-309-2830-XX-01

TYPE	NO. OF POSITIONS	LATCH	TYPE	01	PLATING
ISS1 = Single Row Body	-02, -03, -05, -07, -10, -15, -20	(Leave blank for no latch) -L = Positive Latch	CC09R = Contact, Full Reel (30,000 Parts per Reel)	CC09M = Contact, Mini Reel (5,000 Parts per Reel)	-GF = 3 μ" (0.07 μm) Gold contact and tail -T = Tin
<p>No. of positions x (1.00) .03937 + (1.20) .047</p> <p>(1.00) .03937</p> <p>(5.00) .197</p> <p>(4.20) .165</p> <p>LATCH</p>	<p>No. of positions x (1.00) .03937 + (3.00) .118</p> <p>(1.00) .03937</p> <p>(2.10) .083</p> <p>NO LATCH</p> <p>Insulator Material: Natural Nylon</p>		<p>(9.01) .355</p> <p>(2.76) .109</p> <p>(3.60) .141</p> <p>(3.81) .150</p> <p>(3.60) .141</p>		<p>Contact Material: Phosphor Bronze</p>

Mates with: S1SS(T)

## SPECIFICATIONS

For complete specifications see [www.samtec.com?T1M](http://www.samtec.com?T1M)

- Insulator Material:** Natural LCP  
**Terminal Material:** Phosphor Bronze  
**Weld Tab:** Phosphor Bronze  
**Plating:** Au or Sn over 50 μ" (1.27 μm) Ni  
**Operating Temp Range:** -55 °C to +85 °C  
**Current Rating:** 3.3 A per pin (1 pin powered)  
**Voltage Rating:** 250 VAC/353 VDC  
**RoHS Compliant:** Yes

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



**Note:** Some lengths, styles and options are non-standard, non-returnable.

T1M	NO. OF POSITIONS	PLATING OPTION	ROW OPTION	LATCH	OPTION
	-02, -03, -05, -07, -10, -15, -20	-F = 3 μ" (0.07 μm) Gold on contact, Matte Tin on tail -T = Tin	-SH = Single Row Horizontal -SV = Single Row Vertical	(Required in callout) -L = Positive Latch	-K = (4.00 mm) .157" DIA Polyimide Film Pick & Place Pad (-SH only) -P = Pick & Place Pad (-SV only)
<p>(4.25) .167</p> <p>(5.20) .205</p> <p>(0.20) .008</p> <p>-SH</p>	<p>No. of positions x (1.00) .0394 + (2.40) .094</p> <p>(4.60) .181</p> <p>(1.00) .0394</p> <p>(1.50) .059</p> <p>(5.10) .201</p> <p>-SV</p>		<p>No. of positions x (1.00) .0394 + (2.40) .094</p> <p>(4.25) .167</p> <p>(1.00) .0394</p> <p>(5.50) .217</p> <p>(4.45) .179</p> <p>(0.20) .008</p> <p>(0.80) .031</p> <p>(3.90) .154</p> <p>(1.50) .059</p>		<p><b>OTHER SOLUTIONS</b></p> <ul style="list-style-type: none"> <li>• Without latch Contact Samtec.</li> </ul>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Samtec](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65781-047](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#)