

# MODEL TL-5101


International size reference: 1/2AA, ER14252

## TECHNICAL DATA

(Typical values @+25°C for batteries stored for one year or less)


■ Nominal capacity @ 0.5 mA, to 2V	0.95 Ah
■ Rated voltage	3.6 V
■ Weight	9.2g (0.324 oz)
■ Volume	4.3 cc
■ Operating temperature range	-55°C to +85°C
■ U.L. Component Recognition, MH 12193	

**TADIRAN**  
**LITHIUM**  
**BATTERIES**



### AVAILABLE TERMINATIONS

SUFFIX- /S STANDARD	15-5101-21000
SUFFIX- /T SOLDER TABS	15-5101-31000
SUFFIX- /P AXIAL PINS	15-5101-41000
SUFFIX- /PT2 RADIAL PINS	15-5101-36000
SUFFIX- /TP POLARIZED TABS	15-5101-52000
SUFFIX- /PT POLARIZED TABS	15-5101-53000



**MEMORY BACKUP**

Note: Any presentations in this data sheet concerning performance are for information purpose only and are not construed as warranties either expressed or implied, of future performance. Rev. B 03/03

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Electronic Battery](#) category:*

*Click to view products by [Tadiran](#) manufacturer:*

Other Similar products are found below :

[R88A-BAT02W](#) [TL-5104/SBP](#) [E300781900](#) [E300782100](#) [BR-435/BN](#) [B73180A0101M199](#) [13299-0001](#) [R88A-BAT01G](#) [R88A-BAT01W](#)  
[M4T32-BR12SH6](#) [LR03AD/4P](#) [13331-0001](#) [3G2A9BAT08](#) [LR03AD/B](#) [LR20AD/B](#)