

# XI Type 10.8 x 4.5 mm Crystal

## FEATURE

- Typical 10.8 x 4.5 x 3.4 mm standard footprint.
- Low profile for close PCB stacking.

## TYPICAL APPLICATION

- Automotive
- Bluetooth, Wireless
- Computers, Modems, Communications
- Set-top Box, DECT/WDCT



**RoHS Compliant**

## DIMENSION (mm)

## SOLDER PAD LAYOUT (mm)



## ELECTRICAL SPECIFICATION

| Parameter              | Min.            | Typical | Max. | Unit       |
|------------------------|-----------------|---------|------|------------|
| Storage Temp. Range    | -55             | -       | 125  | °C         |
| Level of Drive         | -               | 10      | 800  | μw         |
| Shunt Capacitance (Co) | -               | -       | 7.0  | pF         |
| Insulation Resistance  | 500 MΩ @ DC100V | -       | -    |            |
| Aging                  |                 | ±5      |      | ppm / year |

Standard frequencies are frequencies which the crystal has been designed and does not imply a stock position.

## EQUIVALENT SERIES RESISTANCE (E.S.R)

| Frequency Range      | MODE | E.S.R  |
|----------------------|------|--------|
| Fo ≤ 3.58 MHz        | A1   | <140 Ω |
| 4 MHz < Fo < 5 MHz   | A1   | <120 Ω |
| 5 MHz ≤ Fo < 7 MHz   | A1   | <80 Ω  |
| 7 MHz ≤ Fo < 9 MHz   | A1   | <45 Ω  |
| 9 MHz ≤ Fo < 13 MHz  | A1   | <40 Ω  |
| 13 MHz ≤ Fo < 16 MHz | A1   | <35 Ω  |
| 16 MHz ≤ Fo < 20 MHz | A1   | <30 Ω  |
| 20 MHz ≤ Fo < 30 MHz | A1   | <25 Ω  |
| 30 MHz ≤ Fo < 36 MHz | A1   | <25 Ω  |
| 30 MHz ≤ Fo < 36 MHz | A3   | <80 Ω  |
| 36 MHz ≤ Fo ≤ 80 MHz | A3   | <80 Ω  |

## FREQ. STABILITY vs. LOAD CAPACITANCE

| Load Capacitance | ppm | ±5 | ±10 | ±15 | ±20 | ±30 |
|------------------|-----|----|-----|-----|-----|-----|
| 8pF              |     | X  | X   | △   | ○   | ○   |
| 10pF             |     | X  | X   | △   | ○   | ○   |
| 12pF             |     | X  | △   | ○   | ○   | ○   |
| 16pF             |     | X  | △   | ○   | ○   | ○   |
| Series           |     | △  | ○   | ○   | ○   | ○   |

\* ○: Available △:Conditional X: Not available

## FREQ. STABILITY vs. TEMP. RANGE

| Temp. (°C) | ppm | ±5 | ±10 | ±15 | ±20 |
|------------|-----|----|-----|-----|-----|
| -10 ~ +60  |     | X  | ○   | ○   | ○   |
| -20 ~ +70  |     | X  | △   | ○   | ○   |
| -40 ~ +85  |     | X  | X   | X   | ○   |

\* ○: Available △:Conditional X: Not available

**Note: not all combination of options are available. Other specifications may be available upon request.**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Crystals](#) category:*

*Click to view products by [TAITIEN](#) manufacturer:*

Other Similar products are found below :

[CX3225GB25000M0PPSZ1](#) [718-13.2-1](#) [7A-40.000MAAE-T](#) [FL2000085](#) [99-BU](#) [9B-15.360MBBK-B](#) [9C-7.680MBBK-T](#) [H10S-12.000-18-EXT-TR](#) [ABC2-6.000MHZ-D4Z-T](#) [ABLS-20.000MHZ-D2-T](#) [ABM3B-27.000MHZ-D4Y-T](#) [ABS071-32.768KHZ-6-T](#) [R38-32.768-12.5-5PPM-NPB](#) [BTD1062E05A-513](#) [21U15A-21.4MHZ](#) [RTX-781DF1-S-20.950](#) [LFXTAL066198Cutt](#) [9C-14.31818MBBK-T](#) [A-11.000MHZ-27](#) [ABL-27.000MHZ-B4Y-T](#) [ABM11-132-24.000MHZ-T3](#) [ABM3B1-25.000MHZ-D2Y-T](#) [SPT2A-.032768B](#) [SPT2A.032768G](#) [SSPT7F-9PF20-R](#) [LFXTAL065253Cutt](#) [LFXTAL066431Cutt](#) [XT9S20ANA14M7456](#) [XT9SNLANA16M](#) [7A-24.576MBBK-T](#) [7B-30.000MBBK-T](#) [MMCC2R32.7680KHZ](#) [7A-14.31818MBBK-T](#) [6504-202-1501](#) [6526-202-1501](#) [ABLS-12.000MHZ-B2Y-T](#) [7A-10.000MBBK-T](#) [SG636PCE-20.000MC](#) [3404](#) [E1SAA18-25.000M](#) [TR](#) [CM315D32768EZFT](#) [C1E-24.000-7-2020-R](#) [C1E-19.200-12-1530-X-R](#) [C1E-16.000-12-1530-X-R](#) [ABM11-16.000MHZ-9-B1U-T](#) [FL5000014](#) [EUCA18-3.1872M](#) [FX0800015](#) [425F35E027M0000](#) [FP0800018](#)