

600W, 5V - 170V Surface Mount Transient Voltage Suppressor

FEATURES

- Ideal for automated placement
- Glass passivated junction
- Excellent clamping capability
- Fast response time: Typically less than 1.0ps
- Typical I_R less than 1 μ A above 10V
- Meets ISO 7637-2 (Pulse 1/2a/2b/3a/3b)
- Moisture sensitivity level: level 1, per J-STD-020
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- Protect sensitive circuit from damage by high voltage transients
- Lighting, ESD transient voltage protection of IC, system
- Inductive switching load protection of IC, system
- Electrical Fast Transient Immunity protection of IC, system

MECHANICAL DATA

- Case: DO-214AA (SMB)
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 2 whisker test
- Polarity: As marked
- Weight: 0.090g (approximately)

| KEY PARAMETERS | | |
|------------------------------|----------------|------|
| PARAMETER | VALUE | UNIT |
| V_{WM} | 5 - 170 | V |
| V_{BR} (uni - directional) | 6.4 - 231 | V |
| V_{BR} (bi - directional) | 6.4 - 231 | V |
| P_{PK} | 600 | W |
| T_{JMAX} | 150 | |
| Package | DO-214AA (SMB) | |
| Configuration | Single die | |



DO-214AA (SMB)

| ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted) | | | |
|---|-----------|--------------|------------------|
| PARAMETER | SYMBOL | VALUE | UNIT |
| Non-repetitive peak impulse power dissipation with 10/1000 μ s waveform ⁽¹⁾ | P_{PK} | 600 | W |
| Steady state power dissipation at $T_A = 25^\circ\text{C}$ | P_D | 3 | W |
| Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load for Uni-directional only | I_{FSM} | 100 | A |
| Forward Voltage @ $I_F = 50\text{A}$ for Uni-directional only ⁽²⁾ | V_F | 3.5 / 5.0 | V |
| Junction temperature | T_J | - 55 to +150 | $^\circ\text{C}$ |
| Storage temperature | T_{STG} | - 55 to +150 | $^\circ\text{C}$ |

Notes:

1. Non-repetitive current pulse per Fig.3 and derated above $T_A = 25^\circ\text{C}$ per Fig.2
2. $V_F = 3.5\text{V}$ on SMBJ5.0 - SMBJ90 devices and $V_F = 5.0\text{V}$ on SMBJ100 - SMBJ170 devices

Devices for Bipolar Applications

1. For bidirectional use C or CA suffix for types SMBJ5.0 - types SMBJ170
2. Electrical characteristics apply in both directions

| THERMAL PERFORMANCE | | | |
|--|-----------------|------------|-------------|
| PARAMETER | SYMBOL | TYP | UNIT |
| Junction-to-case thermal resistance | $R_{\theta JC}$ | 10 | °C/W |
| Junction-to-ambient thermal resistance | $R_{\theta JA}$ | 55 | °C/W |

| ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted) | | | | | | | | |
|---|--------------|--|------|-------------------------------|--|---|---|---|
| Part number | Marking code | Breakdown voltage $V_{BR}@I_T$ (V) (Note 1) | | Test current I_T (mA) | Working stand-off voltage V_{WM} (V) | Maximum blocking leakage current $I_D@V_{WM}$ (μA) | Maximum peak impulse current I_{PP} (A) (Note 2) | Maximum clamping voltage $V_C@I_{PP}$ (V) |
| | | Min | Max | | | | | |
| SMBJ5.0 | KD | 6.40 | 7.30 | 10 | 5.0 | 800 | 65.0 | 9.6 |
| SMBJ5.0A | KE | 6.40 | 7.00 | 10 | 5.0 | 800 | 68.0 | 9.2 |
| SMBJ5V0A | | | | | | | | |
| SMBJ6.0 | KF | 6.67 | 8.15 | 10 | 6.0 | 800 | 55.0 | 11.4 |
| SMBJ6.0A | KG | 6.67 | 7.37 | 10 | 6.0 | 800 | 61.0 | 10.3 |
| SMBJ6V0A | | | | | | | | |
| SMBJ6.5 | KH | 7.22 | 8.82 | 10 | 6.5 | 500 | 51.0 | 12.3 |
| SMBJ6.5A | KK | 7.22 | 7.98 | 10 | 6.5 | 500 | 56.0 | 11.2 |
| SMBJ6V5A | | | | | | | | |
| SMBJ7.0 | KL | 7.78 | 9.51 | 10 | 7.0 | 200 | 47.0 | 13.3 |
| SMBJ7.0A | KM | 7.78 | 8.60 | 10 | 7.0 | 200 | 52.0 | 12.0 |
| SMBJ7V0A | | | | | | | | |
| SMBJ7.5 | KN | 8.33 | 10.3 | 1 | 7.5 | 100 | 44.0 | 14.3 |
| SMBJ7.5A | KP | 8.33 | 9.21 | 1 | 7.5 | 100 | 48.0 | 12.9 |
| SMBJ7V5A | | | | | | | | |
| SMBJ8.0 | KQ | 8.89 | 10.9 | 1 | 8.0 | 50 | 42.0 | 15.0 |
| SMBJ8.0A | KR | 8.89 | 9.83 | 1 | 8.0 | 50 | 46.0 | 13.6 |
| SMBJ8V0A | | | | | | | | |
| SMBJ8.5 | KS | 9.44 | 11.5 | 1 | 8.5 | 10 | 39.0 | 15.9 |
| SMBJ8.5A | KT | 9.44 | 10.4 | 1 | 8.5 | 10 | 43.0 | 14.4 |
| SMBJ8V5A | | | | | | | | |
| SMBJ9.0 | KU | 10.0 | 12.2 | 1 | 9.0 | 5 | 37.0 | 16.9 |
| SMBJ9.0A | KV | 10.0 | 11.1 | 1 | 9.0 | 5 | 40.0 | 15.4 |
| SMBJ9V0A | | | | | | | | |
| SMBJ10 | KW | 11.1 | 13.6 | 1 | 10 | 5 | 33.0 | 18.8 |
| SMBJ10A | KX | 11.1 | 12.3 | 1 | 10 | 5 | 37.0 | 17.0 |
| SMBJ11 | KY | 12.2 | 14.9 | 1 | 11 | 1 | 31.0 | 20.1 |
| SMBJ11A | KZ | 12.2 | 13.5 | 1 | 11 | 1 | 34.0 | 18.2 |
| SMBJ12 | LD | 13.3 | 16.3 | 1 | 12 | 1 | 28.0 | 22.0 |
| SMBJ12A | LE | 13.3 | 14.7 | 1 | 12 | 1 | 31.0 | 19.9 |
| SMBJ13 | LF | 14.4 | 17.6 | 1 | 13 | 1 | 26.0 | 23.8 |
| SMBJ13A | LG | 14.4 | 15.9 | 1 | 13 | 1 | 29.0 | 21.5 |
| SMBJ14 | LH | 15.6 | 19.1 | 1 | 14 | 1 | 24.4 | 25.8 |
| SMBJ14A | LK | 15.6 | 17.2 | 1 | 14 | 1 | 27.0 | 23.2 |
| SMBJ15 | LL | 16.7 | 20.4 | 1 | 15 | 1 | 23.1 | 26.9 |
| SMBJ15A | LM | 16.7 | 18.5 | 1 | 15 | 1 | 25.1 | 24.4 |
| SMBJ16 | LN | 17.8 | 21.8 | 1 | 16 | 1 | 21.8 | 28.8 |
| SMBJ16A | LP | 17.8 | 19.7 | 1 | 16 | 1 | 24.2 | 26.0 |
| SMBJ17 | LQ | 18.9 | 23.1 | 1 | 17 | 1 | 20.0 | 30.5 |
| SMBJ17A | LR | 18.9 | 20.9 | 1 | 17 | 1 | 22.8 | 27.6 |
| SMBJ18 | LS | 20.0 | 24.4 | 1 | 18 | 1 | 19.5 | 32.2 |
| SMBJ18A | LT | 20.0 | 22.1 | 1 | 18 | 1 | 21.5 | 29.2 |
| SMBJ20 | LU | 22.2 | 27.1 | 1 | 20 | 1 | 17.6 | 35.8 |
| SMBJ20A | LV | 22.2 | 24.5 | 1 | 20 | 1 | 19.4 | 32.4 |
| SMBJ22 | LW | 24.4 | 29.8 | 1 | 22 | 1 | 15.0 | 39.4 |
| SMBJ22A | LX | 24.4 | 26.9 | 1 | 22 | 1 | 17.7 | 35.5 |
| SMBJ24 | LY | 26.7 | 32.6 | 1 | 24 | 1 | 14.6 | 43.0 |
| SMBJ24A | LZ | 26.7 | 29.5 | 1 | 24 | 1 | 16.0 | 38.9 |

| ELECTRICAL SPECIFICATIONS (T _A = 25°C unless otherwise noted) | | | | | | | | |
|--|--------------|---|------|--|---|---|--|--|
| Part number | Marking code | Breakdown voltage V _{BR} @I _T (V) (Note 1) | | Test current I _T (mA) | Working stand-off voltage V _{WM} (V) | Maximum blocking leakage current I _D @V _{WM} (μA) | Maximum peak impulse current I _{PP} (A) (Note 2) | Maximum clamping voltage V _C @I _{PP} (V) |
| | | Min | Max | | | | | |
| SMBJ26 | MD | 28.9 | 35.3 | 1 | 26 | 1 | 13.5 | 46.6 |
| SMBJ26A | ME | 28.9 | 31.9 | 1 | 26 | 1 | 14.9 | 42.1 |
| SMBJ28 | MF | 31.1 | 38.0 | 1 | 28 | 1 | 12.6 | 50.0 |
| SMBJ28A | MG | 31.1 | 34.4 | 1 | 28 | 1 | 13.8 | 45.4 |
| SMBJ30 | MH | 33.3 | 40.7 | 1 | 30 | 1 | 11.7 | 53.5 |
| SMBJ30A | MK | 33.3 | 36.8 | 1 | 30 | 1 | 13.0 | 48.4 |
| SMBJ33 | ML | 36.7 | 44.9 | 1 | 33 | 1 | 10.6 | 59.0 |
| SMBJ33A | MM | 36.7 | 40.6 | 1 | 33 | 1 | 11.8 | 53.3 |
| SMBJ36 | MN | 40.0 | 48.9 | 1 | 36 | 1 | 9.8 | 64.3 |
| SMBJ36A | MP | 40.0 | 44.2 | 1 | 36 | 1 | 10.8 | 58.1 |
| SMBJ40 | MQ | 44.4 | 54.3 | 1 | 40 | 1 | 8.8 | 71.4 |
| SMBJ40A | MR | 44.4 | 49.1 | 1 | 40 | 1 | 9.7 | 64.5 |
| SMBJ43 | MS | 47.8 | 58.4 | 1 | 43 | 1 | 8.2 | 76.7 |
| SMBJ43A | MT | 47.8 | 52.8 | 1 | 43 | 1 | 9.0 | 69.4 |
| SMBJ45 | MU | 50.0 | 61.1 | 1 | 45 | 1 | 7.8 | 80.3 |
| SMBJ45A | MV | 50.0 | 55.3 | 1 | 45 | 1 | 8.6 | 72.7 |
| SMBJ48 | MW | 53.3 | 65.1 | 1 | 48 | 1 | 7.3 | 85.5 |
| SMBJ48A | MX | 53.3 | 58.9 | 1 | 48 | 1 | 8.1 | 77.4 |
| SMBJ51 | MY | 56.7 | 69.3 | 1 | 51 | 1 | 6.9 | 91.1 |
| SMBJ51A | MZ | 56.7 | 62.7 | 1 | 51 | 1 | 7.6 | 82.4 |
| SMBJ54 | ND | 60.0 | 73.3 | 1 | 54 | 1 | 6.5 | 96.3 |
| SMBJ54A | NE | 60.0 | 66.3 | 1 | 54 | 1 | 7.2 | 87.1 |
| SMBJ58 | NF | 64.4 | 78.7 | 1 | 58 | 1 | 6.1 | 103 |
| SMBJ58A | NG | 64.4 | 71.2 | 1 | 58 | 1 | 6.7 | 93.6 |
| SMBJ60 | NH | 66.7 | 81.5 | 1 | 60 | 1 | 5.8 | 107 |
| SMBJ60A | NK | 66.7 | 73.7 | 1 | 60 | 1 | 6.5 | 96.8 |
| SMBJ64 | NL | 71.1 | 86.9 | 1 | 64 | 1 | 5.5 | 114 |
| SMBJ64A | NM | 71.1 | 78.6 | 1 | 64 | 1 | 6.1 | 103 |
| SMBJ70 | NN | 77.8 | 95.1 | 1 | 70 | 1 | 5.0 | 125 |
| SMBJ70A | NP | 77.8 | 86 | 1 | 70 | 1 | 5.5 | 113 |
| SMBJ75 | NQ | 83.3 | 102 | 1 | 75 | 1 | 4.7 | 134 |
| SMBJ75A | NR | 83.3 | 92.1 | 1 | 75 | 1 | 5.2 | 121 |
| SMBJ78 | NS | 86.7 | 106 | 1 | 78 | 1 | 4.5 | 139 |
| SMBJ78A | NT | 86.7 | 95.8 | 1 | 78 | 1 | 5.0 | 126 |
| SMBJ85 | NU | 94.4 | 115 | 1 | 85 | 1 | 4.1 | 151 |
| SMBJ85A | NV | 94.4 | 104 | 1 | 85 | 1 | 4.6 | 137 |
| SMBJ90 | NW | 100 | 122 | 1 | 90 | 1 | 3.9 | 160 |
| SMBJ90A | NX | 100 | 111 | 1 | 90 | 1 | 4.3 | 146 |
| SMBJ100 | NY | 111 | 136 | 1 | 100 | 1 | 3.5 | 179 |
| SMBJ100A | NZ | 111 | 123 | 1 | 100 | 1 | 3.8 | 162 |
| SMBJ110 | PD | 122 | 149 | 1 | 110 | 1 | 3.2 | 196 |
| SMBJ110A | PE | 122 | 135 | 1 | 110 | 1 | 3.5 | 177 |
| SMBJ120 | PF | 133 | 163 | 1 | 120 | 1 | 2.9 | 214 |
| SMBJ120A | PG | 133 | 147 | 1 | 120 | 1 | 3.2 | 193 |
| SMBJ130 | PH | 144 | 176 | 1 | 130 | 1 | 2.7 | 231 |
| SMBJ130A | PK | 144 | 159 | 1 | 130 | 1 | 3.0 | 209 |
| SMBJ150 | PL | 167 | 204 | 1 | 150 | 1 | 2.3 | 266 |
| SMBJ150A | PM | 167 | 185 | 1 | 150 | 1 | 2.5 | 243 |
| SMBJ160 | PN | 178 | 218 | 1 | 160 | 1 | 2.2 | 287 |
| SMBJ160A | PP | 178 | 197 | 1 | 160 | 1 | 2.4 | 259 |
| SMBJ170 | PQ | 189 | 231 | 1 | 170 | 1 | 2.0 | 304 |

| ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted) | | | | | | | | |
|---|--------------|--|-----|-------------------------------|--|---|---|---|
| Part number | Marking code | Breakdown voltage $V_{BR}@I_T$ (V) (Note 1) | | Test current I_T (mA) | Working stand-off voltage V_{WM} (V) | Maximum blocking leakage current $I_D@V_{WM}$ (μA) | Maximum peak impulse current I_{PP} (A) (Note 2) | Maximum clamping voltage $V_C@I_{PP}$ (V) |
| | | Min | Max | | | | | |
| SMBJ170A | PR | 189 | 209 | 1 | 170 | 1 | 2.2 | 275 |

Notes:

1. V_{BR} measure after I_T applied for 30ms, $I_T =$ square wave pulse or equivalent.
2. Surge current waveform per Fig.3 and derate per Fig.2.
3. All terms and symbols are consistent with ANSI/IEEE C62.35.
4. For bidirectional use C or CA suffix for types SMBJ5.0 - SMBJ170
5. For bipolar types having V_{WM} of 10V (SMBJ10C) and under, the I_D limit is doubled.

| ORDERING INFORMATION | | |
|------------------------------|----------------|---------------------|
| ORDERING CODE ⁽¹⁾ | PACKAGE | PACKING |
| SMBJx | DO-214AA (SMB) | 3,000 / Tape & Reel |

Notes:

1. "x" defines voltage from 5V(SMBJ5.0) to 170V(SMBJ170A)

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Peak Pulse Power Rating Curve




Fig.2 Pulse Derating Curve





Fig.3 Clamping Power Pulse Waveform




Fig.4 Maximum Non-Repetitive Forward Surge Current



CHARACTERISTICS CURVES


($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.5 Typical Junction Capacitance




PACKAGE OUTLINE DIMENSIONS

DO-214AA (SMB)




| DIM. | Unit (mm) | | Unit (inch) | |
|------|-----------|------|-------------|-------|
| | Min. | Max. | Min. | Max. |
| A | 1.95 | 2.65 | 0.077 | 0.104 |
| A1 | 0.05 | 0.20 | 0.002 | 0.008 |
| b | 1.95 | 2.20 | 0.077 | 0.087 |
| c | 0.15 | 0.31 | 0.006 | 0.012 |
| D | 3.30 | 3.95 | 0.130 | 0.156 |
| E | 5.10 | 5.60 | 0.201 | 0.220 |
| E1 | 4.05 | 4.60 | 0.159 | 0.181 |
| L | 0.75 | 1.60 | 0.030 | 0.063 |

SUGGESTED PAD LAYOUT



| Symbol | Unit (mm) | Unit (inch) |
|--------|-----------|-------------|
| A | 2.30 | 0.091 |
| B | 2.50 | 0.098 |
| C | 4.30 | 0.169 |
| D | 1.80 | 0.071 |
| E | 6.80 | 0.268 |

MARKING DIAGRAM



- P/N = Marking Code
- G = Green Compound
- YW = Date Code
- F = Factory Code

Cathode band for uni-directional products only

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Taiwan Semiconductor manufacturer](#):

Other Similar products are found below :

[1.5KE100A R0G](#) [1.5KE100CA A0G](#) [1.5KE100CA-R0](#) [1.5KE11A R0G](#) [1.5KE15A-R0](#) [1.5KE160A R0G](#) [1.5KE16A-R0](#) [1.5KE16A R0G](#)
[1.5KE180A R0G](#) [1.5KE20CA-R0](#) [1.5KE220A A0G](#) [1.5KE220A R0G](#) [1.5KE250CA A0G](#) [1.5KE27A-R0](#) [1.5KE300A R0G](#)
[1.5KE30CAHA0G](#) [1.5KE30CA R0G](#) [1.5KE33A-R0](#) [1.5KE33CA A0G](#) [1.5KE33CA-R0](#) [1.5KE33CA R0G](#) [1.5KE36CA R0](#) [1.5KE36CA R0G](#)
[1.5KE39A-R0](#) [1.5KE400A-R0](#) [1.5KE400A R0G](#) [1.5KE400CA](#) [1.5KE400CA R0G](#) [1.5KE440A-R0](#) [1.5KE440A R0G](#) [1.5KE47CA R0G](#)
[1.5KE51CA R0G](#) [1.5KE56A-R0](#) [1.5KE6.8CA-R0](#) [1.5KE91CA-R0](#) [1.5SMC12CA M6G](#) [1.5SMC30CA R7G](#) [1.5SMC36CAHV6G](#)
[1.5SMC36CA R7G](#) [1.5SMC36CA-V6G](#) [1.5SMC39CA R7G](#) [1.5SMC39CA V7G](#) [1.5SMC47CA M6G](#) [1.5SMC62A R7G](#) [1.5SMC82A V7G](#)
[1M130Z](#) [1M150Z R0](#) [1M200Z](#) [1M200Z R0](#) [1M200Z R1G](#)