

NPN Silicon Planar High Voltage Transistor


FEATURES

- High BV_{CEO} , BV_{CBO}
- High current gain
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-Free according to IEC 61249-2-21

APPLICATION

- Lighting
- Switch mode power supply

KEY PERFORMANCE PARAMETERS			
PARAMETER		VALUE	UNIT
BV_{CEO}		400	V
BV_{CBO}		600	V
I_C		1	A
$V_{CE(SAT)}$	$I_C=0.5A, I_B=0.1A$	0.5	V



Notes: MSL 3 (Moisture Sensitivity Level) per J-STD-020

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)				
PARAMETER		SYMBOL	LIMIT	UNIT
Collector-Base Voltage		V_{CBO}	600	V
Collector-Emitter Voltage		V_{CEO}	400	V
Emitter-Base Voltage		V_{EBO}	9	V
Collector Current	DC	I_C	1	A
	Pulse		2	A
Power Total Dissipation @ $T_A=25^\circ\text{C}$		P_{DTOT}	1.2	W
Maximum Operating Junction Temperature		T_J	+150	$^\circ\text{C}$
Storage Temperature Range		T_{STG}	-55 to +150	$^\circ\text{C}$

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)						
PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNIT
Static (Note 1)						
Collector-Base voltage	$I_C = 100\mu\text{A}$	BV_{CBO}	600	--	--	V
Collector-Emitter breakdown voltage	$I_C = 1\text{mA}$	BV_{CEO}	400	--	--	V
Emitter-Base breakdown voltage	$I_E = 100\mu\text{A}$	BV_{EBO}	9	--	--	V
Emitter cut-off current	$V_{EB} = 8\text{V}$	I_{EBO}	--	--	100	μA
Collector cut-off current	$V_{CB} = 600\text{V}$	I_{CBO}	--	--	100	μA
Collector-Emitter Cutoff Current	$V_{CE} = 400\text{V}$	I_{CEO}	--	--	1	mA
Collector-Emitter saturation voltage	$I_C = 500\text{mA}, I_B = 100\text{mA}$	$V_{CE(SAT) 1}$	---	--	0.5	V
Collector-Emitter saturation voltage	$I_C = 1\text{A}, I_B = 250\text{mA}$	$V_{CE(SAT) 2}$	---	--	1	V
Base-Emitter saturation voltage	$I_C = 500\text{mA}, I_B = 100\text{mA}$	$V_{BE(SAT) 1}$	--	--	1	V
Base-Emitter saturation voltage	$I_C = 1\text{A}, I_B = 250\text{mA}$	$V_{BE(SAT) 2}$	--	--	1.2	V
DC Current Gain	$V_{CE} = 10\text{V}, I_C = 250\text{mA}$	h_{FE1}	80	--	--	
Resistive Load Switching Time (Note 2)						
Turn-on Time	$V_{CC} = 125\text{V}, I_C = 1\text{A},$ $I_{B1} = I_{B2} = 200\text{mA}$	T_{on}	--	1	--	μs
Storage Time		T_{STG}	--	4	--	μs
Fall Time		T_f	--	0.7	--	μs

Notes:

1. Pulse test: $\leq 380\mu\text{s}$, duty cycle $\leq 2\%$
2. For DESIGN AID ONLY, not subject to production testing.

ORDERING INFORMATION

PART NO.	PACKAGE	PACKING
TSC873CW RPG	SOT-223	2,500pcs / 13"Reel

Electrical Characteristics Curve
($T_a = 25^\circ\text{C}$, unless otherwise noted)

Figure 1. Static Characteristics




Figure 2. DC Current Gain




Figure 3. VCE(SAT) v.s. IC




Figure 4. VBE(sat) vs IC




Figure 5. VBE(on) vs IC






Figure 6. Safety Operation Area




PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)


SOT-223



SUGGESTED PAD LAYOUT (Unit: Millimeters)



Marking Diagram



- Y** = Year Code
- M** = Month Code for Halogen Free Product
 - O** =Jan **P** =Feb **Q** =Mar **R** =Apr
 - S** =May **T** =Jun **U** =Jul **V** =Aug
 - W** =Sep **X** =Oct **Y** =Nov **Z** =Dec
- L** = Lot Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT category](#):

Click to view products by [Taiwan Semiconductor manufacturer](#):

Other Similar products are found below :

[619691C](#) [MCH4017-TL-H](#) [BC546/116](#) [BC557/116](#) [BSW67A](#) [NTE158](#) [NTE187A](#) [NTE195A](#) [NTE2302](#) [NTE2330](#) [NTE63](#) [C4460](#)
[2SA1419T-TD-H](#) [2SA1721-O\(TE85L,F\)](#) [2SA2126-E](#) [2SB1204S-TL-E](#) [2SC5488A-TL-H](#) [2SD2150T100R](#) [SP000011176](#) [FMMTA92QTA](#)
[2N2369ADCSM](#) [2N5769](#) [2SC2412KT146S](#) [2SC5490A-TL-H](#) [2SD1816S-TL-E](#) [2SD1816T-TL-E](#) [CMXT2207 TR](#) [CPH6501-TL-E](#)
[MCH4021-TL-E](#) [US6T6TR](#) [NJL0281DG](#) [732314D](#) [CMXT3906 TR](#) [CPH3121-TL-E](#) [CPH6021-TL-H](#) [873787E](#) [IMZ2AT108](#) [UMX21NTR](#)
[EMT2T2R](#) [MCH6102-TL-E](#) [FP204-TL-E](#) [NJL0302DG](#) [2N3583](#) [2SA1434-TB-E](#) [2SC3143-4-TB-E](#) [2SD1621S-TD-E](#) [NTE103](#) [30A02MH-TL-E](#) [NSV40301MZ4T1G](#) [NTE101](#)