


**SOP-8**
**Pin Definition:**

1. Source 8. Drain
2. Source 7. Drain
3. Source 6. Drain
4. Gate 5. Drain

**Note:**

MSL 1 (Moisture Sensitivity Level)  
per J-STD-020

**Key Parameter Performance**

Parameter	Value	Unit
$V_{DS}$	20	V
$R_{DS(on)}$ (max)	$V_{GS} = 4.5V$	20
	$V_{GS} = 2.5V$	25
	$V_{GS} = 1.8V$	31
$Q_g$	12.3	nC

**Features**

- Advanced High Cell Density Trench Technology.
- Low Gate Charge.


**Application**

- Networking DC-DC Power System.
- Load Switch.

**Ordering Information**

Part No.	Package	Packing
TSM4806CS RLG	SOP-8	2.5kpcs / 13" Reel

•Note: Halogen-free according to IEC 61249-2-21 definition

**Block Diagram**


N-Channel MOSFET

**Absolute Maximum Ratings ( $T_A=25^\circ\text{C}$ , unless otherwise noted)**

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	$V_{DS}$	20	V
Gate-Source Voltage	$V_{GS}$	$\pm 8$	V
Continuous Drain Current <sup>a</sup>	$I_D$	28	A
Pulsed Drain Current <sup>b</sup>	$I_{DM}$	70	A
Continuous Source Current (Diode Conduction) <sup>a,c</sup>	$I_S$	28	A
Total Power Dissipation $ T_A=25^\circ\text{C}$	$P_D$	2	W
Storage Temperature Range	$T_{STG}$	-55 to +150	$^\circ\text{C}$
Operating Junction Temperature Range	$T_J$	-55 to +150	$^\circ\text{C}$

**Thermal Performance**

Parameter	Symbol	Limit	Unit
Thermal Resistance Junction to Lead	$R\theta_{JL}$	40	$^\circ\text{C}/\text{W}$
Thermal Resistance Junction to Ambient	$R\theta_{JA}$	62.5	$^\circ\text{C}/\text{W}$

**Notes:**

- a. The data tested by surface mounted on a 1 inch<sup>2</sup> FR-4 board with 2oz copper.
- b. The data tested by pulsed, pulse width  $\leq 300\mu\text{s}$ , duty cycle  $\leq 2\%$  surface mounted on FR4 Board,  $t \leq 5\text{s}$ .
- c. The data is theoretically the same as  $I_D$  and  $I_{DM}$ , in real applications, should be limited by total power dissipation.

**Electrical Specifications**


Parameter	Conditions	Symbol	Min	Typ	Max	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu A$	$BV_{DSS}$	20	--	--	V
Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu A$	$V_{GS(TH)}$	0.3	0.6	1.0	V
Gate-Source Leakage Current	$V_{GS} = \pm 8V, V_{DS} = 0V$	$I_{GSS}$	--	--	$\pm 100$	nA
Drain-Source Leakage Current	$V_{DS} = 16V, V_{GS} = 0V$	$I_{DSS}$	--	--	1	$\mu A$
Drain-Source On-State Resistance	$V_{GS} = 4.5V, I_D = 20A$	$R_{DS(ON)}$	--	16	20	$m\Omega$
	$V_{GS} = 2.5V, I_D = 15A$		--	20	25	
	$V_{GS} = 1.8V, I_D = 10A$		--	25	31	
Forward Transconductance	$V_{DS} = 5V, I_D = 15A$	$g_{fs}$	--	27	--	S
Diode Forward Voltage	$I_S = 1A, V_{GS} = 0V$	$V_{SD}$	--	--	1.2	V
<b>Dynamic<sup>b</sup></b>						
Gate Resistance	$V_{DS} = 0V, V_{GS} = 0V, f = 1MHz$	$R_g$	--	1.4	2.8	$\Omega$
Total Gate Charge	$V_{DS} = 15V, I_D = 15A, V_{GS} = 4.5V$	$Q_g$	--	12.3	--	$nC$
Gate-Source Charge		$Q_{gs}$	--	1.95	--	
Gate-Drain Charge		$Q_{gd}$	--	3.08	--	
Input Capacitance	$V_{DS} = 15V, V_{GS} = 0V, f = 1MHz$	$C_{iss}$	--	961	--	$pF$
Output Capacitance		$C_{oss}$	--	92.3	--	
Reverse Transfer Capacitance		$C_{rss}$	--	80.4	--	
Reverse Recovery Time	$I_F = 15A, dI/dt = 100A/\mu s, T_J = 25^\circ C$	$t_{rr}$	--	6	--	ns
Reverse Recovery Charge		$Q_{rr}$	--	1.38	--	$nC$
<b>Switching<sup>b,c</sup></b>						
Turn-On Delay Time	$V_{DD} = 10V, I_D = 15A, V_{GS} = 4.5V, R_G = 3.3\Omega$	$t_{d(on)}$	--	3.02	--	ns
Turn-On Rise Time		$t_r$	--	13.1	--	
Turn-Off Delay Time		$t_{d(off)}$	--	28	--	
Turn-Off Fall Time		$t_f$	--	8.3	--	

**Notes:**


- a. Pulse test: PW  $\leq 300\mu s$ , duty cycle  $\leq 2\%$
- b. For DESIGN AID ONLY, not subject to production testing.
- c. Switching time is essentially independent of operating temperature.

**Electrical Characteristics Curve** ( $T_A=25^\circ\text{C}$ , unless otherwise noted)


**Output Characteristics**




**On-Resistance vs. Gate-Source Voltage**




**Source-Drain Diode Forward Voltage**




**Gate Charge**



**Normalized  $V_{GS(th)}$  vs.  $T_J$**




**Normalized  $R_{DS(ON)}$  vs.  $T_J$**




**Electrical Characteristics Curve** ( $T_A=25^\circ\text{C}$ , unless otherwise noted)

Capacitance




## SOP-8 Mechanical Drawing



Unit: Millimeters

## Marking Diagram



**Y** = Year Code

**M** = Month Code for Halogen Free Product

(**O**=Jan, **P**=Feb, **Q**=Mar, **R**=Apr, **S**=May, **T**=Jun, **U**=Jul, **V**=Aug, **W**=Sep,  
**X**=Oct, **Y**=Nov, **Z**=Dec)

**L** = Lot Code

## **Notice**

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for MOSFET category:***

***Click to view products by Taiwan Semiconductor manufacturer:***

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [JANTX2N5237](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [TPCC8103,L1Q\(CM](#)  
[MIC4420CM-TR](#) [VN1206L](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [SSM6J414TU,LF\(T](#) [751625C](#) [BUK954R8-60E](#)  
[NTE6400](#) [SQJ402EP-T1-GE3](#) [2SK2614\(TE16L1,Q\)](#) [2N7002KW-FAI](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [ECH8691-TL-W](#)  
[FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE221](#) [NTE2384](#) [NTE2903](#) [NTE2941](#) [NTE2945](#) [NTE2946](#) [NTE2960](#) [NTE2967](#)  
[NTE2969](#) [NTE2976](#) [NTE455](#) [NTE6400A](#) [NTE2910](#) [NTE2916](#) [NTE2956](#) [NTE2911](#) [DMN2080UCB4-7](#) [TK10A80W,S4X\(S](#)  
[SSM6P69NU,LF](#) [DMP22D4UFO-7B](#) [DMN1006UCA6-7](#)