

Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co.,Ltd.		
System	Band 32 (L-band) Rx	DATE	June. 25, 2014	
Part Number	F6QA1G474H2JS	Version 1.0aA	FINAL	

Table 1. Electrical specification

Passband: 1452 ~ 1496 MHz						
14	Condition	Specification				
Item	(MHz)	Min.	Тур.	Max.	Unit	Remarks
Insertion Loss	1452 ~ 1496	-	1.8	2.6	dB	(*1)
VSWR(Input)	1452 ~ 1496	-	1.8	2.2	-	
VSWR(Output)	1452 ~ 1496	1	1.8	2.2	-	
Absolute attenuation	814 ~ 915	45	47	-	dB	
	1226 ~ 1250	45	49	-	dB	
	1559 ~ 1980	45	54	-	dB	
	2400 ~ 2570	45	49	-	dB	
	2570 ~ 3500	30	41	-	dB	
	3500 ~ 4500	20	35	-	dB	
	4500 ~ 6000	20	38	-	dB	
Input Impedance			50		Ohm	Single-ended
Output Impedance			50		Ohm	Single-ended
Operating temp30 to +85		°C				
Package size 1.1typ.x 0.9typ.x 0.5max.		mm				

^(*1) Specification of insertion loss excludes loss that comes from the test board.






Customer Name	Standard Specification	TAIYO YUDEN Mobile	e Technology Co.,Ltd.
System	Band 32 (L-band) Rx	DATE	June. 25, 2014
Part Number	F6QA1G474H2JS	Version 1.0aA	FINAL

Dimensions


Device size: 1.1typ. x 0.9typ. x 0.5max



Pin Configuration

Pin No.	Symbol	Function
1	IN	Single-ended pin
2	GND	Ground
3	GND	Ground
4	OUT	Single-ended pin
5	GND	Ground

Test Condition





Customer Name	Standard Specification	TAIYO YUDEN Mobile	e Technology Co.,Ltd.
System	Band 32 (L-band) Rx	DATE	June. 25, 2014
Part Number	F6QA1G474H2JS	Version 1.0aA	FINAL




Fig.1 Pass-band Characteristics




Fig.2 In-band Characteristics





Customer Name	Standard Specification	TAIYO YUDEN Mobile	e Technology Co.,Ltd.
System	Band 32 (L-band) Rx	DATE	June. 25, 2014
Part Number	F6QA1G474H2JS	Version 1.0aA	FINAL




Fig.4 Wide-band Characteristics





Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co.,Ltd.		
System	Band 32 (L-band) Rx	DATE	June. 25, 2014	
Part Number	F6QA1G474H2JS	Version 1.0aA	FINAL	




Fig.5 Input Impedance




Fig.6 Output Impedance



Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co.,Ltd.		
System	Band 32 (L-band) Rx	DATE	June. 25, 2014	
Part Number	F6QA1G474H2JS	Version 1.0aA	FINAL	

Ordering Code

Ordering Code	Packing	Reel size	Status
F6QA1G474H2JS-J	Tape & Reel	5,000pcs.	MP
F6QA1G474H2JS-JA	Tape & Reel	less than 5,000 pcs.	MP
F6QA1G474H2JS-Y	Tape & Reel	15,000pcs	MP
F6QA1G474H2JS-YA	Tape & Reel	Less than 15,000pcs	MP
F6QA1G474H2JS-Q	Bulk	few pcs.	MP

^{*}Minimum order quantity (MOQ) is assigned for each inquiry, Please contact to Sales Representatives.

Notice

All of the contents specified herein are subject to change without notice due to technical improvements, etc.

Please contact TAIYO YUDEN Co., Ltd. for further details of product specifications.

Please conduct validation and verification of products in actual condition of mounting and operating environment before commercial shipment of the equipment.

This product is for general electronics equipment such as Audio-Visual equipment, household electronics, office supplies, information services and telecommunications; therefore, in case this product is used for any medical equipment, space equipment, nuclear equipment or disaster prevention equipment, please contact TAIYO YUDEN in advance.

In case this product is used for general electronics equipment or circuits which require high safety and high reliability, thoroughly evaluate on safety and add a protection circuit if necessary.



^{*} MP : Mass Production.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Signal Conditioning category:

Click to view products by Taiyo Yuden manufacturer:

Other Similar products are found below:

MAPDCC0001 MAPDCC0004 PD0409J5050S2HF 880157 HHS-109-PIN DC1417J5005AHF AFS14A30-2185.00-T3 AFS14A35-1591.50-T3 DS-323-PIN B39321R801H210 1A0220-3 JP510S LFB212G45SG8C341 LFB322G45SN1A504 LFL182G45TC3B746 SF2159E 30057 FM-104-PIN CER0813B MAPDCC0005 3A325 40287 41180 ATB3225-75032NCT BD0810N50100AHF BD2425J50200AHF C5060J5003AHF JHS-115-PIN JP503AS DC0710J5005AHF DC2327J5005AHF DC3338J5005AHF 43020 LFB2H2G60BB1C106 LFL15869MTC1B787 X3C19F1-20S XC3500P-20S 10013-20 SF2194E CDBLB455KCAX39-B0 TGL2208-SM, EVAL RF1353C 1E1305-3 1F1304-3S 1G1304-30 B0922J7575AHF 2020-6622-20 10017-3 TP-103-PIN BD1222J50200AHF