



Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co., Ltd.		
System	Band 3 - Tx	DATE	July 29, 2013	
Part Number	F6QA1G747M2QS	Version 1.0a	Final	

Table 1. Electrical Specification						
10	On a Prince (MILL)	Propo	sal Specif	ication	11.2	D I .
Item	Condition (MHz)	Min.	Тур.	Max.	Unit	Remarks
	4740 4705	-	2.1	2.4	dB	at 25 °C
Insertion Loss(*1)	1710 - 1785	-	-	3.0	dB	
Dinnlo	1710 1705	-	1.0	1.5	dB	at 25 °C
Ripple	1710 - 1785	-	-	2.0	dB	
VSWR (Input)	1710 - 1785	-	1.8	2.2	-	
VSWR (Output)	1710 - 1785	-	1.8	2.2	-	
Absolute attenuation	DC - 1570	25	36	-	dB	
	1570 - 1580	35	41	-	dB	
	4005 4000	15	22	-	dB	at 25 °C
	1805 - 1880	10	-	-	dB	
	1930 - 2400	25	34	-	dB	
	2400 - 3000	15	32	-	dB	
	3000 - 4000	10	27	-	dB	
	4000 - 6000	5	21	-	dB	
Input impedance	-	50 // 7.5nH		Ohms		
Output impedance	-	50 // 6.8nH		Ohms		
Temperature range	-	-30 to +85		°C		
Package size	-	1.1typ x 0.9typ x 0.5max mm				

^(*1) Specification of insertion loss includes loss that comes from the test board. (Value: 0.15dB)








Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co., Ltd.		
System	Band 3 - Tx	DATE	July 29, 2013	
Part Number	F6QA1G747M2QS	Version 1.0a	Final	

Dimensions

Device size: 1.1typ. x 0.9typ. x 0.5max.




Unit: mm

Pin Configuration

Pin No.	Symbol	Function	
1	IN	Unbalanced pin	
2	GND	Ground	
3	GND	Ground	
4	OUT	Unbalanced pin	
5	GND	Ground	

Evaluation Circuit




1 to 5; Pin No.







Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co., Ltd.		
System	Band 3 - Tx	DATE	July 29, 2013	
Part Number	F6QA1G747M2QS	Version 1.0a	Final	






Fig.2 In-band Characteristics







Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co., Ltd.		
System	Band 3 - Tx	DATE	July 29, 2013	
Part Number	F6QA1G747M2QS	Version 1.0a	Final	




Fig.3 Wide-band Characteristics







Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co., Ltd.		
System	Band 3 - Tx	DATE	July 29, 2013	
Part Number	F6QA1G747M2QS	Version 1.0a	Final	




Fig.4 Input VSWR 11.0 Mk1: 1710.0MHz VSWR2= 1.469 10.0 Mk2: 1785.0MHz VSWR2= 1.464 9.0 8.0 7.0 VSWR 6.0 5.0 4.0 3.0 2.0 1.0 1738 1750 1762 Frequency[MHz] 1774 1786 1714 1690 1702 1726 1798 1810

Fig.5 Output VSWR







Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co., Ltd.		
System	Band 3 - Tx	DATE	July 29, 2013	
Part Number	F6QA1G747M2QS	Version 1.0a	Final	




Fig.6 Input Impedance




Fig.7 Output Impedance







Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co., Ltd.		
System	Band 3 - Tx	DATE	July 29, 2013	
Part Number	F6QA1G747M2QS	Version 1.0a	Final	

Ordering Code

Ordering Code	Packing	Reel size	Status
F6QA1G747M2QS-J	Tape & Reel	5,000pcs.	MP
F6QA1G747M2QS-JA	Tape & Reel	less than 5,000 pcs.	MP
F6QA1G747M2QS-Y	Tape & Reel	15,000pcs	MP
F6QA1G747M2QS-YA	Tape & Reel	less than 15,000pcs	MP
F6QA1G747M2QS-Q	Bulk	few pcs.	MP

^{*}Minimum order quantity (MOQ) is assigned for each inquiry, Please contact to Sales Representatives..

Notice

All of the contents specified herein are subject to change without notice due to technical improvements, etc.

Please contact TAIYO YUDEN Co., Ltd. for further details of product specifications.

Please conduct validation and verification of products in actual condition of mounting and operating environment before commercial shipment of the equipment.

This product is for general electronics equipment such as Audio-Visual equipment, household electronics, office supplies, information services and telecommunications; therefore, in case this product is used for any medical equipment, space equipment, nuclear equipment or disaster prevention equipment, please contact TAIYO YUDEN in advance.

In case this product is used for general electronics equipment or circuits which require high safety and high reliability, thoroughly evaluate on safety and add a protection circuit if necessary.



^{*}MP : Engineering Sample

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Signal Conditioning category:

Click to view products by Taiyo Yuden manufacturer:

Other Similar products are found below:

MAPDCC0001 MAPDCC0004 PD0409J5050S2HF 880157 HHS-109-PIN DC1417J5005AHF AFS14A30-2185.00-T3 AFS14A35-1591.50-T3 DS-323-PIN B39321R801H210 1A0220-3 JP510S LFB212G45SG8C341 LFB322G45SN1A504 LFL182G45TC3B746 SF2159E 30057 FM-104-PIN CER0813B MAPDCC0005 3A325 40287 41180 ATB3225-75032NCT BD0810N50100AHF BD2425J50200AHF C5060J5003AHF JHS-115-PIN JP503AS DC0710J5005AHF DC2327J5005AHF DC3338J5005AHF 43020 LFB2H2G60BB1C106 LFL15869MTC1B787 X3C19F1-20S XC3500P-20S 10013-20 SF2194E CDBLB455KCAX39-B0 TGL2208-SM, EVAL RF1353C 1E1305-3 1F1304-3S 1G1304-30 B0922J7575AHF 2020-6622-20 10017-3 TP-103-PIN BD1222J50200AHF