



TAOGLAS®



Datasheet

NCP.5820

Part No:
NCP.5820

Description:

NB-IoT SMD Ceramic Antenna
For Bands 5, 8 and 20

Features:

Small size, small footprint SMD antenna
Global NB-IoT Coverage for:
Band 5, 824-894MHz
Band 8, 880-960MHz
Band 20, 791-862mHz
High efficiency across each band
Dimensions: 14.1 x 8.3 x 2mm
Automotive IATF16949 Production and Quality Approved
RoHS & Reach Compliant


| | | |
|-------|-----------------------------------|----|
| 1. | Introduction | 3 |
| 2. | Specifications | 4 |
| 3. | Antenna Characteristics | 5 |
| 4. | Radiation Patterns | 9 |
| 5. | Mechanical Drawing | 18 |
| 6. | Antenna Integration Guide | 22 |
| 7. | Evaluation Board Matching Circuit | 25 |
| 8. | Packaging | 27 |
| <hr/> | | |
| | Changelog | 28 |

Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited.



1. Introduction



The evolution of IoT connectivity has seen an urgent need for low power applications that can connect thousands of devices to the internet and Narrowband IoT (NB-IoT) is a new way to facilitate this demand. For a small compact embedded antenna, the Taoglas NCP.5820 fits will fit in many size challenged designs without performance compromises.

The Taoglas NCP.5820 supports Bands 5 (824-894MHz), 8 (880-960MHz) and 20 (791-862MHz) providing global NB-IoT coverage and demonstrates excellent efficiency across all bands.

The antenna measures just 14.1x8.3x2mm and as it is a surface mount antenna, it can be easily integrated into the smallest of devices. It allows device designers to take advantage of all of the benefits of NB-IoT technology, including reduced power consumption and increased battery life; increased system capacity and spectrum efficiency; and extended coverage in both rural and deep indoors environments all with a very small form factor. For Testing, the NCP.5820 can be supplied with the evaluation board NCPD.5820 – see section 5.

Overall, this antenna is suitable for applications that need to meet the following requirements:

- Small footprint, low profile design factor
- SMD Components for assembly accuracy and reliability
- Excellent antenna efficiency helping to maintain better system gain, hence better device send and receive sensitivity (TRP & TIS)
- Excellent antenna efficiency to aid lower power consumption and increased battery life
- Global coverage for device roaming
- 100% quality and performance testing prior to shipping for reliability and consistency

For more information or support with integrating this antenna into your device, please contact your regional Taoglas customer support team.

2. Specifications

| Band 5,8 Electrical | | | |
|---------------------|---------|---------|--|
| | Band 5 | Band 8 | |
| Frequency (MHz) | 824~894 | 880~960 | |
| Peak Gain (dBi)* | 0.6 | 1.2 | |
| Average Gain (dB)* | -3.5 | -2.7 | |
| Efficiency (%) * | 53.5 | 60.7 | |
| Return Loss (dB)* | <-4.5 | <-5 | |

| Band 5,8,20 Electrical | | | |
|------------------------|---------|---------|---------|
| | Band 5 | Band 8 | Band 20 |
| Frequency (MHz) | 824~894 | 880~960 | 791~862 |
| Peak Gain (dBi)* | 1.1 | 1.7 | -0.3 |
| Average Gain (dB)* | -3.9 | -3.1 | -4.3 |
| Efficiency (%) * | 47 | 53.1 | 38.7 |
| Return Loss (dB)* | <-4.5 | <-5 | <-4.5 |
| Impedance | 50 Ω | | |
| Maximum Input Power | 5W | | |

| Mechanical | |
|--------------------|----------------------|
| Antenna Dimensions | 14.1mm x 8.3mm x 2mm |
| Material | Ceramic |
| Weight | 0.76 g |
| Soldering Type | SMD through Reflow |

| Environmental | |
|----------------------------------|----------------------------|
| Operation Temperature | -40°C ~ +85°C |
| Storage Temperature | -40°C ~ +85°C |
| Humidity | Non-condensing 65°C 95% RH |
| Moisture Sensitivity Level (MSL) | 3 (168 Hours) |


*Note: All measurements were conducted with SMD on a 115*35mm evaluation board with 100mm length ground plane and matching circuit. See EVB drawing and matching circuit diagram in Section 5 and Section 7.

3. Antenna Characteristics


All data was measured on the evaluation board illustrated in Section 5.4, with the documented matching circuit, section 7

3.1 Band 5 & 8 configuration


Return Loss




Efficiency



Average Gain




Peak Gain




3.2 Band 5,8 & 20 configuration


Return Loss




Efficiency



Average Gain




Peak Gain




4. Radiation Patterns

4.1 Test Setup Band 5 & 8 configuration



On Evaluation Board (NCPD.5820)




4.2 824 MHz 3D and 2D Radiation Patterns




XZ Plane

YZ Plane




XY Plane




4.3 894 MHz 3D and 2D Radiation Patterns






XZ Plane YZ Plane XY Plane




4.4 960 MHz 3D and 2D Radiation Patterns



XZ Plane YZ Plane XY Plane




4.5 Test Setup Band 5,8 & 20 configuration



On Evaluation Board (NCPD.5820)




4.6 791MHz 3D and 2D Radiation Patterns




XZ Plane

YZ Plane

XY Plane






4.7 824 MHz 3D and 2D Radiation Patterns




XZ Plane

YZ Plane

XY Plane






4.8 894 MHz 3D and 2D Radiation Patterns




XZ Plane

YZ Plane

XY Plane






4.9 960 MHz 3D and 2D Radiation Patterns



XZ Plane


YZ Plane

XY Plane




5. Mechanical Drawings(Units: mm)


5.1 Antenna Drawing




5.2 Paste Area



5.3 Copper Keep-Out Areas




Top View (Keep-out area)




Bottom View (Keep-out area)

Note:

- 1. Soldered area 
- 2. Copper area 
- 3. Ground Clearance Area 


5.4 Evaluation Board



6. Antenna Integration Guide

6.1 Integration Guide

Whatever the size of the PCB, the ideal location for the antenna is as illustrated in the below diagram; on the PCB's shortest side, in the left corner. This allows placement of the optimized matching components alongside the antenna.




6.2 PCB Layout

The footprint and clearance on the PCB must comply with the antenna specification. The PCB layout shown in the diagram below demonstrates the antenna footprint and the clearance required. The component should be close to Pin 7.




Topside




Bottom Side

6.3 PCB Clearance

In the figure in this section, the footprint and clearance are defined through all layers on the PCB. Only the antenna pads and connections to feed and GND are present within this clearance area (marked RED). The clearance area required is 14.6 x 8.9 (mm). An additional clearance area (marked BLACK) is also needed for the antenna to operate 21.4 x 12.2 (mm).



Topside




Bottom Side

6.4 Schematic Symbol and Pin Definitions

The circuit symbol for the antenna is shown below. The antenna has 7 pins with only two as functional. All other pins are for mechanical strength.



| Pin | Description |
|---------------|---------------|
| 1 | RF Feed |
| 7 | Ground |
| 2, 3, 4, 5, 6 | Not Connected |



7. Evaluation Board Matching Circuit

The antenna may need a matching circuit that can be optimized for each product integration. The matching circuit will require up to four components and the following circuit should be designed into the PCB. Not all components may be required but should be included as a precaution. The matching network must be placed close to the antenna feed to ensure it is more effective for matching the antenna.



Band 5, 8 and 20 Matching Components



Band 5,8 and 20 Matching Components

| Designator | Type | Value | Description |
|------------|-----------|-------|-----------------------|
| C1 | Capacitor | 0.5pF | Murata GJM1555 series |
| L1 | Inductor | 1.5nH | Murata LQG15HS series |
| L2 | Inductor | 6.8nH | Murata LQG15HS series |
| L3 | Inductor | 33nH | Murata LQG15HS series |

Band 5, 8 Matching Components




Band 5,8 Matching Components


| Designator | Type | Value | Description |
|------------|-----------|-------|-----------------------------|
| C1 | Capacitor | 0.5pF | Murata GJM1555 series |
| L2 | Inductor | 5.6nH | Murata LQG15HS series |
| L3 | Inductor | 33nH | Murata LQG15HS series |
| R1 | Resistor | 0 Ω | Vishay Dale CRCW0402 series |

8. Packaging

700pcs NCP.5820 per Tape & Reel
 Dimensions: 330**330*47mm
 Weight: 1.1Kg



3500 pcs in one carton
 Dimensions: 370*360*275mm
 Weight: 5.6Kg



Changelog for the datasheet

SPE-18-8-098 – NCP.5820

Revision: I (Current Version)

| | |
|----------|-----------------------|
| Date: | 2021-09-15 |
| Changes: | Added MSL information |
| Author: | Erik Landi |

Previous Revisions

Revision: H

| | |
|----------|-----------------------|
| Date: | 2019-12-17 |
| Changes: | Updated Eval drawings |
| Author: | Jack Conroy |

Revision: C

| | |
|------------------|----------------------------|
| Date: | 2018-10-11 |
| Changes: | Added Automotive IATF16949 |
| Changes Made by: | Sean Hancox |

Revision: G

| | |
|------------------|--------------------------|
| Date: | 2019-12-11 |
| Changes: | Updated Matching Circuit |
| Changes Made by: | Jack Conroy |

Revision: B

| | |
|------------------|------------------------------|
| Date: | 2018-09-27 |
| Changes: | Updated Packaging spec sheet |
| Changes Made by: | Russell Meyler |

Revision: F

| | |
|------------------|-------------------------------------|
| Date: | 2019-09-19 |
| Changes: | Updated template, updated footprint |
| Changes Made by: | Jack Conroy |

Revision: A

| | |
|------------------|---------------------------|
| Date: | 2018-09-11 |
| Changes: | Initial Datasheet Release |
| Changes Made by: | Jack Conroy |

Revision: E

| | |
|------------------|------------------|
| Date: | 2018-12-13 |
| Changes: | Added Pin layout |
| Changes Made by: | Jack Conroy |

Revision: D

| | |
|------------------|----------------------------|
| Date: | 2018-12-04 |
| Changes: | Added Automotive IATF16949 |
| Changes Made by: | Jack Conroy |



TAOGLAS®

www.taoglas.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antennas](#) category:

Click to view products by [Taoglas](#) manufacturer:

Other Similar products are found below :

[GAN30084EU](#) [930-033-R](#) [GW17.07.0250E](#) [1513563-1](#) [EXE902SM](#) [APAMPG-117](#) [MAF94383](#) [W3908B0100](#) [W6102B0100](#) [YE572113-30RSMM](#) [108-00014-50](#) [66089-2406](#) [SPDA17RP918](#) [A09-F8NF-M](#) [A09-F5NF-M](#) [RGFRA1903041A1T](#) [W3593B0100](#) [W3921B0100](#) [SIMNA-868](#) [SIMNA-915](#) [SIMNA-433](#) [W1044](#) [W1049B090](#) [A75-001](#) [WTL2449CQ1-FRSMM](#) [CPL9C](#) [EXB148BN](#) [0600-00060](#) [TRA9020S3PBN-001](#) [GD5W-28P-NF](#) [MA9-7N](#) [GD53-25](#) [GD5W-21P-NF](#) [C37](#) [MAF94051](#) [MA9-5N](#) [EXD420PL](#) [B1322NR](#) [QWFTB120](#) [MAF94271](#) [MAF94300](#) [GPSMB301](#) [FG4403](#) [AO-AGSM-OM54](#) [5200232](#) [MIKROE-2349](#) [WCM.01.0111](#) [MIKROE-2393](#) [MIKROE-2352](#) [MIKROE-2350](#)