

SPECIFICATION PATENTED

Part No.	:	TG.30.8112
Product Name	:	Apex Black Right Angle TG.30
		Ultra-Wideband 4G LTE Antenna
Feature	:	LTE / GSM / CDMA /DCS /PCS / WCDMA / UMTS /
		HSDPA / GPRS / EDGE /GPS /Wi-Fi
		698MHz to 960MHz, 1575.42MHz,
		1710MHz to 2700Mhz
		Patented
		Typical 70%+ Efficiency and 3dBi+ Peak Gain
		Dipole Swivel Terminal Antenna
		90° termination with SMA(M) Connector
		UV Resistant, IP65 Rated Waterproof Enclosure
		RoHS Compliant









1. Introduction

The Apex TG.30 is an omnidirectional 4G LTE antenna. This fixed 90 degree, connector mount, dipole antenna is primarily designed for use with 4G LTE modules and devices that require the highest possible efficiency and peak gain in order to deliver best-in-class throughput. Ideal for all major worldwide cellular bands, it is perfect for access points, terminals, and routers. The antenna is ground plane independent with an SMA(M) connector and is backward compatible with 3G/2G cellular applications such as GSM, LTE, UMTS, Wi-Fi, and even GPS bands for Assisted GPS and/or E911 applications. With very high efficiency on all global cellular bands, it is an ideal solution for any device requiring reliable performance. It is also guaranteed to meet any type of approval or carrier certification requirements from an RF standpoint.

The Apex TG.30 has a robust, UV-resistant, IP65 rated waterproof enclosure that has been designed so the TG.30 can be used in challenging environments. This patented antenna is available in both white and black versions, and it is also available with straight and rotatable connectors. For more information, contact your regional Taoglas customer support teams.



2. Specification

ELECTRICAL								
Frequency (MHz)	700~800	824~960	1575.42	1710 ~ 1880	1850 ~ 1990	1710 ~ 2170	2400~2700	
Peak Gain (dBi)								
Free Space	2.7	2.1	0.3	3.5	3.6	3.6	5.3	
30x30cm GP center	4.3	5.3	5.3	6.7	6.8	7.5	8.1	
30x30cm GP edge	4.4	2.4	0.5	1.9	2.0	2.5	3.2	
PCB edge	3.2	1.9	2.4	3.2	3.3	3.6	4.7	
Average Gain								
Free Space	-0.7	-1.2	-1.2	-0.4	-0.4	-0.2	-0.6	
30x30cm GP center	-2.8	-1.0	-2.4	-1.6	-1.8	-1.3	-1.2	
30x30cm GP edge	-0.1	-4.3	-2.5	-2.0	-2.0	-2.0	-2.2	
PCB edge	0.8	-1.9	-0.9	-0.6	-0.6	-0.6	-0.8	
Efficiency								
Free Space	85%	75%	76%	90%	90%	90%	87%	
30x30cm GP center	52%	39%	57%	70%	65%	74%	75%	
30x30cm GP edge	91%	64%	56%	62%	62%	63%	60%	
PCB edge	86%	87%	81%	86%	86%	86%	84%	
Impedance		50Ω						
Polarization		Linear						
Radiation Pattern		Omni						
Input Power	10 W							
			MEC	HANICAL				
Casing	UV Resistant PC/ABS							
Connecto	r	SMA Male						
IP Rating			IP65					
ENVIRONMENTAL								
Temperature Range -40°C to 85°C								
Humidity			Non-condensing 65°C 95% RH					



LTE BANDS								
Band Number	LTE / LTE-Advanced ,	/ TD-SCDMA						
	Uplink	Downlink	Covered					
1	UL: 1920 to 1980	DL: 2110 to 2170	\checkmark					
2	UL: 1850 to 1910	DL: 1930 to 1990	\checkmark					
3	UL: 1710 to 1785	DL: 1805 to 1880	\checkmark					
4	UL: 1710 to 1755	DL: 2110 to 2155	\checkmark					
5	UL: 824 to 849	DL: 869 to 894	\checkmark					
7	UL: 2500 to 2570	DL:2620 to 2690	\checkmark					
8	UL: 880 to 915	DL: 925 to 960	\checkmark					
9	UL: 1749.9 to 1784.9	DL: 1844.9 to 1879.9	\checkmark					
11	UL: 1427.9 to 1447.9	DL: 1475.9 to 1495.9	×					
12	UL: 699 to 716	DL: 729 to 746	\checkmark					
13	UL: 777 to 787	DL: 746 to 756	\checkmark					
14	UL: 788 to 798	DL: 758 to 768	\checkmark					
17	UL: 704 to 716	DL: 734 to 746 (LTE only)	\checkmark					
18	UL: 815 to 830	DL: 860 to 875 (LET only)	✓					
19	UL: 830 to 845	DL: 875 to 890	\checkmark					
20	UL: 832 to 862	DL: 791 to 821	\checkmark					
21	UL: 1447.9 to 1462.9	DL: 1495.9 to 1510.9	×					
22	UL: 3410 to 3490	DL: 3510 to 3590	×					
23	UL:2000 to 2020	DL: 2180 to 2200 (LTE only)	\checkmark					
24	UL:1625.5 to 1660.5	DL: 1525 to 1559 (LTE only)	\checkmark					
25	UL: 1850 to 1915	DL: 1930 to 1995	\checkmark					
26	UL: 814 to 849	DL: 859 to 894	\checkmark					
27	UL: 807 to 824	DL: 852 to 869 (LTE only)	\checkmark					
28	UL: 703 to 748	DL: 758 to 803 (LTE only)	✓					
29	UL: -	DL: 717 to 728 (LTE only)	\checkmark					
30	UL: 2305 to 2315	DL: 2350 to 2360 (LTE only)	✓					
31	UL: 452.5 to 457.5	DL: 462.5 to 467.5 (LTE only)	×					
32	UL: -	DL: 1452 - 1496	×					
35	1850 t	✓						
38	2570 t	✓						
39	1880 t	\checkmark						
40	2300 t	\checkmark						
41	2496 t	\checkmark						
42	3400 t	×						
43	3600 t	×						

*Covered bands represent an efficiency greater than 20%



3. Antenna Characteristics





3.2 Peak Gain







3.3 Average Gain

3.4 Efficiency





4. Antenna Radiation Patterns

4.1 Antenna setup (Free Space)





4.2 Radiation Patterns (Free Space)

XY Plane





XZ Plane





4.3 Antenna setup (On 300x300mm ground center)





4.4 Radiation Patterns (On 300x300mm ground center)

XY Plane







XZ Plane







4.5 Antenna setup (On 300x300mm ground edge)





4.6 Radiation Patterns (On 300x300mm ground edge)

XY Plane







XZ Plane







4.7 Antenna setup (On Ground Plane edge)





4.8 Radiation Patterns (On Ground Plane edge)

XY Plane





XZ Plane







5. Drawing





6. Packaging





Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited.

Copyright © Taoglas Ltd.

US Patent No.: 9559423

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Taoglas manufacturer:

Other Similar products are found below :

 GAN30084EU
 930-033-R
 GW17.07.0250E
 1513563-1
 EXE902SM
 APAMPG-117
 MAF94383
 W3908B0100
 W6102B0100
 YE572113

 30RSMM
 108-00014-50
 66089-2406
 SPDA17RP918
 A09-F8NF-M
 A09-F5NF-M
 RGFRA1903041A1T
 W3593B0100
 W3921B0100

 SIMNA-868
 SIMNA-915
 SIMNA-433
 W1044
 W1049B090
 A75-001
 WTL2449CQ1-FRSMM
 CPL9C
 EXB148BN
 0600-00060

 TRA9020S3PBN-001
 Y4503
 GD5W-28P-NF
 MA9-7N
 GD53-25
 GD5W-21P-NF
 C37
 MAF94051
 MA9-5N
 EXD420PL
 B1322NR

 QWFTB120
 MAF94271
 MAF94300
 GPSMB301
 FG4403
 A0-AGSM-OM54
 5200232
 MIKROE-2349
 WCM.01.0111
 MIKROE-2393

 MIKROE-2352
 MIKROE-2352
 MIKROE-2352
 MIKROE-2349
 WCM.01.0111
 MIKROE-2393