

SPECIFICATION

Part No.	:	WLP.4958.12.4.A.02	
Product Name	:	12mm*12mm*4mm 4.9~5.8GHz Patch Pin Fed Embedded High Gain Antenna	
Features	:	For Wi-Fi/WLAN/ISM/Public Safety/Zigbee Industrial and Consumer Applications High Gain 6dBi RoHS Compliant ✓	





1. Introduction

This 12mm*12mm*4mm 6dBi high gain 4.9~5.8GHz patch pin fed antenna is ideally suited for high performance industrial and consumer applications in Wi-fi, ISM, Public Safety, and Zigbee bands. It can also be placed anywhere on the device ground-plane, unlike most chip or loop antennas which need to be edge mounted. The antenna can be matched by a PI matching circuit, or by creating a custom tuned part for a specific layout configuration on a board.

Many module manufacturers specify peak gain limits for any antennas that are to be connected to that module. Those peak gain limits are based on free-space conditions. In practice, the peak gain of an antenna tested in free-space can degrade by at least 1 or 2dBi when put inside a device. So ideally you should go for a slightly higher peak gain antenna than mentioned on the module specification to compensate for this effect, giving you better performance.

Upon testing of any of our antennas with your device and a selection of appropriate layout, integration technique, or cable, Taoglas can make sure any of our antennas' peak gain will be below the peak gain limits. Taoglas can then issue a specification and/or report for the selected antenna in your device that will clearly show it complying with the peak gain limits, so you can be assured you are meeting regulatory requirements for that module.

For example, a module manufacturer may state that the antenna must have less than 2dBi peak gain, but you don't need to select an embedded antenna that has a peak gain of less than 2dBi in free-space. This will give you a less optimized solution. It is better to go for a slightly higher free-space peak gain of 3dBi or more if available. Once that antenna gets integrated into your device, performance will degrade below this 2dBi peak gain due to the effects of GND plane, surrounding components, and device housing. If you want to be absolutely sure, contact Taoglas and we will test. Choosing a Taoglas antenna with a higher peak gain than what is specified by the module manufacturer and enlisting our help will ensure you are getting the best performance possible without exceeding the peak gain limits.



2. Specification*

No	Parameter	Specification
1	Range of Receiving Frequency	4900MHz to 5825MHz
2	Center Frequency	5180MHz±5.0MHz
3	Bandwidth	450 MHz @ Return Loss ≤-10dB
4	Polarization	Linear
5	VSWR	1.5 max @ Center Frequency
6	Peak Gain	+6.0dBic typ. @ Center Frequency
7	Impedance	50 Ohms
8	Dimensions	12mm x 12mm x 4mm
9	Frequency Temperature Coefficient (Tf)	0 ± 20ppm / °C -40°C to +85°C
10	Operating Temperature	-40°C to +85°C

Original Patch Specification measured on EVB 70*70mm, actual value depends on ground-plane and housing



3. Antenna Characteristics



3.1Return Loss









3.3Average Gain



3.4 Peak Gain



4.2D Radiation Patterns

4.1 Antenna Setup (70*70mm Ground Plane)



4.2 XY Plane Radiation







180

(dBi)



5. Drawing





5.1 Layout Dimensions



TDL:±0.20 UNIT:mm

5.2 Test Jig and Dimension





5.3 .Test Fixture Antenna Setup & Measurement





6.Packaging

Pieces per Inner Carton: 400







Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited.

Copyright © Taoglas Ltd.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Taoglas manufacturer:

Other Similar products are found below :

 GAN30084EU
 930-033-R
 GW17.07.0250E
 1513563-1
 EXE902SM
 APAMPG-117
 MAF94383
 W3908B0100
 W6102B0100
 YE572113

 30RSMM
 108-00014-50
 66089-2406
 A09-F8NF-M
 A09-F5NF-M
 RGFRA1903041A1T
 W3593B0100
 W3921B0100
 SIMNA-868
 SIMNA

 915
 SIMNA-433
 W1044
 W1049B090
 A75-001
 WTL2449CQ1-FRSMM
 CPL9C
 EXB148BN
 0600-00060
 TRA9020S3PBN-001
 GD5W

 28P-NF
 MA9-7N
 GD53-25
 GD5W-21P-NF
 EXB144SM
 C37
 MAF94051
 P1744
 MA9-5N
 EXD420PL
 B1322NR
 QWFTB120

 MAF94271
 MAF94300
 GPSMB301
 FG4403
 AO-AGSM-OM54
 5200232
 MIKROE-2349
 WCM.01.0111
 MIKROE-2393
 MIKROE-2352