

Multilayer Antenna (Dual Band type)

For 2400-2484MHz / 5150-5850MHz

ANT162442DT-2001A2

1.6x0.8mm [EIA 0603]*

* Dimensions Code JIS[EIA]




Multilayer Antenna


For 2400-2484MHz / 5150-5850MHz

Conformity to RoHS Directive

ANT162442DT-2001A2

SHAPES AND DIMENSIONS






Terminal functions					
1	Radiator electrode for 2.4GHz ISM				
2	Feed point				
3	Feed point				
4	Radiator electrode for 5.5GHz				
5	Feed point				
6	Feed point				


Dimensions in mm

■ RECOMMENDED LAND PATTERN



Dimensions in mm

SOLDER RESIST PATTERN




Dimensions in mm

OROHS Directive Compliant Product: See the following for more details.https://product.tdk.com/info/en/environment/rohs/index.html


[•] All specifications are subject to change without notice.

[•] Before using these products, be sure to request the delivery specifications.

EVALUATION BOARD




PCB size : 50mm x 20mm x 1mm Antenna area : 8 x 5 mm



	Component P/N
Ft 2.4GHz	6.2pF
Ft 5.5GHz	0.4pF
Mt Common	1.3nH(MLG1005S1N3C:TDK)

☐ Measurement condition for Radiation Pattern



- All specifications are subject to change without notice.Before using these products, be sure to request the delivery specifications.



ELECTRICAL CHARACTERISTICS

Item	Frequency Range (MHz)	Min.	Тур.	Max.		
VSWR	2400 to 2484	_	1.54	3.0		
VOVIN	5150 to 5850	_	1.58	3.0		
Polarization			Linear			
PCB size (mm)			50×20			
Antenna keep-out area (mm)			8×5			
Characteristic Impedance (Ω)			50 (Nominal)			


[·] This is typical antenna performance with the standard PCB.

■TEMPERATURE RANGE


Operating temperature	Storage temperature
(°C)	(°C)
-40 to +85	-40 to +85

■ FREQUENCY CHARACTERISTICS

□2.4GHz WLAN BAND



□5.5GHz WLAN BAND




 \bullet Tested antenna has been soldered. Evaluation board size is 50x20x1 mm.

[•] All specifications are subject to change without notice.

[•] Before using these products, be sure to request the delivery specifications.

RADIATION PATTERNS

□2.4GHz ISM BAND




• Tested antenna has been soldered. Evaluation board size is 50x20x1 mm.

- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

RADIATION PATTERNS

□5.5GHZ BAND




[•]Tested antenna has been soldered. Evaluation board size is 50x20x1 mm.

- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.



■ RECOMMENDED REFLOW PROFILE




Soaking			Working		Soldering Peak	Soldering Peak		
Temp. Time		Temp.	Time	Temp. Time		Temp.		
T1	T2	t1	Т3	t2	T4	t3	T5	
150°C	180°C	60 to 120s	230°C	30 to 60s	247 to 253°C	within 10s	260°C max.	


All specifications are subject to change without notice.Before using these products, be sure to request the delivery specifications.



■PACKAGING STYLE


□REEL DIMENSIONS





Dimensions in mm

TAPE DIMENSIONS



Dimensions in mm										sions in mm
Α	В	С	D	Е	F	G	Н	J	K	t
0.97±0.05	1.8±0.05	8.0±0.2	3.5±0.05	1.75±0.1	4.0±0.1	2.0±0.05	4.0±0.1	1.5+0.1/-0	0.55max.	0.25±0.05

■ PACKAGE QUANTITY

Standardpackage quantity
(pieces/reel)
4,000

[•] All specifications are subject to change without notice.

[•] Before using these products, be sure to request the delivery specifications.



REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using these products.

⚠ REMINDERS

The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.

The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.

Please understand that we are not responsible for any damage or liability caused by use of the products in any of the applications below or for any other use exceeding the range or conditions set forth in this catalog.

- (1) Aerospace/Aviation equipment
- (2) Transportation equipment (cars, electric trains, ships, etc.)
- (3) Medical equipment
- (4) Power-generation control equipment
- (5) Atomic energy-related equipment
- (6) Seabed equipment
- (7) Transportation control equipment

- (8) Public information-processing equipment
- (9) Military equipment
- (10) Electric heating apparatus, burning equipment
- (11) Disaster prevention/crime prevention equipment
- (12) Safety equipment
- (13) Other applications that are not considered general-purpose applications

When using this product in general-purpose applications, you are kindly requested to take into consideration securing protection circuit/ equipment or providing backup circuits, etc., to ensure higher safety.

[•] All specifications are subject to change without notice.

[•] Before using these products, be sure to request the delivery specifications.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by TDK manufacturer:

Other Similar products are found below:

CCT FM1 ABFT AD-NM-SMAF 001-0021 CTC110 MAF94149 EXE902SF MMCX-SMA-100 PDQ24496-91NF GAN30084EU 930-033-R A08-HABUF-P5I AAF95035 DG-ANT-20DP-BG-B APAMPGJ-141 1513563-1 OF86315-FNF OP24516DS-91NM A09-HASM-7 EXE902MD EXE902SM SPDA17806/2170LAR APAMPG-117 GPS1575SP26-004 GPS15MGSMA CMD69273P-30NF CMQ69273-30NF RD2458-5-OTDR-NM RD2458-5-RSMA TRAB24/49003 W4120ER5000 W6102B0100 YE572113-30RSMM 108-00014-50 SPDA17RP918 OP24516SX-91NM OP24516SX-91RSMM CMQ69273P-30NF CMS69273-30NF CMS69273P-30NF TRAB24003N TRAB8213NP TRAB8903 A09-Y8NF A09-Y11NF A09-HSM-7 A09-F8NF-M A09-F5NF-M