



MULTILAYER CERAMIC CHIP CAPACITORS

CGA3EA Series Automotive Grade ESD Protection

Case size: 1608 [EIA CC0603]

**Issue date:
Dec 2014**



REMINDERS

Please read before using this product

SAFETY REMINDERS



REMINDERS

1. If you intend to use a product listed in this catalog for a purpose that may cause loss of life or other damage, you must contact our company's sales window.
2. We may modify products or discontinue production of a product listed in this catalog without prior notification.
3. We provide "Delivery Specification" that explain precautions for the specifications and safety of each product listed in this catalog. We strongly recommend that you exchange these delivery specifications with customers that use one of these products.
4. If you plan to export a product listed in this catalog, keep in mind that it may be a restricted item according to the "Foreign Exchange and Foreign Trade Control Law". In such cases, it is necessary to acquire export permission in harmony with this law.
5. Any reproduction or transferring of the contents of this catalog is prohibited without prior permission from our company.
6. We are not responsible for problems that occur related to the intellectual property rights or other rights of our company or a third party when you use a product listed in this catalog. We do not grant license of these rights.
7. This catalog only applies to products purchased through our company or one of our company's official agencies. This catalog does not apply to products that are purchased through other third parties.

Notice: Effective January 2013, TDK will use a new catalog number which adds product thickness and packaging specification detail. This new catalog number should be referenced on all catalog orders going forward, and is not applicable for OEM part number orders. Please be aware the last five digits of the catalog number will differ from the item description (internal control number) on the product label. Contact your local TDK Sales representative for more information.

(Example)


Catalog Issued date	Catalog Number	Item Description (On Delivery Label)
Prior to January 2013	C1608C0G1E103J	C1608C0G1E103JT000N
January 2013 and Later	C1608C0G1E103J080AA	C1608C0G1E103JT000N



CGA3EA Series

ESD Protection

Case size: 1608 [EIA CC0603]



Features




- The amount of static electricity that is charged and generated from the human body is generally thousands of volts or more. This series consists of in-vehicle products that protect electronic components from static electricity.
- The series has passed the most rigorous level (level 4-8000V) of ESD tests for contact discharge described under the IEC61000-4-2 international standard.
- Available in both COG (125°C max) and NP0 (150°C max) temperature characteristics, and can be used in applications that require high reliability, even in cars.
- AEC-Q200 compliant.

Applications



- Input-output sections of various in-vehicle applications such as ECUs (run, turn and stop), keyless entry systems, and car navigation systems.

Shape & Dimensions



L	Body Length
W	Body Width
T	Body Height
B	Terminal Width
G	Terminal Spacing



Catalog Number Construction

CGA • 3 • E • A • NP0 • 2A • 103 • J • 080 • A • C

Series Name

Dimensions L x W (mm)

Code	Length	Width	Terminal
3	1.60 ± 0.10	0.80 ± 0.10	0.20 min.

Thickness T Code (mm)

Code	Thickness
E	0.80 mm

Function identification code

Code	Description
A	ESD Protection

Temperature Characteristics

Temperature Characteristics	Temperature Coefficient or Capacitance Change	Temperature Range
COG	0 ± 30 ppm/°C	-55 to +125°C
NP0	0 ± 30 ppm/°C	-55 to +150°C

Rated Voltage (DC)

Code	Voltage (DC)
2A	100V

Nominal Capacitance (pF)

The capacitance is expressed in three digit codes and in units of pico Farads (pF). The first and second digits identify the first and second significant figures of the capacitance. The third digit identifies the multiplier.

Ex. 472 = 4,700pH = 4.7nF ; 103 = 10,000pF = 10nF

Capacitance Tolerance

Code	Tolerance
J	± 5%

Nominal Thickness

Code	Thickness
080	0.80 mm

Packaging Style

Code	Style
A	178 mm Reel, 4 mm Pitch

Special Reserved Code

Code	Description
A, C	TDK Internal Code



Capacitance Range Chart

EIA CC0603 [1608]

Capacitance Range Chart

Temperature Characteristics: COG (0 ± 30ppm/°C)、NP0 (0 ± 30ppm/°C)
 Rated Voltage: 100V(2A)

Capacitance (pF)	Code	Tolerance	COG	NP0	ESD Resistance (V)
			2A (100V)	2A (100V)	
1,000	102	J : ± 5%			8,000
1,500	152				10,000
2,200	222				12,000
3,300	332				16,000
4,700	472				16,000
6,800	682				22,000
10,000	103				30,000

Standard Thickness
 0.80 mm



Capacitance Range Table

Class 1 (Temperature Compensating)

Temperature Characteristics: COG (-55 to +125°C, 0±30 ppm/°C)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	ESD Resistance (V)	Catalog Number
					Rated Voltage Edc: 100V
1nF	1608	0.80 ± 0.10	±5%	8,000	CGA3EAC0G2A102J080AA
1.5nF	1608	0.80 ± 0.10	±5%	10,000	CGA3EAC0G2A152J080AC
2.2nF	1608	0.80 ± 0.10	±5%	12,000	CGA3EAC0G2A222J080AC
3.3nF	1608	0.80 ± 0.10	±5%	16,000	CGA3EAC0G2A332J080AC
4.7nF	1608	0.80 ± 0.10	±5%	16,000	CGA3EAC0G2A472J080AC
6.8nF	1608	0.80 ± 0.10	±5%	22,000	CGA3EAC0G2A682J080AC
10nF	1608	0.80 ± 0.10	±5%	30,000	CGA3EAC0G2A103J080AC

Class 1 (Temperature Compensating)

Temperature Characteristics: NP0 (-55 to +150°C, 0±30 ppm/°C)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	ESD Resistance (V)	Catalog Number
					Rated Voltage Edc: 100V
1nF	1608	0.80 ± 0.10	±5%	8,000	CGA3EANP02A102J080AA
1.5nF	1608	0.80 ± 0.10	±5%	10,000	CGA3EANP02A152J080AC
2.2nF	1608	0.80 ± 0.10	±5%	12,000	CGA3EANP02A222J080AC
3.3nF	1608	0.80 ± 0.10	±5%	16,000	CGA3EANP02A332J080AC
4.7nF	1608	0.80 ± 0.10	±5%	16,000	CGA3EANP02A472J080AC
6.8nF	1608	0.80 ± 0.10	±5%	22,000	CGA3EANP02A682J080AC
10nF	1608	0.80 ± 0.10	±5%	30,000	CGA3EANP02A103J080AC

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multilayer Ceramic Capacitors MLCC - SMD/SMT](#) category:

Click to view products by [TDK](#) manufacturer:

Other Similar products are found below :

[M39014/01-1467](#) [M39014/02-1218V](#) [M39014/02-1225V](#) [M39014/02-1262V](#) [M39014/02-1301](#) [M39014/22-0631](#) [1210J5000102JCT](#)
[1210J2K00102KXT](#) [1210J5000103KXT](#) [1210J5000223KXT](#) [D55342E07B379BR-TR](#) [D55342E07B523DR-T/R](#) [1812J1K00103KXT](#)
[1812J1K00473KXT](#) [1812J2K00680JCT](#) [1812J4K00102MXT](#) [1812J5000102JCT](#) [1812J5000103JCT](#) [1812J5000682JCT](#) [NIN-FB391JTRF](#)
[NIN-FC2R7JTRF](#) [NPIS27H102MTRF](#) [C1206C101J1GAC](#) [C1608C0G1E472JT000N](#) [C2012C0G2A472J](#) [2220J2K00101JCT](#)
[KHC201E225M76N0T00](#) [LRC-LRF1206LF-01R025FTR1K](#) [1812J1K00222JCT](#) [1812J2K00102KXT](#) [1812J2K00222KXT](#)
[1812J2K00472KXT](#) [2-1622820-7-CUT-TAPE](#) [2220J3K00102KXT](#) [2225J2500824KXT](#) [CCR07CG103KM](#) [CGA2B2C0G1H010C](#)
[CGA2B2C0G1H040C](#) [CGA2B2C0G1H050C](#) [CGA2B2C0G1H060D](#) [CGA2B2C0G1H070D](#) [CGA2B2C0G1H151J](#) [CGA2B2C0G1H1R5C](#)
[CGA2B2C0G1H2R2C](#) [CGA2B2C0G1H3R3C](#) [CGA2B2C0G1H680J](#) [CGA2B2C0G1H6R8D](#) [CGA2B2X8R1H221K](#) [CGA2B2X8R1H472K](#)
[CGA3E1X7R1C474K](#)