

# Noise Suppression Sheets

## Flexield

For multipurpose

IFL series

Issue date: December 2013

- All specifications are subject to change without notice.
  - Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.
-

# Noise Suppression Sheets/Magnetic Sheets/ Radio Wave Absorbers Flexield

## FOR NOISE SUPPRESSION IFL MATERIALS

TDK's Flexield is a highly flexible and shock resistant soft magnetic sheet material consisting of magnetic material and resin. It suppresses noise radiated from electronic devices across a wide frequency range. Offering excellent flexibility in fabrication, Flexield is a sheet-type noise reduction solution particularly suited for high-frequency range.



### FEATURES

- They are flexible(not crack).
- They are suited for thin and compact devices.
- Available in a wide range of dimensions and shapes.
- Conforming to RoHS Directive.

### APPLICATIONS

- Noise reduction for flexible cables used in mobile devices (including notebook PC's, digital cameras, game machines, and cellular phones).
- Reduction of noise radiated from a wide variety of electronic devices (including noise from CPU).
- Reduction of specific absorbed radiation (SAR) from cellular phones.
- Reduction of internal EMI (resonance, crosstalk) inside a shielded casing.

### PRODUCT IDENTIFICATIONS

IFL12 - 100 N B 300 × 200  
(1) (2) (3) (4) (5) (6)

- (1) Material name
- (2) Magnetic sheet thickness(100: 100μm)
- (3) Surface film thickness symbol
- (4) Double-sided tape thickness symbol
- (5) Length(300: 300mm)
- (6) Width(200: 200mm)

### SPECIFICATIONS

Type (Features/Application)	Thin type High μ/High characteristic	Thin type High μ/High frequency band
Material name	IFL12	IFL10M
Recommended frequency range	5MHz to 3GHz	10MHz to 3GHz
Operating temperature range (°C)	-40 to +85	-40 to +85
Initial permeability[at 1MHz]typ.	180	120
Resistivity(Ω/square) min.	100K	1M
Thermal conductivity (W/m • K)	1.5	1.5
Standard sheet dimensions (mm)	300×200	300×200
Standard magnetic sheet thickness (mm)	0.05, 0.1, 0.2	0.025, 0.05, 0.1, 0.2
Compatible with rolls	✓	✓
Flame retardant	—	—
Environment	RoHS directive Halogen-free	RoHS directive Halogen-free

- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

- All specifications are subject to change without notice.

## Product Identifications of The Standard Sample

IFL12 -  $\frac{100}{(1)}$   $\frac{N}{(2)}$   $\frac{B}{(3)}$   $\frac{300}{(4)}$   $\times$   $\frac{200}{(5)}$   $\frac{200}{(6)}$

(1) Material name

(2) Magnetic sheet thickness (100: 100 $\mu$ m)

(3) Surface film thickness symbol (N: Correspondence thickness)

(4) Double-sided tape thickness symbol (B: 10 $\mu$ m)

(5) Length(300: 300mm)

(6) Width(200: 200mm)

	IFL10M	IFL12
Correspondence thickness(mm)	0.025, 0.5, 0.1, 0.2	0.05, 0.1, 0.2
Product name of the standard sample	IFL10M-025NB300x200 IFL10M-050NB300x200 IFL10M-100NB300x200 IFL10M-200NB300x200	IFL12-050NB300x200 IFL12-100NB300x200 IFL12-200NB300x200

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [tdk manufacturer:](#)*

Other Similar products are found below :

[VLF5012ST-1R0N2R5](#) [SWS1000L-24/BL](#) [CXA-2115](#) [MCZ1210AH301L2T](#) [78P7200-IH/F](#) [MLP2012S1R5TT](#) [ACH3218-682-TD01](#)  
[ACT45B-KIT](#) [NL565050T-822J-PF](#) [C1005JB1H471K050BA](#) [C1608CH1H151J080AA](#) [C2012JB1H105K125AB](#) [C4532NP01H154J250KA](#)  
[SD1209T5-A1](#) [SLF12565T-152MR37-H](#) [CD75-B2GA331KYGKA](#) [CLF10040T-221M](#) [CLF12555T-220M](#) [R22095\\*REPAIRED](#)  
[MLF1005LR12K](#) [C0603C0G1E330J030BA](#) [VLS252015T-3R3M1R0](#) [VLS4012T-150MR65](#) [ZCAT-KIT](#) [MPZ2012-KIT](#) [NLV32T-R27J-EFD](#)  
[CGA3EANP02A682J080AC](#) [CKCM25C0G2A101K060AK](#) [CLF10040T-4R7N](#) [WTM505090-10K2-5V-G1](#) [VLS252010HBX-R24M-1](#)  
[CGJ2B2X7R1C222K](#) [CGA9M1X7T2J334K](#) [CGA8P3X7T2E105M/SOFT](#) [CGA6J4C0G2J392J](#) [CGA6M3X7R2E154K](#) [CGA3E3C0G2E181J](#)  
[CGA2B2C0G1H331J](#) [C-WPTX01-E6-KIT](#) [CEU-AC01-E6-KIT](#) [CERB3UX5R0G105M](#) [RLF12545T-100M5R1-PF](#) [PFE500F28/T](#)  
[CCT406393-600-36-02](#) [PFC3819QM-181K09B-00](#) [VLF3010AT-100MR49](#) [MMZ0603D330C](#) [MPZ2012S102ATD25](#) [MLG0603P-2-KIT](#)  
[MLG1608B18NJ](#)