


LOCAL AREA NETWORK CABLES**APPLICATIONS**

FTP kat.5e 4x2x0,14c mm² are patch cables, applied in multimedia computer networks (data, sound and HDTV transmission) including structural wiring of buildings, in industrial and other dedicated networks sensitive to electromagnetic interferences.

The overall shield protects the cables against external electromagnetic interferences and prevents emission of interferences produced in the cables.

The cables are also applied in computer networks of increased binary transfer where simultaneous transmission in both directions in all 4 symmetrical circuits is used (full duplex, Gigabit Ethernet technique).

The cables are suitable for fixed indoor installations.

CONSTRUCTION

- flexible, multiwire conductors, stranded of annealed tin-plated copper wires, cross-section 0.14 mm² (7x0.16 mm), 26 AWG,
- polyethylene (PE) insulation coloured: white-blue and blue, white-orange and orange, white-green and green, white-brown and brown,
- insulated conductors twisted into pairs,
- pairs laid-up into a cable core,
- collective shield, incorporating aluminium-polyester tape and stranded of an annealed tinned copper drain wire,
- PVC cable sheath, grey RAL 7035, other colours also available.

AVAILABLE UPON REQUEST

FTP-H kat.5e 4x2x0,14c mm² - halogen free material sheathed cables applied in locations where, in case of fire, higher safety level is required. The cables are flame retardant and their smoke emission is low, emitted fumes are non toxic and non corrosive.

CHARACTERISTICS

Characteristic impedance	100 ± 15 Ω	Minimum shielding attenuation at the frequency f=30 ÷ 1000 MHz - min.	50 dB
Mutual capacitance of any pair at 1 kHz, approximate	50 nF/km	Shielding impedance at 10 MHz, maximum	100 mΩ/m
Capacitance unbalance of any pair to ground at 1 kHz, max.	1600 pF/km	DC loop resistance at 20°C, maximum	290 Ω/km
Insulation resistance, minimum	5000 MΩ·km	Resistance unbalance of any pair of conductors, max.	2 %
Operating voltage	150 V	Operating temperature range during operation	from - 20 to + 70°C
Voltage test	700 V rms	Operating temperature range during installation	from 0 to + 50°C
Velocity of propagation	65 %	Minimum bending radius	4 x cable diameter
Return loss, minimum at f=4÷10 MHz	25+5lg(f) dB	Cable combustibility	flame retardant
Return loss, minimum at f=10÷20 MHz	25 dB	Combustibility tests	PN-EN 60332-1-2, IEC 60332-1-2
Return loss, minimum at f=20÷125 MHz	25-8.6lg(f/20) dB	Reference standards	PN-EN 50288-2-2, IEC 61156-6 ISO/IEC 11801, TIA/EIA 568 A

Attenuation loss, maximum

f	[MHz]	1	4	10	16	20	31.25	62.5	100	125
A	[dB/100 m]	3.2	6.0	9.5	12.1	13.5	17.1	24.8	32	34.0

Near end cross-talk between pairs, minimum

f	[MHz]	1	4	8	10	16	20	25	31.25	62.5	100	125
NEXT	[dB]	65.0	56.0	50	50.3	47	46	44.3	43	38	35	34
PSNEXT	[dB]	62.3	53.3	48.8	47.3	44.3	42.8	41.3	39.9	35.4	32.3	29.5
ACR	[dB]	68.3	57.2	51.0	48.8	44.0	41.5	38.9	36.2	26.4	18.3	4.4

Far end cross-talk between pairs, minimum

f	[MHz]	1	4	8	10	16	20	25	31.25	62.5	100	155
ELFEXT	[dB]	63.8	51.7	45.7	43.8	39.7	37.7	35.8	33.9	27.8	23.8	19.9
PSELFEXT	[dB]	60.8	48.7	42.7	40.8	36.7	34.7	32.8	30.9	24.8	20.8	16.9

CE = the cable meets requirements of the low voltage directive 2014/35/EU

Product No.	Cable type	Number of pairs (x 2) x conductor cross-section	Cable outer diameter (appr.)	Copper index	Cable weight (appr.)
		mm ²	mm	kg/km	kg/km
0013 010	FTP kat.5e	4 x 2 x 0,14c	5.0	12.1	27.5

Product No.	Cable type	Number of pairs (x 2) x conductor cross-section	Cable outer diameter (appr.)	Copper index	Cable weight (appr.)
		mm ²	mm	kg/km	kg/km
0503 004	FTP-H kat.5e	4 x 2 x 0,14c	5.3	12.1	33.3

TECHNOKABEL S.A. reserves the right to change specifications without prior notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ethernet Cables / Networking Cables](#) category:

Click to view products by [Technokabel](#) manufacturer:

Other Similar products are found below :

[MCJB2-10P6Q7-120](#) [84909-0204](#) [1200700174](#) [1200860368](#) [1410147](#) [E16A06002M030](#) [E200102-009-S1](#) [AX105346-EW](#) [MT14-187L](#)
[MWDM2L-51GS-6J1-2.82B](#) [ERWPAB3002M005](#) [190-038045-01](#) [NK5EPC1GRY](#) [NK5EPC4Y](#) [1969343-6](#) [ICD056GVP163D-C0](#)
[C5UMB3FBG](#) [2142758-2](#) [2168427-2](#) [21949-1](#) [2J1866A](#) [RJF SFTP 5E 0500](#) [AX100351](#) [UTPCH14GYY](#) [45-5684](#) [09459711142](#) [100345-](#)
[1301](#) [MWDM2L-25P-8K1-.500B](#) [MWDM6L-31S-6C4-.375H](#) [73-7793-1](#) [74764-1101](#) [WHU18-3636-048](#) [RJF2SA2G05100BTX](#)
[1R4000A39M030](#) [190-038045-00-SP328](#) [UTPSP6GYY](#) [UTPSP2GYY](#) [UTPSP10GYY](#) [UTPCH5GYY](#) [UTP28SP15M](#) [UTP28CH100OR](#)
[ENSP2F5C305](#) [74764-2301](#) [SAC-5P-MS/ 1.0-920/FS SCO AR](#) [1-3636-601-5211](#) [1-3636-600-5212](#) [1-3636-461-5208](#) [1-3637-600-5212](#) [1-](#)
[3637-600-5206](#) [1-3636-618-5212](#)