



### Features

- Low on-resistance
- High-speed switching
- Drive circuits can be simple
- Parallel use is easy

### Typical Applications


- Switching application

### Shipping Quantity

- 3000pcs / Tape & Reel



### Circuit Diagram



### Absolute Maximum Ratings (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	$V_{DSS}$	100	V
Gate-to-Source Voltage	$V_{GSS}$	±20	V
Continuous Drain Current	$I_D$	170	mA
Pulsed Drain Current *3	$I_{DM}$	680	mA



**Thermal Characteristics**

Parameter		Symbol	Value	Unit
Power Dissipation	SOT-23	$P_D$	0.35	W
Thermal Resistance Junction-to-Air	SOT-23	$R_{\theta JA}$	357	$^{\circ}C/W$
Operating Junction Temperature Range		$T_J$	-55 to +150	$^{\circ}C$
Storage Temperature Range		$T_{STG}$	-55 to +150	$^{\circ}C$







**Electrical Characteristics** ( $T_A=25^{\circ}C$  unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
<b>Static Characteristics</b>						
$V_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu A$	100	-	-	V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS} = 100V, V_{GS} = 0V$	-	-	1	$\mu A$
		$V_{DS} = 20V, V_{GS} = 0V$	-	-	10	nA
$I_{GSS}$	Gate-Body Leakage Current	$V_{GS} = \pm 20V, V_{DS} = 0V$	-	-	$\pm 1$	$\mu A$
<b>On Characteristics</b>						
$R_{DS(ON)}$	Static Drain-Source On-resistance *1	$V_{GS} = 10V, I_D = 0.17A$	-	3.0	6	$\Omega$
		$V_{GS} = 4.5V, I_D = 0.17A$	-	3.5	10	
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu A$	1	1.9	2.8	V
<b>Dynamic Characteristics</b>						
$C_{iss}$	Input Capacitance	$V_{GS} = 0V$	-	43	-	pF
$C_{oss}$	Output Capacitance	$V_{DS} = 20V$	-	15	-	
$C_{rss}$	Reverse Transfer Capacitance	$f = 1.0MHz$	-	2.8	-	
<b>Switching Characteristics</b> *2						
$t_{d(on)}$	Turn-on Delay Time	$V_{DD} = 30V, I_D = 0.28A$ $V_{GS} = 10V, R_G = 50\Omega$	-	-	8	ns
$t_r$	Turn-on Rise Time		-	-	8	
$t_{d(off)}$	Turn-Off Delay Time		-	-	13	
$t_f$	Turn-Off Fall Time		-	-	16	
<b>Source-Drain Diode Characteristics</b>						
$V_{SD}$	Diode Forward Voltage *1	$I_S = 0.3A, V_{GS} = 0V$	-	0.85	1.3	V






Typical Performance Characteristics (T<sub>A</sub>=25°C unless otherwise Specified)






**Outline Drawing - SOT23**



SOT-23		
Dimension	Min.	Max.
A	2.70	3.10
B	1.10	1.50
C	0.90	1.10
D	0.30	0.50
E	0.35	0.48
G	1.80	2.00
H	0.02	0.10
J	0.05	0.15
K	2.20	2.60

**Land Pattern - SOT23**



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [TECH PUBLIC](#) manufacturer:*

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [2SK2267\(Q\)](#) [BUK455-60A/B](#) [TK100A10N1,S4X\(S](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#)  
[IRS2092STRPBF-EL](#) [IPS70R2K0CEAKMA1](#) [TK31J60W5,S1VQ\(O](#) [TK31J60W,S1VQ\(O](#) [TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#)  
[DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [DMC2700UDMQ-7](#) [DMN2080UCB4-7](#)  
[DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)  
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [IPS60R360PFD7SAKMA1](#)  
[DMN2990UFB-7B](#) [SSM3K35CT,L3F](#) [IPLK60R1K0PFD7ATMA1](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [IPWS65R035CFD7AXKSA1](#)  
[MCQ7328-TP](#) [SSM3J143TU,LXHF](#) [DMN12M3UCA6-7](#) [PJMF280N65E1\\_T0\\_00201](#) [PJMF380N65E1\\_T0\\_00201](#)  
[PJMF280N60E1\\_T0\\_00201](#) [PJMF600N65E1\\_T0\\_00201](#) [PJMF900N65E1\\_T0\\_00201](#)