

**Product Summary**

- $V_{DS}$  -50V
- $I_D$  -0.13A
- $R_{DS(ON)}$ ( at  $V_{GS}=-10V$ ) <5 mohm
- $R_{DS(ON)}$ ( at  $V_{GS}=-4.5V$ ) <6 mohm

**Application**


- Battery protection
- Load switch
- Power management

**Package and Pin Configuration**

SOT-23



**Circuit diagram**



**Absolute Maximum Ratings ( $T_A=25^{\circ}C$  unless otherwise noted)**


Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	-50	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current	$I_D$	-0.13	A
Pulsed Drain Current (note 1) @ $t_p < 10 \mu s$	$I_{DM}$	-0.52	A
Power Dissipation	$P_D$	225	mW
Thermal Resistance from Junction to Ambient (note 2)	$R_{\theta JA}$	556	$^{\circ}C/W$
Junction Temperature	$T_J$	150	$^{\circ}C$
Storage Temperature	$T_{STG}$	-55~+150	$^{\circ}C$
Maximum Lead Temperature for Soldering Purposes , Duration for 5 Seconds	$T_L$	260	$^{\circ}C$

**Electrical Characteristics (T<sub>J</sub>=25 °C, unless otherwise noted)**


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>STATIC CHARACTERISTICS</b>						
Drain-source breakdown voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> = -250μA	-50			V
Zero gate voltage drain current	I <sub>DSS</sub>	V <sub>DS</sub> = -50V, V <sub>GS</sub> = 0V			-15	μA
		V <sub>DS</sub> = -25V, V <sub>GS</sub> = 0V			-0.1	μA
Gate-body leakage current	I <sub>GSS</sub>	V <sub>GS</sub> = ±20V, V <sub>DS</sub> = 0V			±5	μA
Gate threshold voltage (note 3)	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = -250μA	-0.9	-1.6	-2	V
Drain-source on-resistance (note 3)	R <sub>DS(on)</sub>	V <sub>GS</sub> = -5V, I <sub>D</sub> = -0.1A		4	5	Ω
		V <sub>GS</sub> = -10V, I <sub>D</sub> = -0.1A		4.5	6	Ω
Forward transconductance (note 1)	g <sub>FS</sub>	V <sub>DS</sub> = -25V; I <sub>D</sub> = -100mA	50			mS
<b>DYNAMIC CHARACTERISTICS (note 4)</b>						
Input capacitance	C <sub>iss</sub>	V <sub>DS</sub> = 5V, V <sub>GS</sub> = 0V, f = 1MHz		30		pF
Output capacitance	C <sub>oss</sub>			10		pF
Reverse transfer capacitance	C <sub>rss</sub>			5		pF
<b>SWITCHING CHARACTERISTICS (note 4)</b>						
Turn-on delay time	t <sub>d(on)</sub>	V <sub>DD</sub> = -15V, R <sub>L</sub> = 50Ω, I <sub>D</sub> = -2.5A		2.5		ns
Turn-on rise time	t <sub>r</sub>			1		ns
Turn-off delay time	t <sub>d(off)</sub>			16		ns
Turn-off fall time	t <sub>f</sub>			8		ns
<b>SOURCE-DRAIN DIODE CHARACTERISTICS</b>						
Continuous Current	I <sub>S</sub>				-0.13	A
Pulsed Current	I <sub>SM</sub>				-0.52	A
Diode forward voltage (note 3)	V <sub>SD</sub>	I <sub>S</sub> = -0.13A, V <sub>GS</sub> = 0V			-2.2	V




Typical Electrical and Thermal Characteristics




VDS, Drain-Source Voltage (V)  
Fig1. Typical Output Characteristics




VGS(TH), Gate-Source Voltage (V)  
Fig2. Typical Transfer Characteristics




ID, Drain-Source Current (mA)  
Fig3. Drain-Source on Resistance



Tj - Junction Temperature (°C)  
Fig4. Normalized On-Resistance Vs. Temperature




Tj - Junction Temperature (°C)  
Fig5. Gate Threshold vs. Junction Temperature



VDS, Drain-Source Voltage (V)  
Fig6. Typical Capacitance Vs. Drain-Source Voltage



SOT-23 Package Information



Symbol	Dimensions in Millimeters	
	MIN.	MAX.
A	0.900	1.150
A1	0.000	0.100
A2	0.900	1.050
b	0.300	0.500
c	0.080	0.150
D	2.800	3.000
E	1.200	1.400
E1	2.250	2.550
e	0.950TYP	
e1	1.800	2.000
L	0.550REF	
L1	0.300	0.500
$\theta$	0°	8°

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [TECH PUBLIC](#) manufacturer:*

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [2SK2267\(Q\)](#) [BUK455-60A/B](#) [TK100A10N1,S4X\(S](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#)  
[IRS2092STRPBF-EL](#) [IPS70R2K0CEAKMA1](#) [TK31J60W5,S1VQ\(O](#) [TK31J60W,S1VQ\(O](#) [TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#)  
[DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [P85W28HP2F-7071](#) [NTE2384](#) [DMC2700UDMQ-7](#) [DMN2080UCB4-7](#) [DMN61D9UWQ-13](#)  
[US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#)  
[IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [IPS60R360PFD7SAKMA1](#)  
[DMN2990UFB-7B](#) [SSM3K35CT,L3F](#) [IPLK60R1K0PFD7ATMA1](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [IPWS65R035CFD7AXKSA1](#)  
[MCQ7328-TP](#) [SSM3J143TU,LXHF](#) [DMN12M3UCA6-7](#) [PJMF280N65E1\\_T0\\_00201](#) [PJMF380N65E1\\_T0\\_00201](#)  
[PJMF280N60E1\\_T0\\_00201](#) [PJMF600N65E1\\_T0\\_00201](#) [PJMF900N65E1\\_T0\\_00201](#) [PJMF900N60E1\\_T0\\_00201](#)