


### RB521C30 Schottky barrier diode



#### Absolute Maximum Ratings (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Limits	Unit
Reverse voltage(DC)	V <sub>R</sub>	30	V
Average rectified forward current	lo	200	mA
Peak forward surge current	I <sub>FSM</sub>	500	mA
Junction temperature	Ti	125	°C
Storage Temperature Range	T <sub>STG</sub>	-40~+125	°C


#### Electrical Characteristics (TA=25°C unless otherwise specified)


Parameter	Symbol	Min.	Max.	Unit	Conditions
Family and solve	- 0.35 V I⊧=10mA	I <sub>F</sub> =10mA			
Forward voltage	VF	-	0.4	V	I <sub>F</sub> =20mA
Reverse current	IR	-	10	μΑ	V <sub>R</sub> =10V



#### www.sot23.com.tw

# Outline Drawing - SOD923





SYMBOL	Dimensions In Millimet			
	MIN	МАХ		
А	0.74	0.86		
В	0.54	0.66		
с	0.35	0.45		
D	0.14	0.26		
к	0.04	0.16		
S	0.95	1.10		

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Schottky Diodes & Rectifiers category:

Click to view products by TECH PUBLIC manufacturer:

Other Similar products are found below :

MA4E2039 MA4E2508M-1112 MBR10100CT-BP MBR1545CT MMBD301M3T5G GS1JE-TP RB160M-50TR BAS 3010S-02LRH E6327 BAT 54-02LRH E6327 NSR05F40QNXT5G NSVR05F40NXT5G NTE555 JANS1N6640 SB07-03C-TB-H SBS818-TL-E SK310-T SK33A-TP SK34B-TP SS3003CH-TL-E PDS3100Q-7 GA01SHT18 CRS10I30A(TE85L,QM MA4E2501L-1290 MBRB30H30CT-1G DMJ3940-000 SB007-03C-TB-E SK32A-TP SK33B-TP SK35A-TP SK38B-LTP SK38B-TP NRVBM120LT1G NTE505 NTSB30U100CT-1G SS0503SH-TL-E VS-6CWQ10FNHM3 CRG04(T5L,TEMQ) ACDBA1100LR-HF ACDBA1200-HF ACDBA2100-HF ACDBA240-HF ACDBA3100-HF CDBQC0530L-HF ACDBA260LR-HF ACDBA1100-HF MA4E2502L-1246 10BQ060-M3/5BT NRVB130LSFT1G CRS08TE85LQM PMAD1108-LF