


Product Summary

- 60V/ 5A
 $R_{DS(ON)} = 25m\Omega (Typ) @ V_{GS} = -10V$
 $R_{DS(ON)} = 30m\Omega (Typ) @ V_{GS} = -4.5V$
- Reliable and Rugged
- Lead Free and Green Devices Available (RoHS Compliant)


Application

- DC-DC Converters.
- Load Switch.
- Power Management.

Package and Pin Configuration



Circuit diagram



Marking:



Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise noted)


Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current	I_D	5	A
Pulsed Drain Current (note 1)	I_{DM}	30	A
Power Dissipation	P_D	1.7	A
Thermal Resistance from Junction to Ambient (note 2)	$R_{\theta JA}$	106	$^\circ\text{C/W}$
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55~+150	$^\circ\text{C}$

Electrical Characteristics (T_A=25°C unless otherwise noted)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _D =250μA	60			V
Gate-Threshold Voltage ^(Note3)	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	1.0		3.0	V
Gate-Body Leakage Current	I _{GSS}	V _{GS} =± 20V, V _{DS} =0V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =60V, V _{GS} =0V			1	μA
Drain-Source On-Resistance ^(Note3)	R _{DS(on)}	V _{GS} =10V, I _D =3A		25	29	mΩ
		V _{GS} =4.5V, I _D =3A		30	35	
Forward Transconductance ^(Note3)	g _{fs}	V _{DS} =5V, I _D =4.5A	11			S
Dynamic Characteristics^(Note4)						
Input Capacitance	C _{iss}	V _{DS} =30V, V _{GS} =0V, f=1MHz		500		pF
Output Capacitance	C _{oss}		60			
Reverse Transfer Capacitance	C _{rss}		25			
Switching Characteristics^(Note4)						
Total Gate Charge	Q _g	V _{DS} =48V, V _{GS} =10V, I _D =15A		12		nC
Gate-Source Charge	Q _{gs}		4.1			
Gate-Drain Charge	Q _{gd}		4.5			
Turn-on Delay Time	t _{d(on)}	V _{DD} =30V, V _{GS} =10V, I _D =2A, R _G =3Ω, R _L =6.7Ω		5.0		ns
Turn-on Rise Time	t _r		2.6			
Turn-off Delay Time	t _{d(off)}		16.1			
Turn-off Fall Time	t _f		2.3			
Drain-Source Diode Characteristics						
Diode Forward Voltage ^(Note3)	V _{SD}	V _{GS} =0V, I _S =20A			1.2	V
Diode Forward Current ^(Note2)	I _S				20	A
Reverse Recovery Time	t _{rr}	I _F =20A, di/dt=100A/μs ^(Note4)		35		nS
Reverse Recovery Charge	Q _{rr}				53	
Forward Turn-On Time	t _{on}	Intrinsic turn-on time is negligible (turn-on is dominated by LS+LD)				



SOT23-6 Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
theta	0°	8°	0°	8°

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF MOSFET Transistors](#) category:

Click to view products by [TECH PUBLIC](#) manufacturer:

Other Similar products are found below :

[FH2164](#) [BLF245](#) [ARF465BG](#) [BF 2030](#) [E6814](#) [BLF861A](#) [MRF6S20010GNR1](#) [DU28200M](#) [MMRF1015NR1](#) [UF28100M](#) [MW6S010GNR1](#)
[DU2820S](#) [MRF24301HR5](#) [MMRF1014NT1](#) [MRF422](#) [ARF468BG](#) [MAPHST0045](#) [A2T27S020NR1](#) [DU2860U](#) [MHT1803A](#) [VRF152GMP](#)
[MRFE6VP5300NR1](#) [BF2040E6814HTSA1](#) [MRFE6VP5150NR1](#) [MMRF5014HR5](#) [LET9060S](#) [MRF136Y](#) [MRF175GV](#) [AFT27S010NT1](#)
[AFT27S006NT1](#) [MRF1K50NR5](#) [BG 3130](#) [H6327](#) [MRFE6VP5300NR1](#) [MRFE6VP5600HR6](#) [MRFX1K80HR5](#) [BF998E6327HTSA1](#)
[AFM907NT1](#) [AFT05MS006NT1](#) [AFV10700HR5](#) [MRF141](#) [MRF492](#) [MRF141](#) [MRF171](#) [MRF172](#) [MRF174](#) [AFM906NT1](#) [BLF578XR,112](#)
[TPM9305PD6](#) [CJU02N65](#) [FDS9926A](#) [AFT05MS031NR1](#)