



Trace Tech Flux Remover Pen

2506

TraceTech board repair system allows any level of technician to quickly perform quality board repairs in-house without the use of expensive equipment or time-consuming and unsightly jumpers. Meets IPC board repair standards. Other TraceTech pens are available to allow quick, convenient, and high quality board repair and rework.



Spot cleaning for PCB rework and repair

Provides convenient touchup cleaning of flux residues. Cleans R, RMA, SA, and no-clean fluxes.

- Cleans R, RMA, SA, and no-clean fluxes
- Safe on plastics
- Non-ozone depleting
- Rapid evaporation
- Pen tip allows controlled application



Product Packaging

2506-N
Trace Tech Flux Remover Pen
11.5 ml
12 units/case



Chemical & Physical Properties	
Appearance	Clear, colorless liquid
Odor	Alcohol odor
Flash Point	-15°F
VOC (EPA)	
VOC (CARB)	
Boiling Point	80°C (176°F)
Density	

Chemical Composition

CHEMICAL NAME	CAS #
2-Propanol	67-63-0
Hexane	110-54-3





Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Techspray
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe

ITW Contamination Control BV
Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+31 88 1307 400
email: info@itw-cc.com

Countries Outside US

Call to locate a distributor in your country

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Soldering Flux](#) category:

Click to view products by [Techspray](#) manufacturer:

Other Similar products are found below :

[8351-1L](#) [8351-125ML](#) [051-0001](#) [051-0002](#) [051-0003](#) [051-0004](#) [051-0007](#) [051-0008](#) [051-0009](#) [051-0010](#) [053-1000](#) [053-1001](#) [053-1002](#)
[053-1003](#) [8342-50G](#) [ART.AGT-088](#) [270WR](#) [ART.AGT-089](#) [ART.AGT-094](#) [ART.AGT-179](#) [CW8100](#) [CW8400](#) [63-0000-0186](#) [63-0000-0951](#) [63-0000-0977](#) [63-0000-1544](#) [83-1000-0186](#) [83-1000-0951](#) [83-1097-2331](#) [8341-10ML](#) [835-100ML](#) [SF-01](#) [SF-02](#) [CW8700](#) [FL22W](#)
[SMD291SNL50T3](#) [SMD291AX50T3](#) [SMD291/30CC](#) [CQ2LF](#) [CQ4LF](#) [CW8500](#) [CQ4LF-0.5](#) [CQ4LF-1.0](#) [SMD291](#) [SMD291150G](#)
[SMD29175G](#) [SMD291AX](#) [SMD291AX10](#) [SMD291AX250T3](#) [SMD291NL](#)