

BACKPLANE CONNECTOR HOUSINGS



✓ Active



TE CONNECTIVITY (TE) Z-PACK/L F-HSG 6P. Z-PACK | Z-PACK 2mm HM

100746-1 TE Internal Number: 100746-1

Always EU RoHS/ELV Compliant

Centerline (mm) $\, {\bf 2}$

Mating Alignment With Mating Alignment Type Multi-Purpose Center Number of Positions 6

Number of Rows 1

Product Drawings	Z-Pack 2mm Hm Type L Female Conn. Housing		
	English		
	Z-Pack 2mm Hm Type L Female Conn. Housing PDF (TIFF AVAILABLE) English		
CAD Files	Customer View Model TIF English		
	3D PDF PDF English		
	Customer View Model 3D_IGS.ZIP English		
	Customer View Model 3D_STP.ZIP English		
	Customer View Model 2D_DXF.ZIP English		
Product Specifications			
Product Specification	1.5D/2.5D TYPE C COAX CONNECTOR PDF English		
	1.5D/2.5D TYPE C COAX CONNECTOR TIF English		

Product Environmental Compliance

TE Material Declaration

MD_100746-1_10232013516_dmtec PDF English

У 🖬 f v

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	Receptacle	
	Shielded	No	
	Connector Type	Housing	
	Shrouded	No	
	Product Type	Connector	
	Applies To	Printed Circuit Board	
Configuration Features	Number of Positions	6	
	Number of Rows	1	
	Number of DIN Cavities	6	
Electrical Characteristics	Operating Voltage (VAC)	275	
Signal Characteristics	Crosstalk Version	Standard	
Body Features	Color	Gray	
Contact Features	Contact Base Material	Phosphor Bronze	
	Contact Configuration	DIN, Fiber Optic	
	Contact Transmits (Typical)	Signal (Data)	
	CompactPCI	No	
	Contact Mating Area Plating Material	Performance Based	
	Contact Type	Socket	
Termination Features	Interface Type	2mm HM	
Mechanical Attachment	Mating Alignment	With	
	Mating Alignment Type	Multi-Purpose Center	
	Mating Retention	With	
	Mating Retention PCB Mount Retention	With Without	

Housing Features	Centerline (mm)	2
	Housing Material	Polyester - GF
	Housing Color Gray	
Dimensions	Module Length	49.9 mm [1.966 in]
	Length (mm)	49.9
	Height (mm)	11.4
Usage Conditions	Operating Temperature Range (°C)	-55 – 125
Operation/Application	For Use With	4.8 Diameter High Current High Frequency or Fiber Optic Contacts per DIN 41626
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Tube
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

PCB FERRULES & SHIELDS	BACKPLANE GUIDE HARDWARE	HEADER & RECEPTACLE GUIDE HARDWARE	RIBBON CABLE CONNECTORS
Z-PACK SHLD.LOWER A 338108-2	2MM HM REC PWR/GRD MODULE 646273-1	HDI POWER CONTACT ASSY 533065-6	A/L LOW PRO HDR 24P VERT HT 5104338-5
Save to List	Save to List	Save to List	Save to List Find Similar Products
•			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hard Metric Connectors category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

6345127-1 646916-9 6469658-1 973108 1-2000713-0 1-2000713-2 1-2000713-3 1645343-1 1645456-1 1645594-1 1645595-1 1645595-1 1645601-1 1934822-1 278071110010833 1645179-1 1645245-1 1645457-1 1645525-1 1645570-1 1645596-1 17041102202 1857470-1 1934275-1 1934289-1 1934759-1 2000673-1 2170292-2 2-536642-6 3-106015-1 352188-1 352629-1 5120823-1 5120899-1 3-100145-0 3-100147-0 3-100669-1 3-106081-0 HM2DK2368PLF 5646530-1 3-352049-0 3-352069-0 3-352115-0 3-352638-0 352189-1 3-646357-0 3-646487-0 3-646513-0 104108 106726-1 114352