



- 1 ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- 2 TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADERS ARE HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- 3 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



	3.984	3.900	39	40	4-103185-0
5	3.884	3.800	38	39	3-103185-9
	3.784	3.700	37	38	3-103185-8
OBSOLETE	3.684	3.600	36	37	3-103185-7
	3.584	3.500	35	36	3-103185-6
5	3.484	3.400	34	35	3-103185-5
	3.384	3.300	33	34	3-103185-4
OBSOLETE	3.284	3.200	32	33	3-103185-3
	3.184	3.100	31	32	3-103185-2
5	3.084	3.000	30	31	3-103185-1
	2.984	2.900	29	30	3-103185-0
OBSOLETE	2.884	2.800	28	29	2-103185-9
	2.784	2.700	27	28	2-103185-8
5	2.684	2.600	26	27	2-103185-7
	2.584	2.500	25	26	2-103185-6
OBSOLETE	2.484	2.400	24	25	2-103185-5
	2.384	2.300	23	24	2-103185-4
5	2.284	2.200	22	23	2-103185-3
	2.184	2.100	21	22	2-103185-2
OBSOLETE	2.084	2.000	20	21	2-103185-1
	1.984	1.900	19	20	2-103185-0
5	1.884	1.800	18	19	1-103185-9
	1.784	1.700	17	18	1-103185-8
OBSOLETE	1.684	1.600	16	17	1-103185-7
	1.584	1.500	15	16	1-103185-6
5	1.484	1.400	14	15	1-103185-5
	1.384	1.300	13	14	1-103185-4
OBSOLETE	1.284	1.200	12	13	1-103185-3
	1.184	1.100	11	12	1-103185-2
5	1.084	1.000	10	11	1-103185-1
	.984	.900	9	10	1-103185-0
SUPERCEDED BY 6-146280-5	.884	.800	8	9	103185-9
	.784	.700	7	8	103185-8
5	.684	.600	6	7	103185-7
	.584	.500	5	6	103185-6
OBSOLETE	.484	.400	4	5	103185-5
	.384	.300	3	4	103185-4
5	.284	.200	2	3	103185-3
	.184	.100	1	2	103185-2
SUPERCEDED BY 6-146280-0	.084	—	—	1	103185-1
	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN H MOLL 13OCT87	STE TE Connectivity	
DIMENSIONS: INCHES		CHK T. CLARK 20OCT87		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD T. CLARK 20OCT87	NAME	
0 PLC ± -		PRODUCT SPEC	HEADER ASSY, MOD II, BREAKAWAY, SINGLE ROW, .100CL, VERTICAL, WITH .025 SQUARE POSTS	
1 PLC ± -		APPLICATION SPEC	SIZE	
2 PLC ± -		WEIGHT	CAGE CODE DRAWING NO	
3 PLC ± .005		—	A1 00779 103185	
4 PLC ± -		—	RESTRICTED TO	
ANGLES ± -		CUSTOMER DRAWING		
MATERIAL: HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR-BLACK; POSTS: COPPER ALLOY		FINISH: POSTS: .00015 GOLD ON CONTACT AREA; .00100-.00200 MATTE TIN-LEAD ON SOLDER TAIL; ALL OVER .00050 NICKEL		SCALE 4:1
		SHEET 1 OF 1		REV H

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)