


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		J2		REVISED PER ECO-11-004917	11MAR11	RK	HMR



CONTACT IDENTIFICATION LETTER "C" (LOCATED IN THIS AREA)

HOUSING (SEE TABLE FOR PART NO.)

POSITION #1 INDICATOR

OBSOLETE	2	2.59	1.295	1-103653-1	12	6-103948-1
OBSOLETE	2	2.39	1.195	1-103653-0	11	6-103948-0
OBSOLETE	2	2.19	1.095	103653-9	10	5-103948-9
OBSOLETE	2	1.99	.995	103653-8	9	5-103948-8
OBSOLETE	2	1.79	.895	103653-7	8	5-103948-7
OBSOLETE	3	2.39	.795	103653-6	7	5-103948-6
	2	1.39	.695	103653-5	6	5-103948-5
	4	2.38	.595	103653-4	5	5-103948-4
	4	1.98	.495	103653-3	4	5-103948-3
	5	1.98	.395	103653-2	3	5-103948-2
	8	2.36	.295	103653-1	2	5-103948-1
OBSOLETE	2	2.59	1.295	1-103653-1	12	1-103948-1
OBSOLETE	2	2.39	1.195	1-103653-0	11	1-103948-0
	2	2.19	1.095	103653-9	10	103948-9
	2	1.99	.995	103653-8	9	103948-8
	2	1.79	.895	103653-7	8	103948-7
	3	2.39	.795	103653-6	7	103948-6
	2	1.39	.695	103653-5	6	103948-5
	4	2.38	.595	103653-4	5	103948-4
	4	1.98	.495	103653-3	4	103948-3
	5	1.98	.395	103653-2	3	103948-2
	8	2.36	.295	103653-1	2	103948-1
PLATING	6	B	A	HOUSING PART NUMBER	NO OF POSN	ASSEMBLY PART NUMBER ON STRIP

- 1 CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- 2 USE WITH #26-#30 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- 3 THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5. FOR INDIVIDUAL ASSEMBLIES SEE PART NUMBER 103658
- 6 ASSEMBLIES ARE JOINED BY THE CARRIER STRIP. ORDER QUANTITY REFLECTS TOTAL NUMBER OF INDIVIDUAL ASSEMBLIES REQUIRED. SEE TABLE FOR NUMBER OF ASSEMBLIES PER STRIP.
- 7 MATERIAL- HOUSING: FLAME RETARDANT THERMOPLASTIC, COLOR: BLACK PINS: PHOS. BRONZE
- 8 FINISH- PINS: .000015 GOLD IN THE CONTACT AREA, .000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA, OVER .000050 NICKEL.
- 9 FINISH- PINS: .000015 GOLD IN THE CONTACT AREA, .000050-.000100 MATTE TIN ON THE TERMINATION AREA, OVER .000050 NICKEL.
- 10 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	R BROWN	26JUL00
CHK	K WRIGHT	26JUL00
APVD	K WRIGHT	26JUL00

TE Connectivity

SHROUDED PIN ASSY, AMPMDO MTE, SINGLE ROW, .100 CL, POLARIZED, W/ LATCH WINDOWS, FOR #26-#30 AWG WIRE SIZE, STRIP FORM

108-25034
114-25026

SIZE: A2 CAGE CODE: 00779 DRAWING NO: C=103948

SCALE: 4:1 SHEET: 1 of 1 REV: J2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [79531-3000](#) [FCN-](#)
[360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[801-93-011-10-001000](#)