


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
© COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		J		EC 0G3C 0771 04	29DEC04	BSV	JLG
		J1		REVISED PER ECO-09-021826	01SEP09	KK	AEQ



CONTACT IDENTIFICATION LETTER "D" (LOCATED IN THIS AREA)

HOUSING (SEE TABLE FOR PART NO)

POSITION #1 INDICATOR (FARSIDE)

- 1 CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- 2 USE WITH #22-#26 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- 3 THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 FOR INDIVIDUAL ASSEMBLIES SEE PART NUMBER 103655
- 6 ASSEMBLIES ARE JOINED BY THE CARRIER STRIP. ORDER QUANTITY REFLECTS TOTAL NUMBER OF INDIVIDUAL ASSEMBLIES REQUIRED. SEE TABLE FOR NUMBER OF ASSEMBLIES PER STRIP.
- 7 PINS:.000015 GOLD IN THE CONTACT AREA, .000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA, ALL OVER .000050 NICKEL
- 8 PINS:.000015 GOLD IN THE CONTACT AREA, .000050-.000100 MATTE TIN ON THE TERMINATION AREA, ALL OVER .000050 NICKEL
- 9 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OBSOLETE	8	2	2.40	1.198	1-104503-1	12	6-103951-1
		2	2.20	1.098	1-104503-0	11	6-103951-0
2	2.00	.998	104503-9	10	5-103951-9		
2	1.80	.898	104503-8	9	5-103951-8		
2	1.60	.798	104503-7	8	5-103951-7		
2	1.40	.698	104503-6	7	5-103951-6		
4	2.39	.598	104503-5	6	5-103951-5		
4	1.99	.498	104503-4	5	5-103951-4		
5	1.99	.398	104503-3	4	5-103951-3		
5	1.49	.298	104503-2	3	5-103951-2		
10	1.98	.198	104503-1	2	5-103951-1		
OBSOLETE	9	2	2.40	1.198	1-104503-1	12	4-103951-1
		2	2.20	1.098	1-104503-0	11	4-103951-0
		2	2.00	.998	104503-9	10	4-103951-9
		2	1.80	.898	104503-8	9	4-103951-8
		2	1.60	.798	104503-7	8	4-103951-7
		2	1.40	.698	104503-6	7	4-103951-6
		4	2.39	.598	104503-5	6	4-103951-5
		4	1.99	.498	104503-4	5	103951-4
		5	1.99	.398	104503-3	4	103951-3
		5	1.49	.298	104503-2	3	103951-2
		10	1.98	.198	104503-1	2	103951-1
	PLATING	6	B	A	HOUSING PART NUMBER	NO OF POSN PER ASSY	ASSEMBLY PART NUMBER ON STRIP

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN: L. MAYER 11-5-86  
CHK: P.C.deYONG 11-12-86  
APVD: P.C.deYONG 11-12-86

Tyco Electronics Corporation  
Harrisburg, Pa 17105-3608

NAME: PIN ASSEMBLY, AMPMODU MTE, SINGLE ROW, .100, WITH GUIDE RIBS, FOR #22-#26 AWG WIRE SIZE, STRIP FORM

PRODUCT SPEC: 108-25034  
APPLICATION SPEC: 114-25026

SIZE: A2 CAGE CODE: 00779 DRAWING NO: 103951 RESTRICTED TO: -

MATERIALS: FLAME RETARDANT THERMOPLASTIC, COLOR:BLACK, PINS: PHOS BRONZE  
FINISH: SEE TABLE

WEIGHT: -  
CUSTOMER DRAWING

SCALE: 4:1 SHEET: 1 OF 1 REV: J1

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)  
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)  
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)