



DESIGNED FOR USE WITH		.085 SR CABLE	
CABLE ENTRY DIAMETER		MINIMUM	
HOUSING	.089		
CONTACT	.024		

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
02 ₄	REVISED	1/24/01	[Signature]
B	PER EC 0U20-0692-00	9/24/01	C. Hoang

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 304.1	Temperature Rating -65°C TO +125°C
Frequency Range (GHz) DC to 18	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition D
Volt Rating (VRMS MAX) @ Sea Level 599	Torque 12 - 15 LBS	Shock MIL-STD-202, Method 213, Condition I
VSWR 1.06 + .007 fGHz	Force to Engage and Disengage (In/Lbs MAX) 6.0	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp 200°C
Insertion Loss (dB MAX) .05 √ fGHz	Cable Retention	Moisture Resistance MIL-STD-202, Method 106, Except Step 7b (Vibration) Shall Be Omitted
RF Leakage (dB MIN) -(90 -f(GHz))	Axial Force (Lbs) 60	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Corona, 70,000 Ft (VRMS MIN) 500	Torque (In/Oz) 55	
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 2500	Weight (Grams)	
Contact Resistance (Milliohms MAX)		
Center Contact 1.5		
Outer Contact 2.0		
Cable to Housing 2.0		
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 1500		
I.R.(Megohms MIN) 10,000		

COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON		
FRAC.	DEC.	ANGLES
± 1/64	±.005	± °
DRAWN BY PRB DATE 6/15/67		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
CHECKED BY BWC DATE 7/3/67		
APPD BY GH DATE 7/3/67		
USE ASS'Y PROCEDURE		TITLE OSN STRAIGHT PLUG DIRECT SOLDER ATTACHMENT
NO. AP. 408-04914 (30-002)		SIZE B CODE IDENT NO. 26805
		3001-7985-00 REV 02 ₄
SCALE 4:1		SHEET 1 OF 1

CUSTOMER DRAWING

AMP PART # 1057094-1
SHEET 1 OF 1 REV B

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [8808-1511-001](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [1200690078](#) [1-201144-1](#) [R107003010W](#) [R110A172100](#)