



### Interchangeability

The term interchangeability refers to how accurately thermistors track a nominal resistance curve. In the case of a  $\pm 0.2^{\circ}$ C, through all portions of the interchangeable range, the part is within  $\pm 0.2^{\circ}$ C of the nominal value for that part. This term is sometimes confused with accuracy. Keep in mind the  $\pm 0.2^{\circ}$ C figure only refers to nominal curve; absolute accuracy for thermistor at a measured temperature is significantly better. Contact us directly if you require more information.

# **44100 SERIES**

# **Thermistor Components**

Teflon® sheathed epoxy encapsulated precision interchangeable NTC thermistor utilizing high stability pressed-disk ceramic sensor for use in harsh chemical environments. Sensor is protected by a 2" (51mm) Teflon® sheath for protection from harsh chemicals. One inner lead is sleeved with Teflon® tubing for insulation. A nickel stiffening wire allows shaping of the sheath.

#### **Features**

- Teflon® Sheath for Hostile Environments
- 100 Ohm to 1 MEG Ohm Resistance @ 25°C
- Interchangeability ±0.2°C, 0°C to 70°C
- Good Long Term Stability
- High Sensitivity
- Pressed Disk Ceramic Characteristics
- Thermally Conductive Epoxy Coating
- RoHS Compliance

## **Applications**

- Harsh Chemical Environments
- Moderate Temperature Applications
- Tight Tolerance Applications
- General Applications Requiring Stability
- Applications Requiring Sensing Small Changes in Temperature
- Non-condensing Moisture Environments

## Performance Specifications

|                                                            | Model<br>Number | Ordering Part<br>Number | Zero Power<br>Resistance<br>ohm at 25°C | Beta<br>0- 50°C (K) | Ratio ohm<br>25/125°C | Maximum<br>working<br>temperature | Best storage<br>and working<br>temperature |
|------------------------------------------------------------|-----------------|-------------------------|-----------------------------------------|---------------------|-----------------------|-----------------------------------|--------------------------------------------|
| ±0.2°C<br>Interchange-<br>ability<br>Tolerance<br>0 – 70°C | 44101           | 095311                  | 100                                     | 2854                | 11.49                 | 100°C                             | -80 + 50°C                                 |
|                                                            | 44102           | 095312                  | 300                                     | 3118                | 15.15                 | 100°C                             | -80 + 50°C                                 |
|                                                            | 44103           | 095313                  | 1000                                    | 3271                | 17.33                 | 100°C                             | -80 + 50°C                                 |
|                                                            | 44104           | 095403                  | 2252                                    | 3891                | 29.26                 | 150°C                             | -80 + 120°C                                |
|                                                            | 44105           | 095404                  | 3000                                    | 3891                | 29.26                 | 150°C                             | -80 + 120°C                                |
|                                                            | 44107           | 095406                  | 5000                                    | 3891                | 29.26                 | 150°C                             | -80 + 120°C                                |
|                                                            | 44106           | 095405                  | 10K                                     | 3574                | 23.51                 | 150°C                             | -80 + 120°C                                |
|                                                            | 44108           | 095407                  | 30K                                     | 3810                | 29.15                 | 150°C                             | -80 + 120°C                                |
|                                                            | 44111           | 095408                  | 100K                                    | 3988                | 34.82                 | 150°C                             | -80 + 120°C                                |
|                                                            | 44114           | 095409                  | 300K                                    | 4276                | 46.02                 | 150°C                             | -80 + 120°C                                |
|                                                            | 44115           | 095410                  | 1 meg                                   | 4582                | 61.96                 | 150°C                             | -80 + 120°C                                |

#### **NORTH AMERICA**

Measurement Specialties, Inc., a TE Connectivity Company Tel: 800-522-6752

customercare.ando@te.com

#### **EUROPE**

Measurement Specialties (Europe), Ltd., a TE Connectivity Company Tel: 800-440-5100

customercare.tlse@te.com

#### ASIA

Measurement Specialties (China), Ltd., a TE Connectivity Company

Tel: 0400-820-6015 customercare.chdu@te.com

#### te.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties (MEAS), American Sensor Technologies (AST), TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2016 TE Connectivity Ltd. family of companies All Rights Reserved.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for NTC (Negative Temperature Coefficient) Thermistors category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

118-253FAJ-P01 121-202EAC-P01 123-802EAJ-P01 128-105NDP-Q02 129-202VME-S01 135-503LAD-J01 B57250V2473F560

B57620C472K962 B57620C5103J062 B57621C5102J062 A1004SG22P0 192-103LPR-A01 199-303KAF-A02 30054-4 B57471V2474H062

B57620C5102J062 B57620C5223J062 500-52AA04-101 526-31AA19-104 526-31AN12-202 103AT-5-1P-FT 10K3A542I 111-802EAJ-901

112-103FAG-H02 112-104KAG-B01 11028414-00 111-182CAG-H01 112-103FAF-H01 112-104KBF-F01 118-202CAJ-P01 526-31AA79-102 B57442V5103J62 517-59CL01-202 B57401V2103H62 B57621C5472J62 11032565-00 44015RC 194303KEVA01

NTCACAPE3C90193 B57359V2224J260 B57343V5103J360 NXRT15WB473FA1B040 50070974-003-01 189-602LDR-A01

B57621C5472K062 135-105QAF-J02 B57421V2153J062 B57471V2684H062 B57471V2333H062 126-153YJC-B01