



CONTACT IDENTIFICATION LETTER "B" (LOCATED IN THIS AREA)

9	OBSOLETE	8	2-104257-4	25	7-103644-4
9	OBSOLETE	8	2-104257-3	24	7-103644-3
9	OBSOLETE	8	2-104257-2	23	7-103644-2
9	OBSOLETE	8	2-104257-1	22	7-103644-1
		8	2-104257-0	21	7-103644-0
9	OBSOLETE	8	1-104257-9	20	6-103644-9
9	OBSOLETE	8	1-104257-8	19	6-103644-8
9	OBSOLETE	8	1-104257-7	18	6-103644-7
9	OBSOLETE	8	1-104257-6	17	6-103644-6
9	OBSOLETE	8	1-104257-5	16	6-103644-5
9	OBSOLETE	8	1-104257-4	15	6-103644-4
		8	1-104257-3	14	6-103644-3
		8	1-104257-2	13	6-103644-2
		7	2-104257-4	25	2-103644-4
9	OBSOLETE	7	2-104257-3	24	2-103644-3
9	OBSOLETE	7	2-104257-2	23	2-103644-2
9	OBSOLETE	7	2-104257-1	22	2-103644-1
9	SUPERSEDED BY 7-103644-0	7	2-104257-0	21	2-103644-0
		7	1-104257-9	20	1-103644-9
9	OBSOLETE	7	1-104257-8	19	1-103644-8
		7	1-104257-7	18	1-103644-7
		7	1-104257-6	17	1-103644-6
		7	1-104257-5	16	1-103644-5
		7	1-104257-4	15	1-103644-4
		7	1-104257-3	14	1-103644-3
		7	1-104257-2	13	1-103644-2

SUPERSEDED BY 1-103957-1	1-104257-1	12	1-103644-1
SUPERSEDED BY 1-103957-0	1-104257-0	11	1-103644-0
SUPERSEDED BY 103957-9	104257-9	10	103644-9
SUPERSEDED BY 103957-8	104257-8	9	103644-8
SUPERSEDED BY 103957-7	104257-7	8	103644-7
SUPERSEDED BY 103957-6	104257-6	7	103644-6
SUPERSEDED BY 103957-5	104257-5	6	103644-5
SUPERSEDED BY 103957-4	104257-4	5	103644-4
SUPERSEDED BY 103957-3	104257-3	4	103644-3
SUPERSEDED BY 103957-2	104257-2	3	103644-2
SUPERSEDED BY 103957-1	104257-1	2	103644-1

- 1 CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- 2 USE WITH #22-#26 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- 3 THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 FOR STRIP ASSEMBLIES SEE PART NUMBER 103957
- 6 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE BEAMS)
- 7 FINISH: CONTACTS: .000015 GOLD IN THE CONTACT AREA,.000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA, ALL OVER .000050 NICKEL
- 8 .000015 GOLD IN THE CONTACT AREA,.000050-.000100 MATTE TIN ON THE TERMINATION AREA, ALL OVER .000050 NICKEL
- 9 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	11-4-86		TE Connectivity
DIMENSIONS: INCHES		CHK	11-12-86		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		P de Jong		NAME	
0 PLC ± -		APVD -		RCPT ASSY, AMPMODU MTE, SINGLE ROW,.100 C/L	
1 PLC ± -		PRODUCT SPEC		LATCHED AND POLARIZED,	
2 PLC ± .02		108-25034		FOR NO 22- NO 26 AWG WIRE SIZE	
3 PLC ± .005		APPLICATION SPEC		SIZE	
4 PLC ± -		114-25026		CAGE CODE	
ANGLES ± -		WEIGHT -		DRAWING NO	
FINISH		A2 00779		RESTRICTED TO	
SEE TABLE		C=103644		SCALE	
MATERIAL: HOUSING: FLAME RETARDANT THERMOPLASTIC, COLOR-BLACK		CUSTOMER DRAWING		SHEET 1 of 1	
		SCALE 4:1		REV R2	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009508121](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [68002-116](#) [68016-236H](#) [68648-049](#)